



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

# Journey JavaScript SDK

autotrackClick

7/4/2022

---

## Contents

- 1 Description
- 2 Signature
- 3 Example
- 4 Config (required)
  - 4.1 Example
- 5 AI-400 Config (required)
  - 5.1 Example
  - 5.2 Use events to track outcome value
- 6 Callback (optional)

---

Learn how to configure which click events Genesys Predictive Engagement tracks on your websites. This configuration provides more accurate page tracking information for use in segments and outcomes.

### Important

This article only applies to customers using web chat. If you are a Genesys Cloud CX customer, we encourage you to use the new web messaging feature to replace web chat.

**Feature coming soon:** New customAttributes field

## Description

The `autotrackClick` module tracks when and where a visitor clicks on a webpage. To use `autotrackClick`, configure the click events to track using the following options:

- Config
- Callback

## Signature

```
ac('load', 'autotrackClick', config, [callback]);
```

## Example

```
ac('load', 'autotrackClick', {
  clickEvents: [
    { selector: 'button.bg-green', eventName: 'green_button_clicked' },
    { selector: 'footer *', eventName: 'footer_clicked' }
  ]
}, function () {
  console.log('"autotrackClick" has been loaded');
});
```

---

## Config (required)

**Description:** Identifies an array of click events to track.

**Type:** Object

**Properties:** See the following table.

Name	Description	Type	Status
selector	String that selects elements. For more information, see <a href="https://developer.mozilla.org/en-US/docs/Web/API/Element/matches">https://developer.mozilla.org/en-US/docs/Web/API/Element/matches</a>	String	required
eventName	String used as the event name when an element matching the selector is clicked.	String	required

### Example

```
{
  clickEvents: [
    { selector: 'button.bg-green', eventName: 'green_button_clicked' },
    { selector: 'footer *', eventName: 'footer_clicked' }
  ]
}
```

## Callback (optional)

When a module loads, callback is executed. No arguments pass to the callback.