



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

Designer User's Guide

Callback Availability V2

Contents

- 1 Inputs tab
 - 1.1 Example
- 2 Results tab
 - 2.1 Example



- Administrator

This block checks if there are any available slots for the customer's preferred callback date and time.

Related documentation:

-

This block checks to see if there are any available time slots for the caller's preferred callback date and time, and provides up to three possible time slots to choose from.

Inputs tab

Specify the desired date and time for the callback.

Example

Properties - Callback Availability V2



This block is used to retrieve the scheduled callback availability from Genesys Mobile Services (GMS) for a particular Callback service.

Inputs

Results

Specify the desired date and time for scheduled callback.

Name	Description	Type	Value
Virtual Queue	Callback Virtual Queue	variable ▼	callbackVQ ▼
Desired Day of Week	Desired day of week to schedule callback (0=Sunday, 1=Monday, ... , 6=Saturday)	variable ▼	varDesiredDay ▼
Desired Hour	Desired hour of day to schedule callback (0-23)	variable ▼	varDesiredHour ▼
Desired Minute	Desired minute to schedule callback (0-59)	variable ▼	varDesiredMinute ▼

Results tab

The closest available time slot to the requested callback date and time is returned, while also taking into consideration the Estimated Wait Time (for example, if the current Estimated Wait Time is 30

minutes, the earliest time slot that could be offered is 30 minutes from now). In addition, up to two alternate time slots are also proposed.


Important

The desired day of week, hour, and minute should be collected from the caller in the time zone of the Designer application. For the three closest time slots that are returned, the **Slot x Date**, **Slot x Day of Week**, and **Slot x Time** are all in the time zone of the Designer application, so they can be played as prompts back to the customer to confirm the time, and **Slot x UTC** is in the UTC (Coordinated Universal Time) time zone.

You can use this tab to store the time slot results in variables.

Example

Properties - Callback Availability V2

 This block is used to retrieve the scheduled callback availability from Genesys Mobile Services (GMS) for a particular Callback service.

[Inputs](#) **[Results](#)**

Select the variables to store the results.

The possible values for the outcome variable are:

- 'AVAILABILITY_OK' (if successful)
- undefined (if any error occurs)

Name	Description	Variable
Outcome	Outcome of the query.	<input type="text" value="varRequestResult"/>
Slot 1 Date	Date of first slot (MM/dd)	<input type="text" value="varSlot1Date"/>
Slot 1 Day of Week	Day of week of first slot (0=Sunday, ..., 6=Saturday)	<input type="text" value="varSlot1DayOfWeek"/>
Slot 1 Time	Time of first slot (HH:mm)	<input type="text" value="varSlot1Time"/>
Slot 1 UTC	UTC date-time of first slot to use for booking	<input type="text" value="varSlot1UTC"/>
Slot 2 Date	Date of second slot (MM/dd)	<input type="text"/>
Slot 2 Day of Week	Day of week of second slot (0=Sunday, ..., 6=Saturday)	<input type="text"/>
Slot 2 Time	Time of second slot (HH:mm)	<input type="text"/>