



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

## Designer User's Guide

[Check for Existing Callback V2](#)

---

## Contents

- 1 Inputs tab
  - 1.1 Example
- 2 Results tab
  - 2.1 Example



- Administrator

This block checks if an existing callback already exists for a customer's phone number in the specified virtual queue.

## Related documentation:

### Important

This check is performed separately for each virtual queue. Keep in mind that if a caller is using different virtual queues, they could potentially book multiple callbacks with the same phone number.

## Inputs tab

Provide the **Virtual Queue** and **Phone Number** that are to be checked for existing callbacks.

### Example

#### Properties - Check for Existing Callback V2



This block is used to check if the customer's phone number already has an existing callback scheduled or queued in a particular Callback service in Genesys Mobile Services (GMS).

**Inputs** **Results**

Specify the customer's phone number to check for existing callback. It should be a numeric string including the country dialing code.

Name	Description	Type	Value
Virtual Queue	Callback Virtual Queue	variable ▾	callbackVQ ▾
Phone Number	The phone number to receive the callback	variable ▾	callbackPhoneNumber ▾

## Results tab

If an existing callback with the same phone number is found in the same virtual queue, the **Callback Service ID** associated with the existing callback is returned, along with additional information such as the request date, request time, and so on.

You can use this tab to store this information in variables.

### Example

#### Properties - Check for Existing Callback V2



This block is used to check if the customer's phone number already has an existing callback scheduled or queued in a particular Callback service in Genesys Mobile Services (GMS).

#### Inputs      Results

Select the variables to store the results.

The possible values for the outcome variable are:

- 'CALLBACK\_EXISTS\_ASAP'
- 'CALLBACK\_EXISTS\_SCHEDULED'
- 'CALLBACK\_NOT\_EXIST'
- undefined

Name	Description	Variable
Outcome	Outcome of the query.	checkExistingResult
Callback ID	ID of the existing callback	parentCallbackServiceID
Requested Date	Requested date of the callback in local time zone (if exists)	
Requested Time	Requested time of the callback in local time zone (if exists)	
Requested Day of Week	Requested day of the week (0=Sunday, ..., 6=Saturday) of the callback in local time zone (if exists)	
Upcoming Hours	Number of hours until requested scheduled callback (if exists)	
Upcoming Minutes	Number of minutes (excluding hours) until requested scheduled callback (if exists)	