



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

Service Client API Reference

Configuration namespace

Contents

- 1 Methods
 - 1.1 `getOption`
 - 1.2 `getContextualOption`
- 2 Type definitions
 - 2.1 Section
- 3 Examples
 - 3.1 `getContextualOption()`
 - 3.2 `getOption()`

Learn about the Configuration namespace methods and type definitions in the Service Client API.

Important

Depending on your environment, you might need to contact your Genesys representative to complete the configuration described on this page.

Methods

The Configuration namespace includes the following methods:

- `getOption`
- `getContextualOption`

getOption

Signature	<code>getOption(<i>options</i>, succeeded, failed) → {Array. }</code>								
Description	Get configuration options and values for a specific option name or a subset of options from the [interaction-workspace] section or a custom section.								
Parameters	<table border="1"><thead><tr><th>Name</th><th>Type</th><th>Description</th></tr></thead><tbody><tr><td><code>options</code></td><td>string</td><td>An array of configuration options or sections to return. Unless otherwise specified, the API returns options from the [interaction-workspace] section by default. You can specify</td></tr></tbody></table>	Name	Type	Description	<code>options</code>	string	An array of configuration options or sections to return. Unless otherwise specified, the API returns options from the [interaction-workspace] section by default. You can specify		
Name	Type	Description							
<code>options</code>	string	An array of configuration options or sections to return. Unless otherwise specified, the API returns options from the [interaction-workspace] section by default. You can specify							

Signature	getOption(<i>options</i> , succeeded, failed) → {Array. }								
	<table border="1"> <thead> <tr> <th data-bbox="816 317 1027 369">Name</th> <th data-bbox="1027 317 1239 369">Type</th> <th data-bbox="1239 317 1451 369">Description</th> </tr> </thead> <tbody> <tr> <td data-bbox="816 369 1027 1829"></td> <td data-bbox="1027 369 1239 1829"></td> <td data-bbox="1239 369 1451 1829"> any of the following: <ul style="list-style-type: none"> <li data-bbox="1263 457 1430 793">• A single option: genesys.we.service.configuration.getOption('voice.auto-answer', succeeded, failed) <li data-bbox="1263 814 1430 1283">• A single option in a specific section: genesys.we.service.configuration.getOption('CustomSection/option.customer.code', succeeded, failed) <li data-bbox="1263 1304 1430 1745">• Multiple options: genesys.we.service.configuration.getOption(['voice.auto-answer', 'privilege.email.done'], succeeded, failed) <li data-bbox="1263 1766 1390 1797">• Multiple </td> </tr> </tbody> </table>	Name	Type	Description			any of the following: <ul style="list-style-type: none"> <li data-bbox="1263 457 1430 793">• A single option: genesys.we.service.configuration.getOption('voice.auto-answer', succeeded, failed) <li data-bbox="1263 814 1430 1283">• A single option in a specific section: genesys.we.service.configuration.getOption('CustomSection/option.customer.code', succeeded, failed) <li data-bbox="1263 1304 1430 1745">• Multiple options: genesys.we.service.configuration.getOption(['voice.auto-answer', 'privilege.email.done'], succeeded, failed) <li data-bbox="1263 1766 1390 1797">• Multiple 		
Name	Type	Description							
		any of the following: <ul style="list-style-type: none"> <li data-bbox="1263 457 1430 793">• A single option: genesys.we.service.configuration.getOption('voice.auto-answer', succeeded, failed) <li data-bbox="1263 814 1430 1283">• A single option in a specific section: genesys.we.service.configuration.getOption('CustomSection/option.customer.code', succeeded, failed) <li data-bbox="1263 1304 1430 1745">• Multiple options: genesys.we.service.configuration.getOption(['voice.auto-answer', 'privilege.email.done'], succeeded, failed) <li data-bbox="1263 1766 1390 1797">• Multiple 							

Signature	getOption(<i>options</i> , succeeded, failed) → {Array. }														
	<table border="1"> <thead> <tr> <th data-bbox="816 317 1027 369">Name</th> <th data-bbox="1027 317 1239 369">Type</th> <th data-bbox="1239 317 1451 369">Description</th> </tr> </thead> <tbody> <tr> <td data-bbox="816 369 1027 1623"></td> <td data-bbox="1027 369 1239 1623"></td> <td data-bbox="1239 369 1451 1623"> <p>options in different sections: genesys.w we.servic e.configu ration.ge tOption(['privileg e.*', 'CustomSe ction/ option.cu stom.cust omer.code '], succeeded , failed)</p> <p>You can use an asterisk '*' as a wildcard, but only at the end of each word. For example:</p> <ul style="list-style-type: none"> • voice.* • voice.auto* • sipendpoint.* • CustomAPI/test.* <p>You cannot use an asterisk at the start of an option or section. For example, the following values are not allowed:</p> <ul style="list-style-type: none"> • *.mark-done • *.auto </td> </tr> <tr> <td data-bbox="816 1623 1027 1745">succeeded</td> <td data-bbox="1027 1623 1239 1745">function</td> <td data-bbox="1239 1623 1451 1745">A function called when the operation succeeds.</td> </tr> <tr> <td data-bbox="816 1745 1027 1818">failed</td> <td data-bbox="1027 1745 1239 1818">function</td> <td data-bbox="1239 1745 1451 1818">A function called when</td> </tr> </tbody> </table>	Name	Type	Description			<p>options in different sections: genesys.w we.servic e.configu ration.ge tOption(['privileg e.*', 'CustomSe ction/ option.cu stom.cust omer.code '], succeeded , failed)</p> <p>You can use an asterisk '*' as a wildcard, but only at the end of each word. For example:</p> <ul style="list-style-type: none"> • voice.* • voice.auto* • sipendpoint.* • CustomAPI/test.* <p>You cannot use an asterisk at the start of an option or section. For example, the following values are not allowed:</p> <ul style="list-style-type: none"> • *.mark-done • *.auto 	succeeded	function	A function called when the operation succeeds.	failed	function	A function called when		
Name	Type	Description													
		<p>options in different sections: genesys.w we.servic e.configu ration.ge tOption(['privileg e.*', 'CustomSe ction/ option.cu stom.cust omer.code '], succeeded , failed)</p> <p>You can use an asterisk '*' as a wildcard, but only at the end of each word. For example:</p> <ul style="list-style-type: none"> • voice.* • voice.auto* • sipendpoint.* • CustomAPI/test.* <p>You cannot use an asterisk at the start of an option or section. For example, the following values are not allowed:</p> <ul style="list-style-type: none"> • *.mark-done • *.auto 													
succeeded	function	A function called when the operation succeeds.													
failed	function	A function called when													
	succeeded	function	A function called when the operation succeeds.												
	failed	function	A function called when												

Signature	getOption(<i>options</i> , succeeded, failed) → {Array. }		
	Name	Type	Description
			the operation fails.
Returns	Array.		

getContextualOption

Signature	getContextualOption(<i>options</i> , <i>interactionId</i> , succeeded, failed) → {Array. }		
Description	<p>Get configuration options and values in the context of this interaction when they are overridden by a routing strategy. If the interaction is not found or this parameter is missing, the API throws an exception. Note: The getContextualOption method can be applied to any option, even if the option doesn't support overriding options with a routing strategy in Workspace Web Edition. Only Workspace Web Edition options with the following text in their descriptions can be overridden by a routing strategy: "This option can be overridden by a routing strategy as described in this Configuration Guide." Using the getContextualOption method doesn't interfere with how Workspace Web Edition handles options.</p>		
Parameters	Name	Type	Description
	options	string	<p>An option or array of options and their values. Unless otherwise specified, the API returns options from the [interaction-workspace] section by default. You can specify any of the following:</p> <ul style="list-style-type: none"> A single option by name:

Signature	<code>getContextualOption(options, interactionId, succeeded, failed) → {Array.}</code>		
	Name	Type	Description
			<p>genesys.we.service.configuration.getOption('voice.auto-answer', succeeded, failed)</p> <ul style="list-style-type: none"> • A subset of options defined by '*': • A subset of options in a specific section: genesys.we.service.configuration.getOption('interaction-workspace / interaction.case-data.*', succeeded, failed) <p>You can use an asterisk '*' as a wildcard, but only at the end of each word. For example:</p> <ul style="list-style-type: none"> • voice.* • voice.auto* • sipendpoint.* • CustomAPI/test.* <p>You cannot use an asterisk at the</p>

Signature	getContextualOption(<i>options</i> , <i>interactionId</i> , succeeded, failed) → {Array. }		
	Name	Type	Description
			start of an option or section. For example, the following values are not allowed: <ul style="list-style-type: none"> • *.mark-done • *.auto
	interactionId	string	The unique identifier for the interaction.
	succeeded	function	A function called when the operation succeeds.
	failed	function	A function called when the operation fails.
Returns	Array.		

Type definitions

The Configuration namespace includes the following object types:

- Section

Section

Description	Represents the JSON structure of a configuration section. Each section includes a list of key/value pairs for the matching option(s).		
Type	Object		
Properties	Name	Type	Description
	name	string	The name of the configuration option.

Description	Represents the JSON structure of a configuration section. Each section includes a list of key/value pairs for the matching option(s).								
	<table border="1"> <thead> <tr> <th data-bbox="818 350 1032 401">Name</th> <th data-bbox="1037 350 1235 401">Type</th> <th data-bbox="1240 350 1450 401">Description</th> </tr> </thead> <tbody> <tr> <td data-bbox="818 407 1032 520">value</td> <td data-bbox="1037 407 1235 520">string or array of strings</td> <td data-bbox="1240 407 1450 520">The value of the configuration option.</td> </tr> </tbody> </table>			Name	Type	Description	value	string or array of strings	The value of the configuration option.
Name	Type	Description							
value	string or array of strings	The value of the configuration option.							

Examples

Consider the following scenario:

1. You set `interaction-workspace/interaction.case-data.frame-color="#FFBA00"`.
2. You also set the override option key: `interaction-workspace/interaction.override-option-key="IW_OverrideOptions"`.
3. An interaction arrives with the attached data `IW_OverrideOptions="CaseDataColor"`.
4. The transaction object `"CaseDataColor"` annex has the option `interaction-workspace/interaction.case-data.frame-color="#FF00088"`.

Here's how this scenario would look for each of the Configuration namespace methods:

getContextualOption()

Use `getContextualOption()` to get the option:

```
genesys.wwe.service.configuration.getContextualOption("interaction.case-data.frame-color",
"1", succeeded, failed)
```

You receive this response:

```
{
  "request": "configuration.getContextualOption",
  "data": {
    "interaction-workspace": {
      "interaction.case-data.frame-color": "#FF008000"
    }
  },
  "userAgent": "WWE Server",
  "protocolVersion": 2
}
```

If the interaction isn't found, the failed callback receives this response:

```
{
  "request": "configuration.getContextualOption",
  "errorMessage": "Error: Interaction not found.",
  "userAgent": "WWE Server",
  "protocolVersion": 2
}
```

```
}
```

getOption()

Use `getOption()` to get the option::

```
genesys.wwe.service.configuration.getOption("interaction.case-data.frame-color", succeeded,  
failed)
```

The response includes the original default value of the option instead of the overridden value:

```
{  
  "request": "configuration.getOption",  
  "data": {  
    "interaction-workspace": {  
      "interaction.case-data.frame-color": "#FFBA00"  
    }  
  },  
  "userAgent": "WWE Server",  
  "protocolVersion": 2  
}
```