



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

Service Client API Reference

Email namespace

Contents

- [1 Methods](#)
 - [1.1 create](#)

Learn about the Email namespace methods in the Service Client API.

Methods

The Email namespace includes the following methods:

- create

create

Signature	<code>create(destination, userData, succeeded, failed)</code>																				
Description	Creates a new empty email.																				
Parameters	<table border="1"><thead><tr><th>Name</th><th>Type</th><th>Argument</th><th>Description</th></tr></thead><tbody><tr><td>destination</td><td>string</td><td></td><td>The destination address for the email.</td></tr><tr><td>userData</td><td>object</td><td></td><td>The attached user data key/value object that is updated with each interaction event.</td></tr><tr><td>succeeded</td><td>function</td><td></td><td>A function called when the operation succeeds.</td></tr><tr><td>failed</td><td>function</td><td></td><td>A function called when the operation fails.</td></tr></tbody></table>	Name	Type	Argument	Description	destination	string		The destination address for the email.	userData	object		The attached user data key/value object that is updated with each interaction event.	succeeded	function		A function called when the operation succeeds.	failed	function		A function called when the operation fails.
	Name	Type	Argument	Description																	
	destination	string		The destination address for the email.																	
	userData	object		The attached user data key/value object that is updated with each interaction event.																	
	succeeded	function		A function called when the operation succeeds.																	
failed	function		A function called when the operation fails.																		