



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

Genesys Multicloud CX Web-based API Reference

Authentication API

Contents

- [1 Base path: /auth/v3](#)

Base path: /auth/v3

POST	/change-password Change password
------	-------------------------------------

Change the user's password.

Parameters

Name	Default	Description	Parameter Type	Data Type	Required														
Authorization	bearer	The OAuth 2 bearer access token you received from /auth/v3/oauth/token. For example: Authorization: bearer a4b5da75-a584-4053-9227-0f0ab23ff06e	header	string															
request		Request	body		true														
<pre>{ "data": { "newPassword": "string", "oldPassword": "string", "userName": "string" }, "operationId": "string" }</pre>			<table><thead><tr><th colspan="2">ChangePasswordOperation</th></tr></thead><tbody><tr><td>newPassword</td><td>(string, required):</td></tr><tr><td>oldPassword</td><td>(string, required):</td></tr><tr><td>userName</td><td>(string, optional):</td></tr><tr><th colspan="2">ApiRequestOfChangePasswordOperation</th></tr><tr><td>data</td><td>(ChangePasswordOperation, required):</td></tr><tr><td>operationId</td><td>(string, optional): Used for asynchronous operations to map request and response</td></tr></tbody></table>			ChangePasswordOperation		newPassword	(string, required):	oldPassword	(string, required):	userName	(string, optional):	ApiRequestOfChangePasswordOperation		data	(ChangePasswordOperation, required):	operationId	(string, optional): Used for asynchronous operations to map request and response
ChangePasswordOperation																			
newPassword	(string, required):																		
oldPassword	(string, required):																		
userName	(string, optional):																		
ApiRequestOfChangePasswordOperation																			
data	(ChangePasswordOperation, required):																		
operationId	(string, optional): Used for asynchronous operations to map request and response																		

Responses

Code	Reason
200	Ok

Code	Reason																						
<pre>{ "data": { }, "errors": [{ "status": { "code": 0, "detail": { }, "message": "string" } }], "path": "string", "status": { "code": 0, "detail": { }, "message": "string" } }</pre>	<table border="1"> <tr> <td colspan="2">ResponseStatus</td> </tr> <tr> <td>code</td> <td>(integer):</td> </tr> <tr> <td>detail</td> <td>(object):</td> </tr> <tr> <td>message</td> <td>(string):</td> </tr> <tr> <td colspan="2">ErrorResponse</td> </tr> <tr> <td>status</td> <td>(ResponseStatus):</td> </tr> <tr> <td colspan="2">ErrorResponse</td> </tr> <tr> <td>data</td> <td>(object):</td> </tr> <tr> <td>errors</td> <td>(array:ErrorResponse):</td> </tr> <tr> <td>path</td> <td>(string):</td> </tr> <tr> <td>status</td> <td>(ResponseStatus):</td> </tr> </table>	ResponseStatus		code	(integer):	detail	(object):	message	(string):	ErrorResponse		status	(ResponseStatus):	ErrorResponse		data	(object):	errors	(array:ErrorResponse):	path	(string):	status	(ResponseStatus):
ResponseStatus																							
code	(integer):																						
detail	(object):																						
message	(string):																						
ErrorResponse																							
status	(ResponseStatus):																						
ErrorResponse																							
data	(object):																						
errors	(array:ErrorResponse):																						
path	(string):																						
status	(ResponseStatus):																						
403	Unable to update password																						
503	Service unavailable																						

Usage

```
curl -X POST
-H "x-api-key: your_API_key"
-H "Content-Type: application/json"
-d '{
  "data": {
    "newPassword": "string",
    "oldPassword": "string",
    "userName": "string"
  },
  "operationId": "string"
}'
"https://api-demo.com/auth/v3/change-password?"
```

GET	/jwt-userinfo Get user information by access token. The information will be encoded as jwt and returned in 'X-GWS-User' header
-----	---

Get information about a user by their OAuth 2 access token.

Parameters

Name	Default	Description	Parameter Type	Data Type	Required
Authorization		The OAuth 2 bearer access token. For example: Authorization: bearer	header	string	true

Name	Default	Description	Parameter Type	Data Type	Required
		a4b5da75 - a584 - 4053 - 9227 - 0f0ab23ff06e			

Responses

Code	Reason																						
200	Ok																						
<pre> { "data": { }, "errors": [{ "status": { "code": 0, "detail": { }, "message": "string" } }], "path": "string", "status": { "code": 0, "detail": { }, "message": "string" } } </pre>	<table border="1"> <thead> <tr> <th colspan="2">ResponseStatus</th> </tr> </thead> <tbody> <tr> <td>code</td> <td>(integer):</td> </tr> <tr> <td>detail</td> <td>(object):</td> </tr> <tr> <td>message</td> <td>(string):</td> </tr> <tr> <th colspan="2">ErrorResponse</th> </tr> <tr> <td>status</td> <td>(ResponseStatus):</td> </tr> <tr> <th colspan="2">ApiResponse</th> </tr> <tr> <td>data</td> <td>(object):</td> </tr> <tr> <td>errors</td> <td>(array:ErrorResponse):</td> </tr> <tr> <td>path</td> <td>(string):</td> </tr> <tr> <td>status</td> <td>(ResponseStatus):</td> </tr> </tbody> </table>	ResponseStatus		code	(integer):	detail	(object):	message	(string):	ErrorResponse		status	(ResponseStatus):	ApiResponse		data	(object):	errors	(array:ErrorResponse):	path	(string):	status	(ResponseStatus):
ResponseStatus																							
code	(integer):																						
detail	(object):																						
message	(string):																						
ErrorResponse																							
status	(ResponseStatus):																						
ApiResponse																							
data	(object):																						
errors	(array:ErrorResponse):																						
path	(string):																						
status	(ResponseStatus):																						

Usage

```

curl -X GET
-H "x-api-key: your_API_key"
-H "Content-Type: application/json"

```

"https://api-demo.com/auth/v3/jwt-userinfo?"

GET	/oauth/authorize Perform authorization
-----	---

Perform authorization for the Authorization Code Grant type, which is currently the only type supported by the Authentication API. For more information, see [Authorization Endpoint](#). **Note:** For the optional scope parameter, the API supports only the * value.

Parameters

Name	Default	Description	Parameter Type	Data Type	Required
Authorization		Basic authorization. For example: Authorization:	header	string	

Name	Default	Description	Parameter Type	Data Type	Required
		Basic Y3...MQ==			
client_id		The ID of the application or service that is registered as the client. You'll need to get this value from your Engage Cloud representative.	query	string	true
hideTenant	false	Hide the tenant field in the UI for Authorization Code Grant.	query	boolean	
redirect_uri		The URI that you want users to be redirected to after entering valid credentials during an Implicit or Authorization Code grant. The Authentication API includes this as part of the URI it returns in the 'Location' header.	query	string	true
response_type		The response type to let the Authentication API know which grant flow you're using. Possible values are code for Authorization Code Grant or token for Implicit Grant. For more information about this parameter, see Response Type.	query	string	true

Name	Default	Description	Parameter Type	Data Type	Required
scope		The scope of the access request. The Authentication API supports only the * value.	query	string	

Responses

Code	Reason
302	Found
"string"	
401	Unauthorized

Usage

```
curl -X GET
-H "x-api-key: your_API_key"
-H "Content-Type: application/json"
```

```
"https://api-demo.com/auth/v3/oauth/authorize?client_id=string&hideTenant=true&redirect_uri=string&response_type=string>ope=string"
```

POST	/oauth/token Retrieve access token
------	---------------------------------------

Retrieve an access token for the Authorization Code Grant type, which is which is currently the only type supported by the Authentication API. For more information, see Token Endpoint. **Note:** For the optional scope parameter, the API supports only the * value.

Parameters

Name	Default	Description	Parameter Type	Data Type	Required
Accept		The media type the Authentication API should use for the response. For example: Accept: application/x-www-form-urlencoded	header	string	
Authorization		Basic authorization. For example:	header	string	

Name	Default	Description	Parameter Type	Data Type	Required
		Authorization: Basic Y3..MQ==			
client_id		The ID of the application or service that is registered as the client. You'll need to get this value from your Engage Cloud representative.	formData	string	
code		Authorization code, see Access Token Request for details.	formData	string	
grant_type		The grant type you use to implement authentication.	formData	string	true
password		The agent's password.	formData	string	
refresh_token		See Refresh Token for details.	formData	string	
scope		The scope of the access request. The Authentication API supports only the * value.	formData	string	
username		The agent's username.	formData	string	

Responses

Code	Reason						
200	Ok						
<pre>{ "access_token": "string", "expires_in": 0, "refresh_token": "string", "scope": "string", "token_type": "string" }</pre>	<table border="1"> <thead> <tr> <th colspan="2">DefaultOAuth2AccessToken</th> </tr> </thead> <tbody> <tr> <td>access_token</td> <td>(string): The access token.</td> </tr> <tr> <td>expires_in</td> <td>(integer):</td> </tr> </tbody> </table>	DefaultOAuth2AccessToken		access_token	(string): The access token.	expires_in	(integer):
DefaultOAuth2AccessToken							
access_token	(string): The access token.						
expires_in	(integer):						

Code	Reason												
	<table border="1"> <tr> <td data-bbox="820 304 1128 409"></td> <td data-bbox="1136 304 1445 409">The time, in seconds, before the token expiration.</td> </tr> <tr> <td data-bbox="820 409 1128 514">refresh_token</td> <td data-bbox="1136 409 1445 514">(string): The refresh token.</td> </tr> <tr> <td data-bbox="820 514 1128 619">scope</td> <td data-bbox="1136 514 1445 619">(string): The scope of the token.</td> </tr> <tr> <td data-bbox="820 619 1128 766">token_type</td> <td data-bbox="1136 619 1445 766">(string): The type of access token — always 'bearer'.</td> </tr> </table>		The time, in seconds, before the token expiration.	refresh_token	(string): The refresh token.	scope	(string): The scope of the token.	token_type	(string): The type of access token — always 'bearer'.				
	The time, in seconds, before the token expiration.												
refresh_token	(string): The refresh token.												
scope	(string): The scope of the token.												
token_type	(string): The type of access token — always 'bearer'.												
400	Error as specified by standard (username/password is wrong, for example)												
<pre data-bbox="186 934 495 1144"> { "status": { "code": 0, "detail": { }, "message": "string" } } </pre>	<table border="1"> <tr> <td colspan="2" data-bbox="820 913 1128 955">ResponseStatus</td> </tr> <tr> <td data-bbox="820 955 1128 997">code</td> <td data-bbox="1136 955 1445 997">(integer):</td> </tr> <tr> <td data-bbox="820 997 1128 1039">detail</td> <td data-bbox="1136 997 1445 1039">(object):</td> </tr> <tr> <td data-bbox="820 1039 1128 1081">message</td> <td data-bbox="1136 1039 1445 1081">(string):</td> </tr> <tr> <td colspan="2" data-bbox="820 1081 1128 1123">ErrorResponse</td> </tr> <tr> <td data-bbox="820 1123 1128 1165">status</td> <td data-bbox="1136 1123 1445 1165">(ResponseStatus):</td> </tr> </table>	ResponseStatus		code	(integer):	detail	(object):	message	(string):	ErrorResponse		status	(ResponseStatus):
ResponseStatus													
code	(integer):												
detail	(object):												
message	(string):												
ErrorResponse													
status	(ResponseStatus):												
401	Unauthorized												
<pre data-bbox="186 1312 495 1522"> { "status": { "code": 0, "detail": { }, "message": "string" } } </pre>	<table border="1"> <tr> <td colspan="2" data-bbox="820 1291 1128 1333">ResponseStatus</td> </tr> <tr> <td data-bbox="820 1333 1128 1375">code</td> <td data-bbox="1136 1333 1445 1375">(integer):</td> </tr> <tr> <td data-bbox="820 1375 1128 1417">detail</td> <td data-bbox="1136 1375 1445 1417">(object):</td> </tr> <tr> <td data-bbox="820 1417 1128 1459">message</td> <td data-bbox="1136 1417 1445 1459">(string):</td> </tr> <tr> <td colspan="2" data-bbox="820 1459 1128 1501">ErrorResponse</td> </tr> <tr> <td data-bbox="820 1501 1128 1543">status</td> <td data-bbox="1136 1501 1445 1543">(ResponseStatus):</td> </tr> </table>	ResponseStatus		code	(integer):	detail	(object):	message	(string):	ErrorResponse		status	(ResponseStatus):
ResponseStatus													
code	(integer):												
detail	(object):												
message	(string):												
ErrorResponse													
status	(ResponseStatus):												
403	Forbidden												
<pre data-bbox="186 1669 397 1795"> { "status": { "code": 0, "detail": { }, }, } </pre>	<table border="1"> <tr> <td colspan="2" data-bbox="820 1669 1128 1711">ResponseStatus</td> </tr> <tr> <td data-bbox="820 1711 1128 1753">code</td> <td data-bbox="1136 1711 1445 1753">(integer):</td> </tr> <tr> <td data-bbox="820 1753 1128 1795">detail</td> <td data-bbox="1136 1753 1445 1795">(object):</td> </tr> </table>	ResponseStatus		code	(integer):	detail	(object):						
ResponseStatus													
code	(integer):												
detail	(object):												

Code	Reason						
<pre> { "message": "string" } </pre>	<table border="1"> <tr> <td>message</td> <td>(string):</td> </tr> <tr> <td colspan="2">ErrorResponse</td> </tr> <tr> <td>status</td> <td>(ResponseStatus):</td> </tr> </table>	message	(string):	ErrorResponse		status	(ResponseStatus):
message	(string):						
ErrorResponse							
status	(ResponseStatus):						
503	Service unavailable						

Usage

```

curl -X POST
-H "x-api-key: your_API_key"
-H "Content-Type: application/json"

```

"https://api-demo.com/auth/v3/oauth/token?"

GET	/openid/userinfo Get OpenID user information by access token
-----	---

Get information about a user by their OAuth 2 access token.

Parameters

Name	Default	Description	Parameter Type	Data Type	Required
Authorization		The OAuth 2 bearer access token you received from /auth/v3/oauth/token. For example: Authorization: bearer a4b5da75-a584-4053-9227-0f0ab23ff06e	header	string	true

Responses

Code	Reason										
200	Ok										
<pre> { "aud": "string", "authorities": [{ "name": "string", "privileges": [] }], "contact_center_id": "string", "dbid": 0, </pre>	<table border="1"> <tr> <td colspan="2">UserRole</td> </tr> <tr> <td>name</td> <td>(string):</td> </tr> <tr> <td>privileges</td> <td>(array:string):</td> </tr> <tr> <td colspan="2">OpenIdUserInfo</td> </tr> <tr> <td>aud</td> <td>(string): OpenID Connect 'aud' claim. This is present if user authenticated with openid scope.</td> </tr> </table>	UserRole		name	(string):	privileges	(array:string):	OpenIdUserInfo		aud	(string): OpenID Connect 'aud' claim. This is present if user authenticated with openid scope.
UserRole											
name	(string):										
privileges	(array:string):										
OpenIdUserInfo											
aud	(string): OpenID Connect 'aud' claim. This is present if user authenticated with openid scope.										

Code	Reason	
<pre> "email": "string", "environment_id": "string", "family_name": "string", "given_name": "string", "properties": { "": "" }, "sub": "string", "user_name": "string" } </pre>	<p>authorities</p>	<p>(array:UserRole): Authorities assigned to the user.</p>
	<p>contact_center_id</p>	<p>(string): OpenID Connect 'aud' claim. This is present if user authenticated with openid scope.</p>
	<p>dbid</p>	<p>(integer): The DBID of the corresponding user record in Configuration Server. This is present if the user belongs to a contact center.</p>
	<p>email</p>	<p>(string): OpenID Connect 'email' claim. This is present if user authenticated with openid scope.</p>
	<p>environment_id</p>	<p>(string): OpenID Connect 'environment_id' claim. This is present if user authenticated with openid scope.</p>
	<p>family_name</p>	<p>(string): OpenID Connect 'family_name' (last name) claim. This is present if user authenticated with openid scope.</p>
	<p>given_name</p>	<p>(string): OpenID Connect 'given_name' (first name) claim. This is present if user authenticated with openid scope.</p>
	<p>properties</p>	<p>(object): The user's properties</p>
	<p>sub</p>	<p>(string): OpenID Connect 'sub' claim. This is present if user</p>

Code	Reason				
	<table border="1"> <tr> <td></td> <td>authenticated with openid scope.</td> </tr> <tr> <td>user_name</td> <td>(string): OpenID Connect 'aud' claim. This is present if user authenticated with openid scope.</td> </tr> </table>		authenticated with openid scope.	user_name	(string): OpenID Connect 'aud' claim. This is present if user authenticated with openid scope.
	authenticated with openid scope.				
user_name	(string): OpenID Connect 'aud' claim. This is present if user authenticated with openid scope.				
401	Unauthorized				
503	Service unavailable				

Usage

```
curl -X GET
-H "x-api-key: your_API_key"
-H "Content-Type: application/json"

"https://api-demo.com/auth/v3/openid/userinfo?"
```

GET	/ping Check connection
-----	---------------------------

Return 200 if user is authenticated otherwise 403.

Responses

Code	Reason																						
200	Ok																						
<pre>{ "data": { }, "errors": [{ "status": { "code": 0, "detail": { }, "message": "string" } }], "path": "string", "status": { "code": 0, "detail": { }, "message": "string" } }</pre>	<table border="1"> <tr> <td colspan="2">ResponseStatus</td> </tr> <tr> <td>code</td> <td>(integer):</td> </tr> <tr> <td>detail</td> <td>(object):</td> </tr> <tr> <td>message</td> <td>(string):</td> </tr> <tr> <td colspan="2">ErrorResponse</td> </tr> <tr> <td>status</td> <td>(ResponseStatus):</td> </tr> <tr> <td colspan="2">ApiResponse</td> </tr> <tr> <td>data</td> <td>(object):</td> </tr> <tr> <td>errors</td> <td>(array:ErrorResponse):</td> </tr> <tr> <td>path</td> <td>(string):</td> </tr> <tr> <td>status</td> <td>(ResponseStatus):</td> </tr> </table>	ResponseStatus		code	(integer):	detail	(object):	message	(string):	ErrorResponse		status	(ResponseStatus):	ApiResponse		data	(object):	errors	(array:ErrorResponse):	path	(string):	status	(ResponseStatus):
ResponseStatus																							
code	(integer):																						
detail	(object):																						
message	(string):																						
ErrorResponse																							
status	(ResponseStatus):																						
ApiResponse																							
data	(object):																						
errors	(array:ErrorResponse):																						
path	(string):																						
status	(ResponseStatus):																						

Code	Reason
403	Prohibited
503	Service unavailable

Usage

```
curl -X GET
-H "x-api-key: your_API_key"
-H "Content-Type: application/json"
```

```
"https://api-demo.com/auth/v3/ping?"
```

GET	/sign-out Sign-out a logged in user
-----	--

Sign-out the current user and invalidate either the current token or all tokens associated with the user.

Parameters

Name	Default	Description	Parameter Type	Data Type	Required
Authorization		The OAuth 2 bearer access token you received from /auth/v3/oauth/token. For example: Authorization: bearer a4b5da75-a584-4053-9227-0f0ab23ff06e	header	string	true
global		Specifies whether to invalidate all tokens for the current user (true) or only the current token (false).	query	boolean	
redirectUri		Specifies the URI where the browser is redirected after sign-out is successful.	query	string	

Responses

Code	Reason
200	Ok
{	ResponseStatus

Code	Reason																				
<pre> "data": { }, "errors": [{ "status": { "code": 0, "detail": { }, "message": "string" } }], "path": "string", "status": { "code": 0, "detail": { }, "message": "string" } } </pre>	<table border="1"> <tr> <td>code</td> <td>(integer):</td> </tr> <tr> <td>detail</td> <td>(object):</td> </tr> <tr> <td>message</td> <td>(string):</td> </tr> <tr> <td>ErrorResponse</td> <td></td> </tr> <tr> <td>status</td> <td>(ResponseStatus):</td> </tr> <tr> <td>ApiResponse</td> <td></td> </tr> <tr> <td>data</td> <td>(object):</td> </tr> <tr> <td>errors</td> <td>(array:ErrorResponse):</td> </tr> <tr> <td>path</td> <td>(string):</td> </tr> <tr> <td>status</td> <td>(ResponseStatus):</td> </tr> </table>	code	(integer):	detail	(object):	message	(string):	ErrorResponse		status	(ResponseStatus):	ApiResponse		data	(object):	errors	(array:ErrorResponse):	path	(string):	status	(ResponseStatus):
code	(integer):																				
detail	(object):																				
message	(string):																				
ErrorResponse																					
status	(ResponseStatus):																				
ApiResponse																					
data	(object):																				
errors	(array:ErrorResponse):																				
path	(string):																				
status	(ResponseStatus):																				
401	Unauthorized																				
503	Service unavailable																				

Usage

```

curl -X GET
-H "x-api-key: your_API_key"
-H "Content-Type: application/json"

```

"https://api-demo.com/auth/v3/sign-out?global=true&redirectUri=string"

POST	/sign-out Sign-out a logged in user
------	--

Sign-out the current user and invalidate either the current token or all tokens associated with the user.

Parameters

Name	Default	Description	Parameter Type	Data Type	Required
Authorization		The OAuth 2 bearer access token you received from /auth/v3/oauth/token. For example: Authorization: bearer a4b5da75-a584-4053-9227-0f0ab23ff06e	header	string	true
global		Specifies whether to	query	boolean	

Name	Default	Description	Parameter Type	Data Type	Required
		invalidate all tokens for the current user (true) or only the current token (false).			

Responses

Code	Reason																						
200	Ok																						
<pre> { "data": { }, "errors": [{ "status": { "code": 0, "detail": { }, "message": "string" } }], "path": "string", "status": { "code": 0, "detail": { }, "message": "string" } } </pre>	<table border="1"> <thead> <tr> <th colspan="2">ResponseStatus</th> </tr> </thead> <tbody> <tr> <td>code</td> <td>(integer):</td> </tr> <tr> <td>detail</td> <td>(object):</td> </tr> <tr> <td>message</td> <td>(string):</td> </tr> <tr> <th colspan="2">ErrorResponse</th> </tr> <tr> <td>status</td> <td>(ResponseStatus):</td> </tr> <tr> <th colspan="2">ApiResponse</th> </tr> <tr> <td>data</td> <td>(object):</td> </tr> <tr> <td>errors</td> <td>(array:ErrorResponse):</td> </tr> <tr> <td>path</td> <td>(string):</td> </tr> <tr> <td>status</td> <td>(ResponseStatus):</td> </tr> </tbody> </table>	ResponseStatus		code	(integer):	detail	(object):	message	(string):	ErrorResponse		status	(ResponseStatus):	ApiResponse		data	(object):	errors	(array:ErrorResponse):	path	(string):	status	(ResponseStatus):
ResponseStatus																							
code	(integer):																						
detail	(object):																						
message	(string):																						
ErrorResponse																							
status	(ResponseStatus):																						
ApiResponse																							
data	(object):																						
errors	(array:ErrorResponse):																						
path	(string):																						
status	(ResponseStatus):																						
401	Unauthorized																						
503	Service unavailable																						

Usage

```

curl -X POST
-H "x-api-key: your_API_key"
-H "Content-Type: application/json"

```

"https://api-demo.com/auth/v3/sign-out?global=true"

GET	/userinfo Get user information by access token
-----	---

Get information about a user by their OAuth 2 access token.

Parameters

Name	Default	Description	Parameter Type	Data Type	Required
Authorization		The OAuth 2 bearer access token. For example: Authorization: bearer a4b5da75-a584-4053-9227-0f0ab23ff06e	header	string	true

Responses

Code	Reason																				
200	Ok																				
<pre>{ "authorities": [{ "name": "string", "privileges": [] }], "cmeUserName": "string", "contactCenterId": "string", "dbid": 0, "environmentId": "string", "loginName": "string", "properties": { "": "" }, "username": "string" }</pre>	<table border="1"> <thead> <tr> <th colspan="2">UserRole</th> </tr> </thead> <tbody> <tr> <td>name</td> <td>(string):</td> </tr> <tr> <td>privileges</td> <td>(array:string):</td> </tr> <tr> <th colspan="2">CloudUserDetails</th> </tr> <tr> <td>authorities</td> <td>(array:UserRole): Authorities assigned to the user.</td> </tr> <tr> <td>cmeUserName</td> <td>(string): The username in Configuration Server. This property is not set for users who aren't in Configuration Server (for example, applications/services, cloud system admin and so on.)</td> </tr> <tr> <td>contactCenterId</td> <td>(string): The ID of the contact center the user belongs to (if any).</td> </tr> <tr> <td>dbid</td> <td>(integer): The DBID of the corresponding user record in Configuration Server. This is present if the user belongs to a contact center.</td> </tr> <tr> <td>environmentId</td> <td>(string): The ID of the Genesys environment the user belongs to (if any).</td> </tr> <tr> <td>loginName</td> <td>(string):</td> </tr> </tbody> </table>	UserRole		name	(string):	privileges	(array:string):	CloudUserDetails		authorities	(array:UserRole): Authorities assigned to the user.	cmeUserName	(string): The username in Configuration Server. This property is not set for users who aren't in Configuration Server (for example, applications/services, cloud system admin and so on.)	contactCenterId	(string): The ID of the contact center the user belongs to (if any).	dbid	(integer): The DBID of the corresponding user record in Configuration Server. This is present if the user belongs to a contact center.	environmentId	(string): The ID of the Genesys environment the user belongs to (if any).	loginName	(string):
UserRole																					
name	(string):																				
privileges	(array:string):																				
CloudUserDetails																					
authorities	(array:UserRole): Authorities assigned to the user.																				
cmeUserName	(string): The username in Configuration Server. This property is not set for users who aren't in Configuration Server (for example, applications/services, cloud system admin and so on.)																				
contactCenterId	(string): The ID of the contact center the user belongs to (if any).																				
dbid	(integer): The DBID of the corresponding user record in Configuration Server. This is present if the user belongs to a contact center.																				
environmentId	(string): The ID of the Genesys environment the user belongs to (if any).																				
loginName	(string):																				

Code	Reason						
	<table border="1"> <tr> <td data-bbox="813 281 1122 533"></td> <td data-bbox="1122 281 1451 533">The username in Configuration Server. This property is not set for users who aren't in Configuration Server (for example, applications/services, cloud system admin and so on.)</td> </tr> <tr> <td data-bbox="813 533 1122 638">properties</td> <td data-bbox="1122 533 1451 638">(object): The user's properties</td> </tr> <tr> <td data-bbox="813 638 1122 997">username</td> <td data-bbox="1122 638 1451 997">(string): The system-wide unique name of the user. For contact center users, this includes the userName in Configuration Server, the DBID in Configuration Server and the contact center ID. For non-Configuration Server users the username can have other formats.</td> </tr> </table>		The username in Configuration Server. This property is not set for users who aren't in Configuration Server (for example, applications/services, cloud system admin and so on.)	properties	(object): The user's properties	username	(string): The system-wide unique name of the user. For contact center users, this includes the userName in Configuration Server, the DBID in Configuration Server and the contact center ID. For non-Configuration Server users the username can have other formats.
	The username in Configuration Server. This property is not set for users who aren't in Configuration Server (for example, applications/services, cloud system admin and so on.)						
properties	(object): The user's properties						
username	(string): The system-wide unique name of the user. For contact center users, this includes the userName in Configuration Server, the DBID in Configuration Server and the contact center ID. For non-Configuration Server users the username can have other formats.						
401	Unauthorized						
503	Service unavailable						

Usage

```
curl -X GET
-H "x-api-key: your_API_key"
-H "Content-Type: application/json"

"https://api-demo.com/auth/v3/userinfo?"
```