



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

Genesys Multicloud CX Web-based API Reference

Third-Party Messaging API

Contents

- [1 Base path: /nexus/v3](#)

Base path: /nexus/v3

POST	/channels/{channelId}/media Upload a media resource
------	--

Upload a binary media file to Genesys to use in a RichMedia message. The response to this request includes a URL you can use as the image in the outgoing message payload.

Parameters

Name	Default	Description	Parameter Type	Data Type	Required
X-Hub-Signature		The request signature, for example sha1=hash. The hash is built using the body of the message and secret for the channel.	header	string	true
x-ccid		The ID of the contact center the message is sent within.	header	string	true
X-B3-TraceId		The unique trace ID for the request.	header	string	
channelId		The ID of the channel.	path	string	true
file		The file to upload.	formData	file	

Responses

Code	Reason
200	Operation was successful

Code	Reason																								
<pre> { "status": { "code": 0, "message": "string" }, "data": { "mediaId": "string", "url": "string", "filename": "string", "mimetype": "string", "length": 0 } } </pre>	<table border="1"> <tr> <td colspan="2" data-bbox="828 315 1442 357">status</td> </tr> <tr> <td data-bbox="828 367 1128 514">code</td> <td data-bbox="1131 367 1442 514">(integer): A code that can provide more information when an error occurs.</td> </tr> <tr> <td data-bbox="828 518 1128 665">message</td> <td data-bbox="1131 518 1442 665">(string): Provides additional information when a request returns an error response.</td> </tr> <tr> <td colspan="2" data-bbox="828 669 1442 711">data</td> </tr> <tr> <td data-bbox="828 716 1128 852">mediaId</td> <td data-bbox="1131 716 1442 852">(string): The ID of the media resource. bb4a9f86-dbbb-4464-a669-650da94fbad6</td> </tr> <tr> <td data-bbox="828 856 1128 1052">url</td> <td data-bbox="1131 856 1442 1052">(string): A synthetic URL to be used as reference in the outgoing message payload. genesys://nexus/ bb4a9f86-dbbb-4464-a669-650da94fbad6</td> </tr> <tr> <td data-bbox="828 1056 1128 1182">filename</td> <td data-bbox="1131 1056 1442 1182">(string): The name of the media resource. MyImage</td> </tr> <tr> <td data-bbox="828 1186 1128 1287">mimetype</td> <td data-bbox="1131 1186 1442 1287">(string): The type of file. image/jpeg</td> </tr> <tr> <td data-bbox="828 1291 1128 1392">length</td> <td data-bbox="1131 1291 1442 1392">(integer): The length of the media file.</td> </tr> <tr> <td colspan="2" data-bbox="828 1396 1442 1438">UploadResponse</td> </tr> <tr> <td data-bbox="828 1442 1128 1484">status</td> <td data-bbox="1131 1442 1442 1484">(object):</td> </tr> <tr> <td data-bbox="828 1488 1128 1530">data</td> <td data-bbox="1131 1488 1442 1530">(object):</td> </tr> </table>	status		code	(integer): A code that can provide more information when an error occurs.	message	(string): Provides additional information when a request returns an error response.	data		mediaId	(string): The ID of the media resource. bb4a9f86-dbbb-4464-a669-650da94fbad6	url	(string): A synthetic URL to be used as reference in the outgoing message payload. genesys://nexus/ bb4a9f86-dbbb-4464-a669-650da94fbad6	filename	(string): The name of the media resource. MyImage	mimetype	(string): The type of file. image/jpeg	length	(integer): The length of the media file.	UploadResponse		status	(object):	data	(object):
status																									
code	(integer): A code that can provide more information when an error occurs.																								
message	(string): Provides additional information when a request returns an error response.																								
data																									
mediaId	(string): The ID of the media resource. bb4a9f86-dbbb-4464-a669-650da94fbad6																								
url	(string): A synthetic URL to be used as reference in the outgoing message payload. genesys://nexus/ bb4a9f86-dbbb-4464-a669-650da94fbad6																								
filename	(string): The name of the media resource. MyImage																								
mimetype	(string): The type of file. image/jpeg																								
length	(integer): The length of the media file.																								
UploadResponse																									
status	(object):																								
data	(object):																								
400	Bad Request																								
<pre> {} </pre>	<table border="1"> <tr> <td colspan="2" data-bbox="828 1638 1442 1680">BadRequest</td> </tr> <tr> <td data-bbox="828 1684 1128 1726">status</td> <td data-bbox="1131 1684 1442 1726">(object):</td> </tr> <tr> <td data-bbox="828 1730 1128 1814">code</td> <td data-bbox="1131 1730 1442 1814">(integer):</td> </tr> </table>	BadRequest		status	(object):	code	(integer):																		
BadRequest																									
status	(object):																								
code	(integer):																								

Code	Reason	
{}	ServerError	
	status	(object):
	status	
	code	(integer): A code that can provide more information when an error occurs.
	message	(string): Provides additional information when a request returns an error response.
	ResponseError	
	status	(object):

Usage

```
curl -X POST
-H "x-api-key: your_API_key"
-H "Content-Type: application/json"
```

"https://api-demo.com/nexus/v3/channels/{channelId}/media?"

GET	/channels/{channelId}/media/{mediaId} Download a media resource
-----	--

Download a media resource you previously uploaded to Genesys with POST /channels/{channelId}/media.

Parameters

Name	Default	Description	Parameter Type	Data Type	Required
X-Hub-Signature		The request signature, for example sha1=hash. The hash is built using the body of the message and secret for the channel.	header	string	true
x-ccid		The ID of the contact center the message is sent within.	header	string	true
X-B3-TraceId		The unique	header	string	

Name	Default	Description	Parameter Type	Data Type	Required
		trace ID for the request.			
channelId		The ID of the channel.	path	string	true
mediaId		The media resource ID.	path	string	true

Responses

Code	Reason														
200	Operation was successful														
400	Bad Request														
{}	<table border="1"> <thead> <tr> <th colspan="2">BadRequest</th> </tr> </thead> <tbody> <tr> <td>status</td> <td>(object):</td> </tr> <tr> <td>status</td> <td></td> </tr> <tr> <td>code</td> <td>(integer): A code that can provide more information when an error occurs.</td> </tr> <tr> <td>message</td> <td>(string): Provides additional information when a request returns an error response.</td> </tr> <tr> <th colspan="2">ResponseError</th> </tr> <tr> <td>status</td> <td>(object):</td> </tr> </tbody> </table>	BadRequest		status	(object):	status		code	(integer): A code that can provide more information when an error occurs.	message	(string): Provides additional information when a request returns an error response.	ResponseError		status	(object):
BadRequest															
status	(object):														
status															
code	(integer): A code that can provide more information when an error occurs.														
message	(string): Provides additional information when a request returns an error response.														
ResponseError															
status	(object):														
401	Unauthorized														
{}	<table border="1"> <thead> <tr> <th colspan="2">Unauthorized</th> </tr> </thead> <tbody> <tr> <td>status</td> <td>(object):</td> </tr> <tr> <td>status</td> <td></td> </tr> <tr> <td>code</td> <td>(integer): A code that can provide more information when an error occurs.</td> </tr> <tr> <td>message</td> <td>(string): Provides additional information when a request returns an error response.</td> </tr> </tbody> </table>	Unauthorized		status	(object):	status		code	(integer): A code that can provide more information when an error occurs.	message	(string): Provides additional information when a request returns an error response.				
Unauthorized															
status	(object):														
status															
code	(integer): A code that can provide more information when an error occurs.														
message	(string): Provides additional information when a request returns an error response.														

Code	Reason														
	<table border="1"> <tr> <td colspan="2">ResponseError</td> </tr> <tr> <td>status</td> <td>(object):</td> </tr> </table>	ResponseError		status	(object):										
ResponseError															
status	(object):														
403	Forbidden														
{}	<table border="1"> <tr> <td colspan="2">Forbidden</td> </tr> <tr> <td>status</td> <td>(object):</td> </tr> <tr> <td>status</td> <td></td> </tr> <tr> <td>code</td> <td>(integer): A code that can provide more information when an error occurs.</td> </tr> <tr> <td>message</td> <td>(string): Provides additional information when a request returns an error response.</td> </tr> <tr> <td colspan="2">ResponseError</td> </tr> <tr> <td>status</td> <td>(object):</td> </tr> </table>	Forbidden		status	(object):	status		code	(integer): A code that can provide more information when an error occurs.	message	(string): Provides additional information when a request returns an error response.	ResponseError		status	(object):
Forbidden															
status	(object):														
status															
code	(integer): A code that can provide more information when an error occurs.														
message	(string): Provides additional information when a request returns an error response.														
ResponseError															
status	(object):														
404	Channel 1234567890 not found														
{}	<table border="1"> <tr> <td colspan="2">NotFound</td> </tr> <tr> <td>status</td> <td>(object):</td> </tr> <tr> <td>status</td> <td></td> </tr> <tr> <td>code</td> <td>(integer): A code that can provide more information when an error occurs.</td> </tr> <tr> <td>message</td> <td>(string): Provides additional information when a request returns an error response.</td> </tr> <tr> <td colspan="2">ResponseError</td> </tr> <tr> <td>status</td> <td>(object):</td> </tr> </table>	NotFound		status	(object):	status		code	(integer): A code that can provide more information when an error occurs.	message	(string): Provides additional information when a request returns an error response.	ResponseError		status	(object):
NotFound															
status	(object):														
status															
code	(integer): A code that can provide more information when an error occurs.														
message	(string): Provides additional information when a request returns an error response.														
ResponseError															
status	(object):														
500	Internal Server Error														

Code	Reason	
{}	ServerError	
	status	(object):
	status	
	code	(integer): A code that can provide more information when an error occurs.
	message	(string): Provides additional information when a request returns an error response.
	ResponseError	
	status	(object):

Usage

```
curl -X GET
-H "x-api-key: your_API_key"
-H "Content-Type: application/json"
```

```
"https://api-demo.com/nexus/v3/channels/{channelId}/media/{mediaId}?"
```

DELETE	/channels/{channelId}/media/{mediaId} Delete a media resource
--------	--

Delete a media resource you previously uploaded to Genesys with POST /channels/{channelId}/media.

Parameters

Name	Default	Description	Parameter Type	Data Type	Required
X-Hub-Signature		The request signature, for example sha1=hash. The hash is built using the body of the message and secret for the channel.	header	string	true
x-ccid		The ID of the contact center the message is sent within.	header	string	true
X-B3-TraceId		The unique	header	string	

Name	Default	Description	Parameter Type	Data Type	Required
		trace ID for the request.			
channelId		The ID of the channel.	header	path	true
mediaId		The media resource ID.	header	path	true

Responses

Code	Reason																				
200	Operation was successful																				
<pre> { "status": { "code": 0, "message": "string" }, "data": { "mediaId": "string", "url": "string", "filename": "string", "mimetype": "string", "length": 0 } } </pre>	<table border="1"> <thead> <tr> <th colspan="2">status</th> </tr> </thead> <tbody> <tr> <td>code</td> <td>(integer): A code that can provide more information when an error occurs.</td> </tr> <tr> <td>message</td> <td>(string): Provides additional information when a request returns an error response.</td> </tr> <tr> <th colspan="2">data</th> </tr> <tr> <td>mediaId</td> <td>(string): The ID of the media resource. bb4a9f86-dbbb-4464-a669-650da94fbad6</td> </tr> <tr> <td>url</td> <td>(string): A synthetic URL to be used as reference in the outgoing message payload. genesys://nexus/ bb4a9f86-dbbb-4464-a669-650da94fbad6</td> </tr> <tr> <td>filename</td> <td>(string): The name of the media resource. MyImage</td> </tr> <tr> <td>mimetype</td> <td>(string): The type of file. image/jpeg</td> </tr> <tr> <td>length</td> <td>(integer): The length of the media file.</td> </tr> <tr> <th colspan="2">UploadResponse</th> </tr> </tbody> </table>	status		code	(integer): A code that can provide more information when an error occurs.	message	(string): Provides additional information when a request returns an error response.	data		mediaId	(string): The ID of the media resource. bb4a9f86-dbbb-4464-a669-650da94fbad6	url	(string): A synthetic URL to be used as reference in the outgoing message payload. genesys://nexus/ bb4a9f86-dbbb-4464-a669-650da94fbad6	filename	(string): The name of the media resource. MyImage	mimetype	(string): The type of file. image/jpeg	length	(integer): The length of the media file.	UploadResponse	
status																					
code	(integer): A code that can provide more information when an error occurs.																				
message	(string): Provides additional information when a request returns an error response.																				
data																					
mediaId	(string): The ID of the media resource. bb4a9f86-dbbb-4464-a669-650da94fbad6																				
url	(string): A synthetic URL to be used as reference in the outgoing message payload. genesys://nexus/ bb4a9f86-dbbb-4464-a669-650da94fbad6																				
filename	(string): The name of the media resource. MyImage																				
mimetype	(string): The type of file. image/jpeg																				
length	(integer): The length of the media file.																				
UploadResponse																					

Code	Reason														
	<table border="1"> <tr> <td>status</td> <td>(object):</td> </tr> <tr> <td>data</td> <td>(object):</td> </tr> </table>	status	(object):	data	(object):										
status	(object):														
data	(object):														
400	Bad Request														
{}	<table border="1"> <tr> <td colspan="2">BadRequest</td> </tr> <tr> <td>status</td> <td>(object):</td> </tr> <tr> <td colspan="2">status</td> </tr> <tr> <td>code</td> <td>(integer): A code that can provide more information when an error occurs.</td> </tr> <tr> <td>message</td> <td>(string): Provides additional information when a request returns an error response.</td> </tr> <tr> <td colspan="2">ResponseError</td> </tr> <tr> <td>status</td> <td>(object):</td> </tr> </table>	BadRequest		status	(object):	status		code	(integer): A code that can provide more information when an error occurs.	message	(string): Provides additional information when a request returns an error response.	ResponseError		status	(object):
BadRequest															
status	(object):														
status															
code	(integer): A code that can provide more information when an error occurs.														
message	(string): Provides additional information when a request returns an error response.														
ResponseError															
status	(object):														
401	Unauthorized														
{}	<table border="1"> <tr> <td colspan="2">Unauthorized</td> </tr> <tr> <td>status</td> <td>(object):</td> </tr> <tr> <td colspan="2">status</td> </tr> <tr> <td>code</td> <td>(integer): A code that can provide more information when an error occurs.</td> </tr> <tr> <td>message</td> <td>(string): Provides additional information when a request returns an error response.</td> </tr> <tr> <td colspan="2">ResponseError</td> </tr> <tr> <td>status</td> <td>(object):</td> </tr> </table>	Unauthorized		status	(object):	status		code	(integer): A code that can provide more information when an error occurs.	message	(string): Provides additional information when a request returns an error response.	ResponseError		status	(object):
Unauthorized															
status	(object):														
status															
code	(integer): A code that can provide more information when an error occurs.														
message	(string): Provides additional information when a request returns an error response.														
ResponseError															
status	(object):														
403	Forbidden														

Code	Reason														
{}	<table border="1"> <tr> <td colspan="2" data-bbox="820 315 1445 357">Forbidden</td> </tr> <tr> <td data-bbox="820 357 1128 399">status</td> <td data-bbox="1128 357 1445 399">(object):</td> </tr> <tr> <td colspan="2" data-bbox="820 399 1445 441">status</td> </tr> <tr> <td data-bbox="820 441 1128 598">code</td> <td data-bbox="1128 441 1445 598">(integer): A code that can provide more information when an error occurs.</td> </tr> <tr> <td data-bbox="820 598 1128 745">message</td> <td data-bbox="1128 598 1445 745">(string): Provides additional information when a request returns an error response.</td> </tr> <tr> <td colspan="2" data-bbox="820 745 1445 787">ResponseError</td> </tr> <tr> <td data-bbox="820 787 1128 829">status</td> <td data-bbox="1128 787 1445 829">(object):</td> </tr> </table>	Forbidden		status	(object):	status		code	(integer): A code that can provide more information when an error occurs.	message	(string): Provides additional information when a request returns an error response.	ResponseError		status	(object):
	Forbidden														
	status	(object):													
	status														
	code	(integer): A code that can provide more information when an error occurs.													
	message	(string): Provides additional information when a request returns an error response.													
ResponseError															
status	(object):														
404	Channel not found														
{}	<table border="1"> <tr> <td colspan="2" data-bbox="820 945 1445 987">NotFound</td> </tr> <tr> <td data-bbox="820 987 1128 1029">status</td> <td data-bbox="1128 987 1445 1029">(object):</td> </tr> <tr> <td colspan="2" data-bbox="820 1029 1445 1071">status</td> </tr> <tr> <td data-bbox="820 1071 1128 1228">code</td> <td data-bbox="1128 1071 1445 1228">(integer): A code that can provide more information when an error occurs.</td> </tr> <tr> <td data-bbox="820 1228 1128 1375">message</td> <td data-bbox="1128 1228 1445 1375">(string): Provides additional information when a request returns an error response.</td> </tr> <tr> <td colspan="2" data-bbox="820 1375 1445 1417">ResponseError</td> </tr> <tr> <td data-bbox="820 1417 1128 1459">status</td> <td data-bbox="1128 1417 1445 1459">(object):</td> </tr> </table>	NotFound		status	(object):	status		code	(integer): A code that can provide more information when an error occurs.	message	(string): Provides additional information when a request returns an error response.	ResponseError		status	(object):
	NotFound														
	status	(object):													
	status														
	code	(integer): A code that can provide more information when an error occurs.													
	message	(string): Provides additional information when a request returns an error response.													
ResponseError															
status	(object):														
500	Internal Server Error														
{}	<table border="1"> <tr> <td colspan="2" data-bbox="820 1575 1445 1617">ServerError</td> </tr> <tr> <td data-bbox="820 1617 1128 1659">status</td> <td data-bbox="1128 1617 1445 1659">(object):</td> </tr> <tr> <td colspan="2" data-bbox="820 1659 1445 1701">status</td> </tr> <tr> <td data-bbox="820 1701 1128 1816">code</td> <td data-bbox="1128 1701 1445 1816">(integer): A code that can provide</td> </tr> </table>	ServerError		status	(object):	status		code	(integer): A code that can provide						
	ServerError														
	status	(object):													
	status														
code	(integer): A code that can provide														

Code	Reason
	more information when an error occurs.
	(string): Provides additional information when a request returns an error response.
	message
	ResponseError
	status (object):

Usage

```
curl -X DELETE
-H "x-api-key: your_API_key"
-H "Content-Type: application/json"
```

```
"https://api-demo.com/nexus/v3/channels/{channelId}/media/{mediaId}?"
```

POST	/channels/{channelId}/messages Send a message
------	--

Send a message to an agent in Genesys from an external messaging system, such as SMS.

Parameters

Name	Default	Description	Parameter Type	Data Type	Required
X-Hub-Signature		The request signature, for example sha1=hash. The hash is built using the body of the message and secret for the channel.	header	string	true
x-ccid		The ID of the contact center the message is sent within.	header	string	true
X-B3-TraceId		The unique trace ID for the request.	header	string	
channelId		The ID of the channel.	path	string	true
messages		Message	body		true

Name	Default	Description	Parameter Type	Data Type	Required

Responses

Code	Reason																				
200	Operation was successful																				
<pre>{ "status": { "code": 0, "message": "string" }, "data": { "ids": [{ "id": "string" }] } }</pre>	<table border="1"> <thead> <tr> <th colspan="2">status</th> </tr> </thead> <tbody> <tr> <td>code</td> <td>(integer): A code that can provide more information when an error occurs.</td> </tr> <tr> <td>message</td> <td>(string): Provides additional information when a request returns an error response.</td> </tr> <tr> <th colspan="2">ids</th> </tr> <tr> <td>id</td> <td>(string):</td> </tr> <tr> <th colspan="2">data</th> </tr> <tr> <td>ids</td> <td>(array:object): The ID of the accepted message, if provided.</td> </tr> <tr> <th colspan="2">InboundMessageResponse</th> </tr> <tr> <td>status</td> <td>(object):</td> </tr> <tr> <td>data</td> <td>(object):</td> </tr> </tbody> </table>	status		code	(integer): A code that can provide more information when an error occurs.	message	(string): Provides additional information when a request returns an error response.	ids		id	(string):	data		ids	(array:object): The ID of the accepted message, if provided.	InboundMessageResponse		status	(object):	data	(object):
status																					
code	(integer): A code that can provide more information when an error occurs.																				
message	(string): Provides additional information when a request returns an error response.																				
ids																					
id	(string):																				
data																					
ids	(array:object): The ID of the accepted message, if provided.																				
InboundMessageResponse																					
status	(object):																				
data	(object):																				
400	Bad Request																				
<pre>{}</pre>	<table border="1"> <thead> <tr> <th colspan="2">BadRequest</th> </tr> </thead> <tbody> <tr> <td>status</td> <td>(object):</td> </tr> <tr> <th colspan="2">status</th> </tr> <tr> <td>code</td> <td>(integer): A code that can provide more information when an error occurs.</td> </tr> <tr> <td>message</td> <td>(string):</td> </tr> </tbody> </table>	BadRequest		status	(object):	status		code	(integer): A code that can provide more information when an error occurs.	message	(string):										
BadRequest																					
status	(object):																				
status																					
code	(integer): A code that can provide more information when an error occurs.																				
message	(string):																				

Code	Reason														
404	Channel not found														
{}	<table border="1"> <tr> <td colspan="2">NotFound</td> </tr> <tr> <td>status</td> <td>(object):</td> </tr> <tr> <td colspan="2">status</td> </tr> <tr> <td>code</td> <td>(integer): A code that can provide more information when an error occurs.</td> </tr> <tr> <td>message</td> <td>(string): Provides additional information when a request returns an error response.</td> </tr> <tr> <td colspan="2">ResponseError</td> </tr> <tr> <td>status</td> <td>(object):</td> </tr> </table>	NotFound		status	(object):	status		code	(integer): A code that can provide more information when an error occurs.	message	(string): Provides additional information when a request returns an error response.	ResponseError		status	(object):
NotFound															
status	(object):														
status															
code	(integer): A code that can provide more information when an error occurs.														
message	(string): Provides additional information when a request returns an error response.														
ResponseError															
status	(object):														
500	Internal Server Error														
{}	<table border="1"> <tr> <td colspan="2">ServerError</td> </tr> <tr> <td>status</td> <td>(object):</td> </tr> <tr> <td colspan="2">status</td> </tr> <tr> <td>code</td> <td>(integer): A code that can provide more information when an error occurs.</td> </tr> <tr> <td>message</td> <td>(string): Provides additional information when a request returns an error response.</td> </tr> <tr> <td colspan="2">ResponseError</td> </tr> <tr> <td>status</td> <td>(object):</td> </tr> </table>	ServerError		status	(object):	status		code	(integer): A code that can provide more information when an error occurs.	message	(string): Provides additional information when a request returns an error response.	ResponseError		status	(object):
ServerError															
status	(object):														
status															
code	(integer): A code that can provide more information when an error occurs.														
message	(string): Provides additional information when a request returns an error response.														
ResponseError															
status	(object):														

Usage

```
curl -X POST
-H "x-api-key: your_API_key"
-H "Content-Type: application/json"
-d '{}'
"https://api-demo.com/nexus/v3/channels/{channelId}/messages?"
```