



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

# Genesys Multicloud CX Web-based API Reference

Third-Party Messaging API

---

## Contents

- [1 Base path: /nexus/v3](#)

---

Base path: /nexus/v3

POST	/channels/{channelId}/media Upload a media resource
------	--

Upload a binary media file to Genesys to use in a RichMedia message. The response to this request includes a URL you can use as the image in the outgoing message payload.

Parameters

Name	Default	Description	Parameter Type	Data Type	Required
X-Hub-Signature		The request signature, for example sha1=hash. The hash is built using the body of the message and secret for the channel.	header	string	true
x-ccid		The ID of the contact center the message is sent within.	header	string	true
X-B3-TraceId		The unique trace ID for the request.	header	string	
channelId		The ID of the channel.	path	string	true
file		The file to upload.	formData	file	

Responses

Code	Reason
200	Operation was successful

Code	Reason																								
<pre> {   "status": {     "code": 0,     "message": "string"   },   "data": {     "mediaId": "string",     "url": "string",     "filename": "string",     "mimetype": "string",     "length": 0   } } </pre>	<table border="1"> <tr> <td colspan="2" data-bbox="828 315 1442 357">status</td> </tr> <tr> <td data-bbox="828 367 1128 514">code</td> <td data-bbox="1131 367 1442 514">(integer): A code that can provide more information when an error occurs.</td> </tr> <tr> <td data-bbox="828 518 1128 665">message</td> <td data-bbox="1131 518 1442 665">(string): Provides additional information when a request returns an error response.</td> </tr> <tr> <td colspan="2" data-bbox="828 669 1442 711">data</td> </tr> <tr> <td data-bbox="828 716 1128 852">mediaId</td> <td data-bbox="1131 716 1442 852">(string): The ID of the media resource. bb4a9f86-dbbb-4464-a669-650da94fbad6</td> </tr> <tr> <td data-bbox="828 856 1128 1052">url</td> <td data-bbox="1131 856 1442 1052">(string): A synthetic URL to be used as reference in the outgoing message payload. genesys://nexus/ bb4a9f86-dbbb-4464-a669-650da94fbad6</td> </tr> <tr> <td data-bbox="828 1056 1128 1182">filename</td> <td data-bbox="1131 1056 1442 1182">(string): The name of the media resource. MyImage</td> </tr> <tr> <td data-bbox="828 1186 1128 1287">mimetype</td> <td data-bbox="1131 1186 1442 1287">(string): The type of file. image/jpeg</td> </tr> <tr> <td data-bbox="828 1291 1128 1392">length</td> <td data-bbox="1131 1291 1442 1392">(integer): The length of the media file.</td> </tr> <tr> <td colspan="2" data-bbox="828 1396 1442 1438">UploadResponse</td> </tr> <tr> <td data-bbox="828 1442 1128 1484">status</td> <td data-bbox="1131 1442 1442 1484">(object):</td> </tr> <tr> <td data-bbox="828 1488 1128 1530">data</td> <td data-bbox="1131 1488 1442 1530">(object):</td> </tr> </table>	status		code	(integer): A code that can provide more information when an error occurs.	message	(string): Provides additional information when a request returns an error response.	data		mediaId	(string): The ID of the media resource. bb4a9f86-dbbb-4464-a669-650da94fbad6	url	(string): A synthetic URL to be used as reference in the outgoing message payload. genesys://nexus/ bb4a9f86-dbbb-4464-a669-650da94fbad6	filename	(string): The name of the media resource. MyImage	mimetype	(string): The type of file. image/jpeg	length	(integer): The length of the media file.	UploadResponse		status	(object):	data	(object):
status																									
code	(integer): A code that can provide more information when an error occurs.																								
message	(string): Provides additional information when a request returns an error response.																								
data																									
mediaId	(string): The ID of the media resource. bb4a9f86-dbbb-4464-a669-650da94fbad6																								
url	(string): A synthetic URL to be used as reference in the outgoing message payload. genesys://nexus/ bb4a9f86-dbbb-4464-a669-650da94fbad6																								
filename	(string): The name of the media resource. MyImage																								
mimetype	(string): The type of file. image/jpeg																								
length	(integer): The length of the media file.																								
UploadResponse																									
status	(object):																								
data	(object):																								
400	Bad Request																								
<pre> {} </pre>	<table border="1"> <tr> <td colspan="2" data-bbox="828 1638 1442 1680">BadRequest</td> </tr> <tr> <td data-bbox="828 1684 1128 1726">status</td> <td data-bbox="1131 1684 1442 1726">(object):</td> </tr> <tr> <td data-bbox="828 1730 1128 1814">code</td> <td data-bbox="1131 1730 1442 1814">(integer):</td> </tr> </table>	BadRequest		status	(object):	code	(integer):																		
BadRequest																									
status	(object):																								
code	(integer):																								





Code	Reason	
{}	ServerError	
	status	(object):
	status	
	code	(integer): A code that can provide more information when an error occurs.
	message	(string): Provides additional information when a request returns an error response.
	ResponseError	
	status	(object):

## Usage

```
curl -X POST
-H "x-api-key: your_API_key"
-H "Content-Type: application/json"
```

"https://api-demo.com/nexus/v3/channels/{channelId}/media?"

GET	/channels/{channelId}/media/{mediaId} Download a media resource
-----	--

Download a media resource you previously uploaded to Genesys with POST /channels/{channelId}/media.

## Parameters

Name	Default	Description	Parameter Type	Data Type	Required
X-Hub-Signature		The request signature, for example sha1=hash. The hash is built using the body of the message and secret for the channel.	header	string	true
x-ccid		The ID of the contact center the message is sent within.	header	string	true
X-B3-TraceId		The unique	header	string	

Name	Default	Description	Parameter Type	Data Type	Required
		trace ID for the request.			
channelId		The ID of the channel.	path	string	true
mediaId		The media resource ID.	path	string	true

## Responses

Code	Reason														
200	Operation was successful														
400	Bad Request														
{}	<table border="1"> <thead> <tr> <th colspan="2">BadRequest</th> </tr> </thead> <tbody> <tr> <td>status</td> <td>(object):</td> </tr> <tr> <td>status</td> <td></td> </tr> <tr> <td>code</td> <td>(integer): A code that can provide more information when an error occurs.</td> </tr> <tr> <td>message</td> <td>(string): Provides additional information when a request returns an error response.</td> </tr> <tr> <th colspan="2">ResponseError</th> </tr> <tr> <td>status</td> <td>(object):</td> </tr> </tbody> </table>	BadRequest		status	(object):	status		code	(integer): A code that can provide more information when an error occurs.	message	(string): Provides additional information when a request returns an error response.	ResponseError		status	(object):
BadRequest															
status	(object):														
status															
code	(integer): A code that can provide more information when an error occurs.														
message	(string): Provides additional information when a request returns an error response.														
ResponseError															
status	(object):														
401	Unauthorized														
{}	<table border="1"> <thead> <tr> <th colspan="2">Unauthorized</th> </tr> </thead> <tbody> <tr> <td>status</td> <td>(object):</td> </tr> <tr> <td>status</td> <td></td> </tr> <tr> <td>code</td> <td>(integer): A code that can provide more information when an error occurs.</td> </tr> <tr> <td>message</td> <td>(string): Provides additional information when a request returns an error response.</td> </tr> </tbody> </table>	Unauthorized		status	(object):	status		code	(integer): A code that can provide more information when an error occurs.	message	(string): Provides additional information when a request returns an error response.				
Unauthorized															
status	(object):														
status															
code	(integer): A code that can provide more information when an error occurs.														
message	(string): Provides additional information when a request returns an error response.														

Code	Reason														
	<table border="1"> <tr> <td colspan="2">ResponseError</td> </tr> <tr> <td>status</td> <td>(object):</td> </tr> </table>	ResponseError		status	(object):										
ResponseError															
status	(object):														
403	Forbidden														
{}	<table border="1"> <tr> <td colspan="2">Forbidden</td> </tr> <tr> <td>status</td> <td>(object):</td> </tr> <tr> <td>status</td> <td></td> </tr> <tr> <td>code</td> <td>(integer): A code that can provide more information when an error occurs.</td> </tr> <tr> <td>message</td> <td>(string): Provides additional information when a request returns an error response.</td> </tr> <tr> <td colspan="2">ResponseError</td> </tr> <tr> <td>status</td> <td>(object):</td> </tr> </table>	Forbidden		status	(object):	status		code	(integer): A code that can provide more information when an error occurs.	message	(string): Provides additional information when a request returns an error response.	ResponseError		status	(object):
Forbidden															
status	(object):														
status															
code	(integer): A code that can provide more information when an error occurs.														
message	(string): Provides additional information when a request returns an error response.														
ResponseError															
status	(object):														
404	Channel 1234567890 not found														
{}	<table border="1"> <tr> <td colspan="2">NotFound</td> </tr> <tr> <td>status</td> <td>(object):</td> </tr> <tr> <td>status</td> <td></td> </tr> <tr> <td>code</td> <td>(integer): A code that can provide more information when an error occurs.</td> </tr> <tr> <td>message</td> <td>(string): Provides additional information when a request returns an error response.</td> </tr> <tr> <td colspan="2">ResponseError</td> </tr> <tr> <td>status</td> <td>(object):</td> </tr> </table>	NotFound		status	(object):	status		code	(integer): A code that can provide more information when an error occurs.	message	(string): Provides additional information when a request returns an error response.	ResponseError		status	(object):
NotFound															
status	(object):														
status															
code	(integer): A code that can provide more information when an error occurs.														
message	(string): Provides additional information when a request returns an error response.														
ResponseError															
status	(object):														
500	Internal Server Error														

Code	Reason	
{}	ServerError	
	status	(object):
	status	
	code	(integer): A code that can provide more information when an error occurs.
	message	(string): Provides additional information when a request returns an error response.
	ResponseError	
	status	(object):

## Usage

```
curl -X GET
-H "x-api-key: your_API_key"
-H "Content-Type: application/json"
```

```
"https://api-demo.com/nexus/v3/channels/{channelId}/media/{mediaId}?"
```

DELETE	/channels/{channelId}/media/{mediaId} Delete a media resource
--------	--

Delete a media resource you previously uploaded to Genesys with POST /channels/{channelId}/media.

### Parameters

Name	Default	Description	Parameter Type	Data Type	Required
X-Hub-Signature		The request signature, for example sha1=hash. The hash is built using the body of the message and secret for the channel.	header	string	true
x-ccid		The ID of the contact center the message is sent within.	header	string	true
X-B3-TraceId		The unique	header	string	

Name	Default	Description	Parameter Type	Data Type	Required
		trace ID for the request.			
channelId		The ID of the channel.	header	path	true
mediaId		The media resource ID.	header	path	true

## Responses

Code	Reason																				
200	Operation was successful																				
<pre>{   "status": {     "code": 0,     "message": "string"   },   "data": {     "mediaId": "string",     "url": "string",     "filename": "string",     "mimetype": "string",     "length": 0   } }</pre>	<table border="1"> <thead> <tr> <th colspan="2">status</th> </tr> </thead> <tbody> <tr> <td>code</td> <td>(integer): A code that can provide more information when an error occurs.</td> </tr> <tr> <td>message</td> <td>(string): Provides additional information when a request returns an error response.</td> </tr> <tr> <th colspan="2">data</th> </tr> <tr> <td>mediaId</td> <td>(string): The ID of the media resource. bb4a9f86-dbbb-4464-a669-650da94fbad6</td> </tr> <tr> <td>url</td> <td>(string): A synthetic URL to be used as reference in the outgoing message payload. genesys://nexus/ bb4a9f86-dbbb-4464-a669-650da94fbad6</td> </tr> <tr> <td>filename</td> <td>(string): The name of the media resource. MyImage</td> </tr> <tr> <td>mimetype</td> <td>(string): The type of file. image/jpeg</td> </tr> <tr> <td>length</td> <td>(integer): The length of the media file.</td> </tr> <tr> <th colspan="2">UploadResponse</th> </tr> </tbody> </table>	status		code	(integer): A code that can provide more information when an error occurs.	message	(string): Provides additional information when a request returns an error response.	data		mediaId	(string): The ID of the media resource. bb4a9f86-dbbb-4464-a669-650da94fbad6	url	(string): A synthetic URL to be used as reference in the outgoing message payload. genesys://nexus/ bb4a9f86-dbbb-4464-a669-650da94fbad6	filename	(string): The name of the media resource. MyImage	mimetype	(string): The type of file. image/jpeg	length	(integer): The length of the media file.	UploadResponse	
status																					
code	(integer): A code that can provide more information when an error occurs.																				
message	(string): Provides additional information when a request returns an error response.																				
data																					
mediaId	(string): The ID of the media resource. bb4a9f86-dbbb-4464-a669-650da94fbad6																				
url	(string): A synthetic URL to be used as reference in the outgoing message payload. genesys://nexus/ bb4a9f86-dbbb-4464-a669-650da94fbad6																				
filename	(string): The name of the media resource. MyImage																				
mimetype	(string): The type of file. image/jpeg																				
length	(integer): The length of the media file.																				
UploadResponse																					

Code	Reason														
	<table border="1"> <tr> <td data-bbox="812 296 1127 359">status</td> <td data-bbox="1130 296 1458 359">(object):</td> </tr> <tr> <td data-bbox="812 363 1127 405">data</td> <td data-bbox="1130 363 1458 405">(object):</td> </tr> </table>	status	(object):	data	(object):										
status	(object):														
data	(object):														
400	Bad Request														
<pre data-bbox="186 766 219 798">{}</pre>	<table border="1"> <tr> <td colspan="2" data-bbox="812 499 1127 562">BadRequest</td> </tr> <tr> <td data-bbox="812 567 1127 609">status</td> <td data-bbox="1130 567 1458 609">(object):</td> </tr> <tr> <td colspan="2" data-bbox="812 613 1127 644">status</td> </tr> <tr> <td data-bbox="812 648 1127 800">code</td> <td data-bbox="1130 648 1458 800">(integer): A code that can provide more information when an error occurs.</td> </tr> <tr> <td data-bbox="812 804 1127 955">message</td> <td data-bbox="1130 804 1458 955">(string): Provides additional information when a request returns an error response.</td> </tr> <tr> <td colspan="2" data-bbox="812 959 1127 991">ResponseError</td> </tr> <tr> <td data-bbox="812 995 1127 1037">status</td> <td data-bbox="1130 995 1458 1037">(object):</td> </tr> </table>	BadRequest		status	(object):	status		code	(integer): A code that can provide more information when an error occurs.	message	(string): Provides additional information when a request returns an error response.	ResponseError		status	(object):
BadRequest															
status	(object):														
status															
code	(integer): A code that can provide more information when an error occurs.														
message	(string): Provides additional information when a request returns an error response.														
ResponseError															
status	(object):														
401	Unauthorized														
<pre data-bbox="186 1396 219 1428">{}</pre>	<table border="1"> <tr> <td colspan="2" data-bbox="812 1129 1127 1192">Unauthorized</td> </tr> <tr> <td data-bbox="812 1197 1127 1239">status</td> <td data-bbox="1130 1197 1458 1239">(object):</td> </tr> <tr> <td colspan="2" data-bbox="812 1243 1127 1274">status</td> </tr> <tr> <td data-bbox="812 1278 1127 1430">code</td> <td data-bbox="1130 1278 1458 1430">(integer): A code that can provide more information when an error occurs.</td> </tr> <tr> <td data-bbox="812 1434 1127 1585">message</td> <td data-bbox="1130 1434 1458 1585">(string): Provides additional information when a request returns an error response.</td> </tr> <tr> <td colspan="2" data-bbox="812 1589 1127 1621">ResponseError</td> </tr> <tr> <td data-bbox="812 1625 1127 1667">status</td> <td data-bbox="1130 1625 1458 1667">(object):</td> </tr> </table>	Unauthorized		status	(object):	status		code	(integer): A code that can provide more information when an error occurs.	message	(string): Provides additional information when a request returns an error response.	ResponseError		status	(object):
Unauthorized															
status	(object):														
status															
code	(integer): A code that can provide more information when an error occurs.														
message	(string): Provides additional information when a request returns an error response.														
ResponseError															
status	(object):														
403	Forbidden														

Code	Reason														
{}	<table border="1"> <tr> <td colspan="2" data-bbox="812 296 1456 359">Forbidden</td> </tr> <tr> <td data-bbox="812 359 1127 401">status</td> <td data-bbox="1130 359 1456 401">(object):</td> </tr> <tr> <td colspan="2" data-bbox="812 401 1456 443">status</td> </tr> <tr> <td data-bbox="812 443 1127 590">code</td> <td data-bbox="1130 443 1456 590">(integer): A code that can provide more information when an error occurs.</td> </tr> <tr> <td data-bbox="812 590 1127 737">message</td> <td data-bbox="1130 590 1456 737">(string): Provides additional information when a request returns an error response.</td> </tr> <tr> <td colspan="2" data-bbox="812 737 1456 779">ResponseError</td> </tr> <tr> <td data-bbox="812 779 1127 821">status</td> <td data-bbox="1130 779 1456 821">(object):</td> </tr> </table>	Forbidden		status	(object):	status		code	(integer): A code that can provide more information when an error occurs.	message	(string): Provides additional information when a request returns an error response.	ResponseError		status	(object):
	Forbidden														
	status	(object):													
	status														
	code	(integer): A code that can provide more information when an error occurs.													
	message	(string): Provides additional information when a request returns an error response.													
ResponseError															
status	(object):														
404	Channel not found														
{}	<table border="1"> <tr> <td colspan="2" data-bbox="812 911 1456 974">NotFound</td> </tr> <tr> <td data-bbox="812 974 1127 1016">status</td> <td data-bbox="1130 974 1456 1016">(object):</td> </tr> <tr> <td colspan="2" data-bbox="812 1016 1456 1058">status</td> </tr> <tr> <td data-bbox="812 1058 1127 1205">code</td> <td data-bbox="1130 1058 1456 1205">(integer): A code that can provide more information when an error occurs.</td> </tr> <tr> <td data-bbox="812 1205 1127 1352">message</td> <td data-bbox="1130 1205 1456 1352">(string): Provides additional information when a request returns an error response.</td> </tr> <tr> <td colspan="2" data-bbox="812 1352 1456 1394">ResponseError</td> </tr> <tr> <td data-bbox="812 1394 1127 1436">status</td> <td data-bbox="1130 1394 1456 1436">(object):</td> </tr> </table>	NotFound		status	(object):	status		code	(integer): A code that can provide more information when an error occurs.	message	(string): Provides additional information when a request returns an error response.	ResponseError		status	(object):
	NotFound														
	status	(object):													
	status														
	code	(integer): A code that can provide more information when an error occurs.													
	message	(string): Provides additional information when a request returns an error response.													
ResponseError															
status	(object):														
500	Internal Server Error														
{}	<table border="1"> <tr> <td colspan="2" data-bbox="812 1526 1456 1589">ServerError</td> </tr> <tr> <td data-bbox="812 1589 1127 1631">status</td> <td data-bbox="1130 1589 1456 1631">(object):</td> </tr> <tr> <td colspan="2" data-bbox="812 1631 1456 1673">status</td> </tr> <tr> <td data-bbox="812 1673 1127 1835">code</td> <td data-bbox="1130 1673 1456 1835">(integer): A code that can provide</td> </tr> </table>	ServerError		status	(object):	status		code	(integer): A code that can provide						
	ServerError														
	status	(object):													
	status														
code	(integer): A code that can provide														

Code	Reason
	more information when an error occurs.
	(string): Provides additional information when a request returns an error response.
	message
	ResponseError
	status (object):

## Usage

```
curl -X DELETE
-H "x-api-key: your_API_key"
-H "Content-Type: application/json"
```

```
"https://api-demo.com/nexus/v3/channels/{channelId}/media/{mediaId}?"
```

POST	/channels/{channelId}/messages Send a message
------	--

Send a message to an agent in Genesys from an external messaging system, such as SMS.

## Parameters

Name	Default	Description	Parameter Type	Data Type	Required
X-Hub-Signature		The request signature, for example sha1=hash. The hash is built using the body of the message and secret for the channel.	header	string	true
x-ccid		The ID of the contact center the message is sent within.	header	string	true
X-B3-TraceId		The unique trace ID for the request.	header	string	
channelId		The ID of the channel.	path	string	true
messages		Message	body		true

Name	Default	Description	Parameter Type	Data Type	Required

## Responses

Code	Reason																				
200	Operation was successful																				
<pre>{   "status": {     "code": 0,     "message": "string"   },   "data": {     "ids": [       {         "id": "string"       }     ]   } }</pre>	<table border="1"> <thead> <tr> <th colspan="2">status</th> </tr> </thead> <tbody> <tr> <td>code</td> <td>(integer): A code that can provide more information when an error occurs.</td> </tr> <tr> <td>message</td> <td>(string): Provides additional information when a request returns an error response.</td> </tr> <tr> <th colspan="2">ids</th> </tr> <tr> <td>id</td> <td>(string):</td> </tr> <tr> <th colspan="2">data</th> </tr> <tr> <td>ids</td> <td>(array:object): The ID of the accepted message, if provided.</td> </tr> <tr> <th colspan="2">InboundMessageResponse</th> </tr> <tr> <td>status</td> <td>(object):</td> </tr> <tr> <td>data</td> <td>(object):</td> </tr> </tbody> </table>	status		code	(integer): A code that can provide more information when an error occurs.	message	(string): Provides additional information when a request returns an error response.	ids		id	(string):	data		ids	(array:object): The ID of the accepted message, if provided.	InboundMessageResponse		status	(object):	data	(object):
status																					
code	(integer): A code that can provide more information when an error occurs.																				
message	(string): Provides additional information when a request returns an error response.																				
ids																					
id	(string):																				
data																					
ids	(array:object): The ID of the accepted message, if provided.																				
InboundMessageResponse																					
status	(object):																				
data	(object):																				
400	Bad Request																				
<pre>{}</pre>	<table border="1"> <thead> <tr> <th colspan="2">BadRequest</th> </tr> </thead> <tbody> <tr> <td>status</td> <td>(object):</td> </tr> <tr> <th colspan="2">status</th> </tr> <tr> <td>code</td> <td>(integer): A code that can provide more information when an error occurs.</td> </tr> <tr> <td>message</td> <td>(string):</td> </tr> </tbody> </table>	BadRequest		status	(object):	status		code	(integer): A code that can provide more information when an error occurs.	message	(string):										
BadRequest																					
status	(object):																				
status																					
code	(integer): A code that can provide more information when an error occurs.																				
message	(string):																				



Code	Reason														
404	Channel not found														
{}	<table border="1"> <tr> <td colspan="2">NotFound</td> </tr> <tr> <td>status</td> <td>(object):</td> </tr> <tr> <td colspan="2">status</td> </tr> <tr> <td>code</td> <td>(integer): A code that can provide more information when an error occurs.</td> </tr> <tr> <td>message</td> <td>(string): Provides additional information when a request returns an error response.</td> </tr> <tr> <td colspan="2">ResponseError</td> </tr> <tr> <td>status</td> <td>(object):</td> </tr> </table>	NotFound		status	(object):	status		code	(integer): A code that can provide more information when an error occurs.	message	(string): Provides additional information when a request returns an error response.	ResponseError		status	(object):
	NotFound														
	status	(object):													
	status														
	code	(integer): A code that can provide more information when an error occurs.													
	message	(string): Provides additional information when a request returns an error response.													
ResponseError															
status	(object):														
500	Internal Server Error														
{}	<table border="1"> <tr> <td colspan="2">ServerError</td> </tr> <tr> <td>status</td> <td>(object):</td> </tr> <tr> <td colspan="2">status</td> </tr> <tr> <td>code</td> <td>(integer): A code that can provide more information when an error occurs.</td> </tr> <tr> <td>message</td> <td>(string): Provides additional information when a request returns an error response.</td> </tr> <tr> <td colspan="2">ResponseError</td> </tr> <tr> <td>status</td> <td>(object):</td> </tr> </table>	ServerError		status	(object):	status		code	(integer): A code that can provide more information when an error occurs.	message	(string): Provides additional information when a request returns an error response.	ResponseError		status	(object):
	ServerError														
	status	(object):													
	status														
	code	(integer): A code that can provide more information when an error occurs.													
	message	(string): Provides additional information when a request returns an error response.													
ResponseError															
status	(object):														

## Usage

```
curl -X POST
-H "x-api-key: your_API_key"
-H "Content-Type: application/json"
-d '{}'
```

"https://api-demo.com/nexus/v3/channels/{channelId}/messages?"