



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

Genesys Multicloud CX Web-based API Reference

Third-Party Messaging Webhook

Contents

- [1 Base path: /nexus/v3](#)

Base path: /nexus/v3

| | |
|------|--|
| POST | /some/webhook/path Send a message to the third-party system |
|------|--|

Send a message to the third-party system. Refer to `OutgoingSmsMessage` and `OutgoingEmailMessage` models for examples and channel-specific differences.
Parameters

| Name | Default | Description | Parameter Type | Data Type | Required |
|-----------------|---------|---|----------------|-----------|----------|
| X-Hub-Signature | | The request signature, for example sha1=hash. The hash is built using the body of the message and secret for the channel. | header | string | true |
| X-B3-TraceId | | The unique trace ID for the request. | header | string | |
| messages | | Message | body | | true |

```
{}
```

Responses

| Code | Reason |
|------|-----------------------|
| 200 | Message has been sent |

```
{  
  "messageId": "string"  
}
```

OutgoingMessageResponse

messageId (string):

| Code | Reason | | |
|------|---|--|-------------------|
| | <table border="1"><tr><td data-bbox="813 287 1122 401"></td><td data-bbox="1122 287 1463 401">Unique message ID</td></tr></table> | | Unique message ID |
| | Unique message ID | | |
| 500 | Error occurred while sending message | | |

Usage

```
curl -X POST
-H "x-api-key: your_API_key"
-H "Content-Type: application/json"
-d '{}'
```

"https://api-demo.com/nexus/v3/some/webhook/path?"