



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

Genesys Multicloud CX Web-based API Reference

User Data Management API

Contents

- 1 Base path: /udm
 - 1.1 Version 10 API Requests
 - 1.2 Version 4 API Requests
 - 1.3 Version 3 API Requests

Base path: /udm

Version 10 API Requests

| | |
|-----|-------------|
| GET | /v10/cipher |
|-----|-------------|

This request is intended to get already uploaded certificate info.

Parameters

| Name | Default | Description | Parameter Type | Data Type | Required |
|---------------|---------|---|----------------|-----------|----------|
| x-api-key | | API key provided by Genesys. UDM deployments are accessed through GAPI-based URLs, for example, https://gapi-use1.genesyscloud.com/udm | header | string | |
| Authorization | | Bearer token in the format, Authorization: Bearer . See details about GAAuth token. | header | string | Yes |

Responses

| Code | Reason | | | | | | | | |
|--|---|-----------------|--|------|-----------|------|-----------|------|------------|
| 200 | 200 response | | | | | | | | |
| <pre>{ "ccid": "string", "name": "string", "size": 0, "lastModified": "string" }</pre> | <table><thead><tr><th colspan="2">CertificateInfo</th></tr></thead><tbody><tr><td>ccid</td><td>(string):</td></tr><tr><td>name</td><td>(string):</td></tr><tr><td>size</td><td>(integer):</td></tr></tbody></table> | CertificateInfo | | ccid | (string): | name | (string): | size | (integer): |
| CertificateInfo | | | | | | | | | |
| ccid | (string): | | | | | | | | |
| name | (string): | | | | | | | | |
| size | (integer): | | | | | | | | |

| Code | Reason |
|------|------------------------|
| } | lastModified (string): |

Usage

```
curl -X GET
-H "x-api-key: your_API_key"
-H "Content-Type: application/json"
-H "Authorization: Bearer eyJhbGciOiJSU...afA1Q"
"https://api-demo.com/udm/v10/cipher?"
```

| | |
|------|-----------------------------------|
| POST | /v10/cipher/{certificatefilename} |
|------|-----------------------------------|

This request is intended to upload a certificate.

Parameters

| Name | Default | Description | Parameter Type | Data Type | Required |
|---------------------|---------|---|----------------|-----------|----------|
| x-api-key | | API key provided by Genesys. UDM deployments are accessed through GAPI-based URLs, for example, https://gapi-use1.genesyscloud.com/udm | header | string | |
| certificatefilename | | | path | string | true |
| file | | The certificate content, field name must be 'file' | formData | file | true |
| Authorization | | Bearer token in the format, Authorization: Bearer . See details about GAuth token. | header | string | Yes |

Responses

| Code | Reason |
|----------|--------------|
| 201 | 201 response |
| "string" | |
| 400 | 400 response |

Usage

```
curl -X POST
-H "x-api-key: your_API_key"
-H "Content-Type: application/json"
-H "Authorization: Bearer eyJhbGciOiJSU...afA1Q"
"https://api-demo.com/udm/v10/cipher/{certificatefilename}?"
```

| | |
|-----|----------------------|
| GET | /v10/data/attributes |
|-----|----------------------|

This request is intended to get allow filtering on top of interaction attributes.
Parameters

| Name | Default | Description | Parameter Type | Data Type | Required |
|---------------|---------|---|----------------|-----------|----------|
| entities | | | query | string | |
| Authorization | | Bearer token in the format, Authorization: Bearer . See details about GAuth token. | header | string | Yes |

Responses

| Code | Reason |
|---------------|--------------|
| 200 | 200 response |
| <pre>{}</pre> | |

Usage

```
curl -X GET
-H "x-api-key: your_API_key"
-H "Content-Type: application/json"
-H "Authorization: Bearer eyJhbGciOiJSU...afA1Q"
"https://api-demo.com/udm/v10/data/attributes?entities=string"
```

| | |
|-----|------------------------|
| GET | /v10/data/job-statuses |
|-----|------------------------|

This request is intended to get a list of job statuses.
Parameters

| Name | Default | Description | Parameter Type | Data Type | Required |
|-----------|---------|---|----------------|-----------|----------|
| x-api-key | | API key provided by Genesys. UDM deployments are accessed through GAPI-based URLs, for example, | header | string | |

| Name | Default | Description | Parameter Type | Data Type | Required |
|---------------|---------|---|----------------|-----------|----------|
| | | https://gapi-use1.genesyscloud.com/udm | | | |
| Authorization | | Bearer token in the format, Authorization: Bearer . See details about GAuth token. | header | string | Yes |

Responses

| Code | Reason |
|---------------|--------------|
| 200 | 200 response |
| <pre>{}</pre> | |

Usage

```
curl -X GET
-H "x-api-key: your_API_key"
-H "Content-Type: application/json"
-H "Authorization: Bearer eyJhbGciOiJSU...afA1Q"
"https://api-demo.com/udm/v10/data/job-statuses?"
```

| | |
|-----|-------------------|
| GET | /v10/data/sources |
|-----|-------------------|

This request is intended to get a list of sources.

Parameters

| Name | Default | Description | Parameter Type | Data Type | Required |
|---------------|---------|--|----------------|-----------|----------|
| x-api-key | | API key provided by Genesys. UDM deployments are accessed through GAPI-based URLs, for example, https://gapi-use1.genesyscloud.com/udm | header | string | |
| Authorization | | Bearer token in the format, Authorization: Bearer . See details about GAuth token. | header | string | Yes |

Responses

| Code | Reason |
|---------------|--------------|
| 200 | 200 response |
| <pre>{}</pre> | |
| 204 | 204 response |

Usage

```
curl -X GET
-H "x-api-key: your_API_key"
-H "Content-Type: application/json"
-H "Authorization: Bearer eyJhbGciOiJSU...afA1Q"
"https://api-demo.com/udm/v10/data/sources?"
```

| | |
|-----|---------------------|
| GET | /v10/data/sub-types |
|-----|---------------------|

This request is intended to get a list of entities for specific type and source.

Parameters

| Name | Default | Description | Parameter Type | Data Type | Required |
|---------------|---------|---|----------------|-----------|----------|
| x-api-key | | API key provided by Genesys. UDM deployments are accessed through GAPI-based URLs, for example, https://gapi-use1.genesyscloud.com/udm | header | string | |
| dataType | | | query | string | |
| source | | | query | string | |
| Authorization | | Bearer token in the format, Authorization: Bearer . See details about GAuth token. | header | string | Yes |

Responses

| Code | Reason |
|---------------|--------------|
| 200 | 200 response |
| <pre>{}</pre> | |
| 204 | 204 response |

| Code | Reason |
|------|--------------|
| 400 | 400 response |

Usage

```
curl -X GET
-H "x-api-key: your_API_key"
-H "Content-Type: application/json"
-H "Authorization: Bearer eyJhbGciOiJSU...afA1Q"
"https://api-demo.com/udm/v10/data/sub-types?dataType=string&source=string"
```

| | |
|-----|-----------------|
| GET | /v10/data/types |
|-----|-----------------|

This request is intended to get a list of types for specific source.

Parameters

| Name | Default | Description | Parameter Type | Data Type | Required |
|---------------|---------|---|----------------|-----------|----------|
| x-api-key | | API key provided by Genesys. UDM deployments are accessed through GAPI-based URLs, for example, https://gapi-use1.genesyscloud.com/udm | header | string | |
| source | | | query | string | |
| Authorization | | Bearer token in the format, Authorization: Bearer . See details about GAuth token. | header | string | Yes |

Responses

| Code | Reason |
|------|---------------|
| 200 | 200 response |
| | <pre>{}</pre> |
| 204 | 204 response |

Usage

```
curl -X GET
-H "x-api-key: your_API_key"
-H "Content-Type: application/json"
-H "Authorization: Bearer eyJhbGciOiJSU...afA1Q"
"https://api-demo.com/udm/v10/data/types?source=string"
```

GET

/v10/export/history

This request is intended to get a list of history records.
Parameters

| Name | Default | Description | Parameter Type | Data Type | Required |
|---------------|---------|---|----------------|-----------|----------|
| x-api-key | | API key provided by Genesys. UDM deployments are accessed through GAPI-based URLs, for example, https://gapi-use1.genesyscloud.com/udm | header | string | |
| descAsc | | | query | string | |
| jobId | | | query | string | |
| type | | | query | string | |
| orderField | | | query | string | |
| fileName | | | query | string | |
| status | | | query | string | |
| from | | | query | string | |
| title | | | query | string | |
| size | | | query | string | |
| source | | | query | string | |
| bgUpdate | | | query | string | |
| Authorization | | Bearer token in the format, Authorization: Bearer . See details about GAAuth token. | header | string | Yes |

Responses

| Code | Reason | | | | | | | | | | |
|---|---|-------|--|---------------|--|-------|------------|------|------------|-------|-----------------|
| 200 | 200 response | | | | | | | | | | |
| <pre>{ "count": 0, "from": 0, "items": [], "size": 0 }</pre> | <table border="1"> <thead> <tr> <th colspan="2">items</th> </tr> <tr> <th colspan="2">PagedResponse</th> </tr> </thead> <tbody> <tr> <td>count</td> <td>(integer):</td> </tr> <tr> <td>from</td> <td>(integer):</td> </tr> <tr> <td>items</td> <td>(array:object):</td> </tr> </tbody> </table> | items | | PagedResponse | | count | (integer): | from | (integer): | items | (array:object): |
| items | | | | | | | | | | | |
| PagedResponse | | | | | | | | | | | |
| count | (integer): | | | | | | | | | | |
| from | (integer): | | | | | | | | | | |
| items | (array:object): | | | | | | | | | | |

| Code | Reason |
|--------|-----------------|
| } } | size (integer): |
| 204 | 204 response |

Usage

```
curl -X GET
-H "x-api-key: your_API_key"
-H "Content-Type: application/json"
-H "Authorization: Bearer eyJhbGciOiJSU...afA1Q"
"https://api-demo.com/udm/v10/export/history?descAsc=string&jobId=string&type=string&ofField=string&fileName=string&status=string&from=string&title=string"
```

| | |
|--------|---------------------|
| DELETE | /v10/export/history |
|--------|---------------------|

This request is intended to delete a bunch of history records.

Parameters

| Name | Default | Description | Parameter Type | Data Type | Required |
|---------------|---------|---|----------------|-----------|----------|
| x-api-key | | API key provided by Genesys. UDM deployments are accessed through GAPI-based URLs, for example, https://gapi-use1.genesyscloud.com/udm | header | string | |
| jobIDs | | | query | string | true |
| Authorization | | Bearer token in the format, Authorization: Bearer . See details about GAuth token. | header | string | Yes |

Responses

| Code | Reason |
|------|--------------|
| 204 | 204 response |
| 400 | 400 response |

Usage

```
curl -X DELETE
-H "x-api-key: your_API_key"
-H "Content-Type: application/json"
-H "Authorization: Bearer eyJhbGciOiJSU...afA1Q"
"https://api-demo.com/udm/v10/export/history?jobIDs=string"
```

| | |
|-----|--------------------------|
| GET | /v10/export/history/{id} |
|-----|--------------------------|

This request is intended to get history record info.

Parameters

| Name | Default | Description | Parameter Type | Data Type | Required |
|---------------|---------|---|----------------|-----------|----------|
| x-api-key | | API key provided by Genesys. UDM deployments are accessed through GAPI-based URLs, for example, https://gapi-use1.genesyscloud.com/udm | header | string | |
| id | | | path | string | true |
| Authorization | | Bearer token in the format, Authorization: Bearer . See details about GAuth token. | header | string | Yes |

Responses

| Code | Reason | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|--|---|---------|--|----|------------|------|-----------|--------|-----------|-------|-----------|---------------|-----------|----------|-----------|----------|------------|--------|-----------|-------------|-----------|----------|-----------|--------|-----------|-------------|-----------|-------|-----------------|----------|------------|
| 200 | 200 response | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <pre>{ "id": 0, "type": "string", "source": "string", "title": "string", "fileSplitSize": "string", "fileName": "string", "fileSize": 0, "status": "string", "createdDate": "string", "dateFrom": "string", "dateTo": "string", "description": "string", "media": [], "progress": 0, "parentId": 0, "exportAttachments": true }</pre> | <table border="1"> <thead> <tr> <th colspan="2">JobInfo</th> </tr> </thead> <tbody> <tr> <td>id</td> <td>(integer):</td> </tr> <tr> <td>type</td> <td>(string):</td> </tr> <tr> <td>source</td> <td>(string):</td> </tr> <tr> <td>title</td> <td>(string):</td> </tr> <tr> <td>fileSplitSize</td> <td>(string):</td> </tr> <tr> <td>fileName</td> <td>(string):</td> </tr> <tr> <td>fileSize</td> <td>(integer):</td> </tr> <tr> <td>status</td> <td>(string):</td> </tr> <tr> <td>createdDate</td> <td>(string):</td> </tr> <tr> <td>dateFrom</td> <td>(string):</td> </tr> <tr> <td>dateTo</td> <td>(string):</td> </tr> <tr> <td>description</td> <td>(string):</td> </tr> <tr> <td>media</td> <td>(array:string):</td> </tr> <tr> <td>progress</td> <td>(integer):</td> </tr> </tbody> </table> | JobInfo | | id | (integer): | type | (string): | source | (string): | title | (string): | fileSplitSize | (string): | fileName | (string): | fileSize | (integer): | status | (string): | createdDate | (string): | dateFrom | (string): | dateTo | (string): | description | (string): | media | (array:string): | progress | (integer): |
| JobInfo | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| id | (integer): | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| type | (string): | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| source | (string): | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| title | (string): | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| fileSplitSize | (string): | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| fileName | (string): | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| fileSize | (integer): | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| status | (string): | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| createdDate | (string): | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| dateFrom | (string): | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| dateTo | (string): | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| description | (string): | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| media | (array:string): | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| progress | (integer): | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

| Code | Reason | | | | |
|-------------------|--|----------|------------|-------------------|------------|
| | <table border="1"> <tr> <td>parentId</td> <td>(integer):</td> </tr> <tr> <td>exportAttachments</td> <td>(boolean):</td> </tr> </table> | parentId | (integer): | exportAttachments | (boolean): |
| parentId | (integer): | | | | |
| exportAttachments | (boolean): | | | | |
| 400 | 400 response | | | | |
| 404 | 404 response | | | | |

Usage

```
curl -X GET
-H "x-api-key: your_API_key"
-H "Content-Type: application/json"
-H "Authorization: Bearer eyJhbGciOiJSU...afA1Q"
"https://api-demo.com/udm/v10/export/history/{id}?"
```

| | |
|--------|--------------------------|
| DELETE | /v10/export/history/{id} |
|--------|--------------------------|

This request is intended to delete a history record.

Parameters

| Name | Default | Description | Parameter Type | Data Type | Required |
|---------------|---------|---|----------------|-----------|----------|
| x-api-key | | API key provided by Genesys. UDM deployments are accessed through GAPI-based URLs, for example, https://gapi-use1.genesyscloud.com/udm | header | string | |
| id | | | path | string | true |
| Authorization | | Bearer token in the format, Authorization: Bearer . See details about GAuth token. | header | string | Yes |

Responses

| Code | Reason |
|------|--------------|
| 204 | 204 response |
| 400 | 400 response |

Usage

```
curl -X DELETE
-H "x-api-key: your_API_key"
-H "Content-Type: application/json"
```

```
-H "Authorization: Bearer eyJhbGciOiJSU...afA1Q"
"https://api-demo.com/udm/v10/export/history/{id}?"
```

| | |
|-----|-----------------------------------|
| GET | /v10/export/history/{id}/progress |
|-----|-----------------------------------|

This request is intended to get job progress.

Parameters

| Name | Default | Description | Parameter Type | Data Type | Required |
|---------------|---------|---|----------------|-----------|----------|
| x-api-key | | API key provided by Genesys. UDM deployments are accessed through GAPI-based URLs, for example, https://gapi-use1.genesyscloud.com/udm | header | string | |
| id | | | path | string | true |
| Authorization | | Bearer token in the format, Authorization: Bearer . See details about GAAuth token. | header | string | Yes |

Responses

| Code | Reason | | | | | | |
|--|--|-------------|--|----------|------------|--------|-----------|
| 200 | 200 response | | | | | | |
| <pre>{ "progress": 0, "status": "string" }</pre> | <table border="1"><thead><tr><th colspan="2">JobProgress</th></tr></thead><tbody><tr><td>progress</td><td>(integer):</td></tr><tr><td>status</td><td>(string):</td></tr></tbody></table> | JobProgress | | progress | (integer): | status | (string): |
| JobProgress | | | | | | | |
| progress | (integer): | | | | | | |
| status | (string): | | | | | | |
| 400 | 400 response | | | | | | |

Usage

```
curl -X GET
-H "x-api-key: your_API_key"
-H "Content-Type: application/json"
-H "Authorization: Bearer eyJhbGciOiJSU...afA1Q"
"https://api-demo.com/udm/v10/export/history/{id}/progress?"
```

| | |
|-----|------------------|
| GET | /v10/export/jobs |
|-----|------------------|

This request is intended to get a list of jobs.

Parameters

| Name | Default | Description | Parameter Type | Data Type | Required |
|---------------|---------|---|----------------|-----------|----------|
| descAsc | | | query | string | |
| scheduleType | | | query | string | |
| x-api-key | | API key provided by Genesys. UDM deployments are accessed through GAPI-based URLs, for example, https://gapi-use1.genesyscloud.com/udm | header | string | |
| type | | | query | string | |
| orderField | | | query | string | |
| suspend | | | query | string | |
| from | | | query | string | |
| title | | | query | string | |
| size | | | query | string | |
| source | | | query | string | |
| bgUpdate | | | query | string | |
| Authorization | | Bearer token in the format, Authorization: Bearer . See details about GAAuth token. | header | string | Yes |

Responses

| Code | Reason | | | | | | | | | | | | |
|---|--|-------|--|---------------|--|-------|------------|------|------------|-------|-----------------|------|------------|
| 200 | 200 response | | | | | | | | | | | | |
| <pre>{ "count": 0, "from": 0, "items": [], "size": 0 }</pre> | <table border="1"> <thead> <tr> <th colspan="2">items</th> </tr> <tr> <th colspan="2">PagedResponse</th> </tr> </thead> <tbody> <tr> <td>count</td> <td>(integer):</td> </tr> <tr> <td>from</td> <td>(integer):</td> </tr> <tr> <td>items</td> <td>(array:object):</td> </tr> <tr> <td>size</td> <td>(integer):</td> </tr> </tbody> </table> | items | | PagedResponse | | count | (integer): | from | (integer): | items | (array:object): | size | (integer): |
| items | | | | | | | | | | | | | |
| PagedResponse | | | | | | | | | | | | | |
| count | (integer): | | | | | | | | | | | | |
| from | (integer): | | | | | | | | | | | | |
| items | (array:object): | | | | | | | | | | | | |
| size | (integer): | | | | | | | | | | | | |
| 204 | 204 response | | | | | | | | | | | | |

Usage

```
curl -X GET
```

```
-H "x-api-key: your_API_key"
-H "Content-Type: application/json"
-H "Authorization: Bearer eyJhbGciOiJSU...afA1Q"
"https://api-demo.com/udm/v10/export/
jobs?descAsc=string>heduleType=string&type=string_oField=string&suspend=string&from=string&title=string&size=string"
```

POST /v10/export/jobs

This request is intended to create a job.
Parameters

| Name | Default | Description | Parameter Type | Data Type | Required |
|---------------|---------|--|----------------|-----------|----------|
| x-api-key | | API key provided by Genesys. UDM deployments are accessed through GAPI-based URLs, for example, https://gapi-use1.genesyscloud.com/udm | header | string | |
| Authorization | | Bearer token in the format, Authorization: Bearer . See details about GAuth token. | header | string | Yes |
| Job | | | body | | true |

```
{
  "source": "string",
  "type": "string",
  "title": "string",
  "timeFrame": {
    "all": true,
    "dateFrom": "string",
    "dateTo": "string"
  },
  "description": "string",
  "schedulerParam": {
    "immediately": true,
    "cron": "string",
    "runs": "string",
    "startDate": "string"
  },
  "jobParams": {
    "fileSplitSize": "string",
    "type": "string",
    "media": [
    ],
    "exportAttachments": true
  },
}
```

| TimeFrame | |
|-------------------|---------------------------|
| all | (boolean, optional): |
| dateFrom | (string, optional): |
| dateTo | (string, optional): |
| SchedulerParam | |
| immediately | (boolean, optional): |
| cron | (string, optional): |
| runs | (string, optional): |
| startDate | (string, optional): |
| UcsJobParams | |
| fileSplitSize | (string, optional): |
| type | (string, required): |
| media | (array:string, required): |
| exportAttachments | (boolean, optional): |

| Name | Default | Description | Parameter Type | Data Type | Required |
|--------------------------------|---------|-------------|------------------------------------|--|----------|
| <pre>"suspended": true }</pre> | | | Job | | |
| | | | source | (string, required): source of job | |
| | | | type | (string, required): UCS or DataSync | |
| | | | title | (string, required): title of job | |
| | | | timeFrame | (TimeFrame, required): export time parameter of job | |
| | | | description | (string, optional): A description | |
| | | | schedulerParam | (SchedulerParam, required): scheduler parameter of job | |
| | | | jobParams | (UcsJobParams, required): parameters of job | |
| | | suspended | (boolean, required): suspended job | | |

Responses

| Code | Reason | |
|--|---------------|------------|
| 202 | 202 response | |
| <pre>{ "id": 0, "type": "string", "source": "string", "title": "string", "fileSplitSize": "string", "fileName": "string", "fileSize": 0, "status": "string", "createdDate": "string", "dateFrom": "string", "dateTo": "string", "description": "string", "media": [], "progress": 0, "parentId": 0, "exportAttachments": true }</pre> | JobInfo | |
| | id | (integer): |
| | type | (string): |
| | source | (string): |
| | title | (string): |
| | fileSplitSize | (string): |
| | fileName | (string): |
| | fileSize | (integer): |
| | status | (string): |
| | createdDate | (string): |
| | dateFrom | (string): |
| | dateTo | (string): |
| | description | (string): |

| Code | Reason | | | | | | | | |
|-------------------|--|-------|-----------------|----------|------------|----------|------------|-------------------|------------|
| | <table border="1"> <tr> <td>media</td> <td>(array:string):</td> </tr> <tr> <td>progress</td> <td>(integer):</td> </tr> <tr> <td>parentId</td> <td>(integer):</td> </tr> <tr> <td>exportAttachments</td> <td>(boolean):</td> </tr> </table> | media | (array:string): | progress | (integer): | parentId | (integer): | exportAttachments | (boolean): |
| media | (array:string): | | | | | | | | |
| progress | (integer): | | | | | | | | |
| parentId | (integer): | | | | | | | | |
| exportAttachments | (boolean): | | | | | | | | |
| 400 | 400 response | | | | | | | | |

Usage

```
curl -X POST
-H "x-api-key: your_API_key"
-H "Content-Type: application/json"
-H "Authorization: Bearer eyJhbGciOiJSU...afA1Q"
-d '{
  "source": "string",
  "type": "string",
  "title": "string",
  "timeFrame": {
    "all": true,
    "dateFrom": "string",
    "dateTo": "string"
  },
  "description": "string",
  "schedulerParam": {
    "immediately": true,
    "cron": "string",
    "runs": "string",
    "startDate": "string"
  },
  "jobParams": {
    "fileSplitSize": "string",
    "type": "string",
    "media": [
      ],
    "exportAttachments": true
  },
  "suspended": true
}'
"https://api-demo.com/udm/v10/export/jobs?"
```

| | |
|--------|------------------|
| DELETE | /v10/export/jobs |
|--------|------------------|

This request is intended to delete a bunch of jobs.

Parameters

| Name | Default | Description | Parameter Type | Data Type | Required |
|-----------|---------|---|----------------|-----------|----------|
| x-api-key | | API key provided by Genesys. UDM deployments are accessed through GAPI- | header | string | |

| Name | Default | Description | Parameter Type | Data Type | Required |
|---------------|---------|--|----------------|-----------|----------|
| | | based URLs, for example, https://gapi-use1.genesyscloud.com/udm | | | |
| jobIDs | | | query | string | true |
| Authorization | | Bearer token in the format, Authorization: Bearer . See details about GAuth token. | header | string | Yes |

Responses

| Code | Reason |
|------|--------------|
| 204 | 204 response |
| 400 | 400 response |

Usage

```
curl -X DELETE
-H "x-api-key: your_API_key"
-H "Content-Type: application/json"
-H "Authorization: Bearer eyJhbGciOiJSU...afA1Q"
"https://api-demo.com/udm/v10/export/jobs?jobIDs=string"
```

| | |
|------|------------------------------|
| POST | /v10/export/jobs/cancel/{id} |
|------|------------------------------|

This request is intended to cancel an unfinished job.

Parameters

| Name | Default | Description | Parameter Type | Data Type | Required |
|---------------|---------|---|----------------|-----------|----------|
| x-api-key | | API key provided by Genesys. UDM deployments are accessed through GAPI-based URLs, for example, https://gapi-use1.genesyscloud.com/udm | header | string | |
| id | | | path | string | true |
| Authorization | | Bearer token in the format, Authorization: Bearer . See details about GAuth token. | header | string | Yes |

Responses

| Code | Reason |
|------|--------------|
| 200 | 200 response |
| 400 | 400 response |
| 404 | 404 response |

Usage

```
curl -X POST
-H "x-api-key: your_API_key"
-H "Content-Type: application/json"
-H "Authorization: Bearer eyJhbGciOiJSU...afA1Q"
"https://api-demo.com/udm/v10/export/jobs/cancel/{id}?"
```

| | |
|------|------------------------------|
| POST | /v10/export/jobs/resume/{id} |
|------|------------------------------|

This request is intended to resume an unfinished job.

Parameters

| Name | Default | Description | Parameter Type | Data Type | Required |
|---------------|---------|---|----------------|-----------|----------|
| x-api-key | | API key provided by Genesys. UDM deployments are accessed through GAPI-based URLs, for example, https://gapi-use1.genesyscloud.com/udm | header | string | |
| id | | | path | string | true |
| Authorization | | Bearer token in the format, Authorization: Bearer . See details about GAuth token. | header | string | Yes |

Responses

| Code | Reason |
|------|--------------|
| 200 | 200 response |

```
{
  "id": 0,
  "type": "string",
  "source": "string",
  "title": "string",
  "fileSplitSize": "string",
  "JobInfo": {
    "id": (integer):
    "type": (string):
    "source": (string):
  }
}
```

| Code | Reason | | | | | | | | | | | | | | | | | | | | | | | | | | |
|---|--|--------|-----------|---------------|-----------|----------|-----------|----------|------------|--------|-----------|-------------|-----------|-------------|-----------|--------|-----------|-------------|-----------|-------|-----------------|----------|------------|----------|------------|-------------------|------------|
| <pre> "fileName": "string", "fileSize": 0, "status": "string", "createdDate": "string", "dateFrom": "string", "dateTo": "string", "description": "string", "media": [], "progress": 0, "parentId": 0, "exportAttachments": true } </pre> | <table border="1"> <tr><td>source</td><td>(string):</td></tr> <tr><td>fileSplitSize</td><td>(string):</td></tr> <tr><td>fileName</td><td>(string):</td></tr> <tr><td>fileSize</td><td>(integer):</td></tr> <tr><td>status</td><td>(string):</td></tr> <tr><td>createdDate</td><td>(string):</td></tr> <tr><td>createdDate</td><td>(string):</td></tr> <tr><td>dateTo</td><td>(string):</td></tr> <tr><td>description</td><td>(string):</td></tr> <tr><td>media</td><td>(array:string):</td></tr> <tr><td>progress</td><td>(integer):</td></tr> <tr><td>parentId</td><td>(integer):</td></tr> <tr><td>exportAttachments</td><td>(boolean):</td></tr> </table> | source | (string): | fileSplitSize | (string): | fileName | (string): | fileSize | (integer): | status | (string): | createdDate | (string): | createdDate | (string): | dateTo | (string): | description | (string): | media | (array:string): | progress | (integer): | parentId | (integer): | exportAttachments | (boolean): |
| source | (string): | | | | | | | | | | | | | | | | | | | | | | | | | | |
| fileSplitSize | (string): | | | | | | | | | | | | | | | | | | | | | | | | | | |
| fileName | (string): | | | | | | | | | | | | | | | | | | | | | | | | | | |
| fileSize | (integer): | | | | | | | | | | | | | | | | | | | | | | | | | | |
| status | (string): | | | | | | | | | | | | | | | | | | | | | | | | | | |
| createdDate | (string): | | | | | | | | | | | | | | | | | | | | | | | | | | |
| createdDate | (string): | | | | | | | | | | | | | | | | | | | | | | | | | | |
| dateTo | (string): | | | | | | | | | | | | | | | | | | | | | | | | | | |
| description | (string): | | | | | | | | | | | | | | | | | | | | | | | | | | |
| media | (array:string): | | | | | | | | | | | | | | | | | | | | | | | | | | |
| progress | (integer): | | | | | | | | | | | | | | | | | | | | | | | | | | |
| parentId | (integer): | | | | | | | | | | | | | | | | | | | | | | | | | | |
| exportAttachments | (boolean): | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 400 | 400 response | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 404 | 404 response | | | | | | | | | | | | | | | | | | | | | | | | | | |

Usage

```

curl -X POST
-H "x-api-key: your_API_key"
-H "Content-Type: application/json"
-H "Authorization: Bearer eyJhbGciOiJSU...afA1Q"
"https://api-demo.com/udm/v10/export/jobs/resume/{id}?"

```

| | |
|------|-------------------------------|
| POST | /v10/export/jobs/suspend/{id} |
|------|-------------------------------|

This request is intended to suspend an unfinished job.

Parameters

| Name | Default | Description | Parameter Type | Data Type | Required |
|---------------|---------|---|----------------|-----------|----------|
| x-api-key | | API key provided by Genesys. UDM deployments are accessed through GAPI-based URLs, for example, https://gapi-use1.genesyscloud.com/udm | header | string | |
| id | | | path | string | true |
| Authorization | | Bearer token in the format, | header | string | Yes |

| Name | Default | Description | Parameter Type | Data Type | Required |
|------|---------|--|----------------|-----------|----------|
| | | Authorization: Bearer . See details about GAAuth token. | | | |

Responses

| Code | Reason | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|--|--|---------|--|----|------------|------|-----------|--------|-----------|--------|-----------|---------------|-----------|----------|-----------|----------|------------|--------|-----------|-------------|-----------|-------------|-----------|--------|-----------|-------------|-----------|-------|-----------------|----------|------------|----------|------------|-------------------|------------|
| 200 | 200 response | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <pre>{ "id": 0, "type": "string", "source": "string", "title": "string", "fileSplitSize": "string", "fileName": "string", "fileSize": 0, "status": "string", "createdDate": "string", "dateFrom": "string", "dateTo": "string", "description": "string", "media": [], "progress": 0, "parentId": 0, "exportAttachments": true }</pre> | <table border="1"> <thead> <tr> <th colspan="2">JobInfo</th> </tr> </thead> <tbody> <tr> <td>id</td> <td>(integer):</td> </tr> <tr> <td>type</td> <td>(string):</td> </tr> <tr> <td>source</td> <td>(string):</td> </tr> <tr> <td>source</td> <td>(string):</td> </tr> <tr> <td>fileSplitSize</td> <td>(string):</td> </tr> <tr> <td>fileName</td> <td>(string):</td> </tr> <tr> <td>fileSize</td> <td>(integer):</td> </tr> <tr> <td>status</td> <td>(string):</td> </tr> <tr> <td>createdDate</td> <td>(string):</td> </tr> <tr> <td>createdDate</td> <td>(string):</td> </tr> <tr> <td>dateTo</td> <td>(string):</td> </tr> <tr> <td>description</td> <td>(string):</td> </tr> <tr> <td>media</td> <td>(array:string):</td> </tr> <tr> <td>progress</td> <td>(integer):</td> </tr> <tr> <td>parentId</td> <td>(integer):</td> </tr> <tr> <td>exportAttachments</td> <td>(boolean):</td> </tr> </tbody> </table> | JobInfo | | id | (integer): | type | (string): | source | (string): | source | (string): | fileSplitSize | (string): | fileName | (string): | fileSize | (integer): | status | (string): | createdDate | (string): | createdDate | (string): | dateTo | (string): | description | (string): | media | (array:string): | progress | (integer): | parentId | (integer): | exportAttachments | (boolean): |
| JobInfo | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| id | (integer): | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| type | (string): | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| source | (string): | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| source | (string): | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| fileSplitSize | (string): | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| fileName | (string): | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| fileSize | (integer): | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| status | (string): | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| createdDate | (string): | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| createdDate | (string): | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| dateTo | (string): | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| description | (string): | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| media | (array:string): | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| progress | (integer): | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| parentId | (integer): | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| exportAttachments | (boolean): | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 400 | 400 response | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 404 | 404 response | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

Usage

```
curl -X POST
-H "x-api-key: your_API_key"
-H "Content-Type: application/json"
-H "Authorization: Bearer eyJhbGciOiJSU...afA1Q"
"https://api-demo.com/udm/v10/export/jobs/suspend/{id}?"
```

| | |
|-----|-----------------------|
| GET | /v10/export/jobs/{id} |
|-----|-----------------------|

This request is intended to get job info.

Parameters

| Name | Default | Description | Parameter Type | Data Type | Required |
|---------------|---------|---|----------------|-----------|----------|
| x-api-key | | API key provided by Genesys. UDM deployments are accessed through GAPI-based URLs, for example, https://gapi-use1.genesyscloud.com/udm | header | string | |
| id | | | path | string | true |
| Authorization | | Bearer token in the format, Authorization: Bearer . See details about GAAuth token. | header | string | Yes |

Responses

| Code | Reason | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|--|--|---------|--|----|------------|------|-----------|--------|-----------|--------|-----------|---------------|-----------|----------|-----------|----------|------------|--------|-----------|-------------|-----------|-------------|-----------|--------|-----------|-------------|-----------|-------|-----------------|----------|------------|----------|------------|-------------------|------------|
| 200 | 200 response | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <pre>{ "id": 0, "type": "string", "source": "string", "title": "string", "fileSplitSize": "string", "fileName": "string", "fileSize": 0, "status": "string", "createdDate": "string", "dateFrom": "string", "dateTo": "string", "description": "string", "media": [], "progress": 0, "parentId": 0, "exportAttachments": true }</pre> | <table border="1"> <thead> <tr> <th colspan="2">JobInfo</th> </tr> </thead> <tbody> <tr> <td>id</td> <td>(integer):</td> </tr> <tr> <td>type</td> <td>(string):</td> </tr> <tr> <td>source</td> <td>(string):</td> </tr> <tr> <td>source</td> <td>(string):</td> </tr> <tr> <td>fileSplitSize</td> <td>(string):</td> </tr> <tr> <td>fileName</td> <td>(string):</td> </tr> <tr> <td>fileSize</td> <td>(integer):</td> </tr> <tr> <td>status</td> <td>(string):</td> </tr> <tr> <td>createdDate</td> <td>(string):</td> </tr> <tr> <td>createdDate</td> <td>(string):</td> </tr> <tr> <td>dateTo</td> <td>(string):</td> </tr> <tr> <td>description</td> <td>(string):</td> </tr> <tr> <td>media</td> <td>(array:string):</td> </tr> <tr> <td>progress</td> <td>(integer):</td> </tr> <tr> <td>parentId</td> <td>(integer):</td> </tr> <tr> <td>exportAttachments</td> <td>(boolean):</td> </tr> </tbody> </table> | JobInfo | | id | (integer): | type | (string): | source | (string): | source | (string): | fileSplitSize | (string): | fileName | (string): | fileSize | (integer): | status | (string): | createdDate | (string): | createdDate | (string): | dateTo | (string): | description | (string): | media | (array:string): | progress | (integer): | parentId | (integer): | exportAttachments | (boolean): |
| JobInfo | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| id | (integer): | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| type | (string): | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| source | (string): | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| source | (string): | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| fileSplitSize | (string): | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| fileName | (string): | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| fileSize | (integer): | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| status | (string): | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| createdDate | (string): | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| createdDate | (string): | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| dateTo | (string): | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| description | (string): | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| media | (array:string): | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| progress | (integer): | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| parentId | (integer): | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| exportAttachments | (boolean): | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 400 | 400 response | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

| Code | Reason |
|------|--------------|
| 404 | 404 response |

Usage

```
curl -X GET
-H "x-api-key: your_API_key"
-H "Content-Type: application/json"
-H "Authorization: Bearer eyJhbGciOiJSU...afA1Q"
"https://api-demo.com/udm/v10/export/jobs/{id}?"
```

| | |
|-----|-----------------------|
| PUT | /v10/export/jobs/{id} |
|-----|-----------------------|

This request is intended to update not started job.

Parameters

| Name | Default | Description | Parameter Type | Data Type | Required |
|---------------|---------|---|----------------|-----------|----------|
| x-api-key | | API key provided by Genesys. UDM deployments are accessed through GAPI-based URLs, for example, https://gapi-use1.genesyscloud.com/udm | header | string | |
| id | | | path | string | true |
| Authorization | | Bearer token in the format, Authorization: Bearer . See details about GAuth token. | header | string | Yes |
| Job | | | body | | true |

```
{
  "source": "string",
  "type": "string",
  "title": "string",
  "timeFrame": {
    "all": true,
    "dateFrom": "string",
    "dateTo": "string"
  },
  "description": "string",
  "schedulerParam": {
    "immediately": true,
    "cron": "string",
    "runs": "string",
    "startDate": "string"
  },
}
```

| TimeFrame | |
|----------------|----------------------|
| all | (boolean, optional): |
| dateFrom | (string, optional): |
| dateTo | (string, optional): |
| SchedulerParam | |
| immediately | (boolean, optional): |
| cron | (string, optional): |
| runs | (string, optional): |
| startDate | (string, optional): |
| UcsJobParams | |

| Name | Default | Description | Parameter Type | Data Type | Required |
|---|---------|-------------|------------------------------------|--|----------|
| <pre> "jobParams": { "fileSplitSize": "string", "type": "string", "media": [], "exportAttachments": true }, "suspended": true } </pre> | | | fileSplitSize | (string, optional): | |
| | | | type | (string, required): | |
| | | | media | (array:string, required): | |
| | | | exportAttachments | (boolean, optional): | |
| | | | Job | | |
| | | | source | (string, required): source of job | |
| | | | type | (string, required): UCS or DataSync | |
| | | | title | (string, required): title of job | |
| | | | timeFrame | (TimeFrame, required): export time parameter of job | |
| | | | description | (string, optional): A description | |
| | | | schedulerParam | (SchedulerParam, required): scheduler parameter of job | |
| | | | jobParams | (UcsJobParams, required): parameters of job | |
| | | suspended | (boolean, required): suspended job | | |

Responses

| Code | Reason | | | | | | | | | | | | | | | | | | | | | | | | |
|--|---|---------|--|--|----|------------|--|------|-----------|--|--------|-----------|--|-------|-----------|--|---------------|-----------|--|----------|-----------|--|----------|------------|--|
| 200 | 200 response | | | | | | | | | | | | | | | | | | | | | | | | |
| <pre> { "id": 0, "type": "string", "source": "string", "title": "string", "fileSplitSize": "string", "fileName": "string", "fileSize": 0, "status": "string", "createdDate": "string", "dateFrom": "string", "dateTo": "string", "description": "string", </pre> | <table border="1"> <thead> <tr> <th>JobInfo</th> <th></th> <th></th> </tr> </thead> <tbody> <tr> <td>id</td> <td>(integer):</td> <td></td> </tr> <tr> <td>type</td> <td>(string):</td> <td></td> </tr> <tr> <td>source</td> <td>(string):</td> <td></td> </tr> <tr> <td>title</td> <td>(string):</td> <td></td> </tr> <tr> <td>fileSplitSize</td> <td>(string):</td> <td></td> </tr> <tr> <td>fileName</td> <td>(string):</td> <td></td> </tr> <tr> <td>fileSize</td> <td>(integer):</td> <td></td> </tr> </tbody> </table> | JobInfo | | | id | (integer): | | type | (string): | | source | (string): | | title | (string): | | fileSplitSize | (string): | | fileName | (string): | | fileSize | (integer): | |
| JobInfo | | | | | | | | | | | | | | | | | | | | | | | | | |
| id | (integer): | | | | | | | | | | | | | | | | | | | | | | | | |
| type | (string): | | | | | | | | | | | | | | | | | | | | | | | | |
| source | (string): | | | | | | | | | | | | | | | | | | | | | | | | |
| title | (string): | | | | | | | | | | | | | | | | | | | | | | | | |
| fileSplitSize | (string): | | | | | | | | | | | | | | | | | | | | | | | | |
| fileName | (string): | | | | | | | | | | | | | | | | | | | | | | | | |
| fileSize | (integer): | | | | | | | | | | | | | | | | | | | | | | | | |

| Code | Reason | | | | | | | | | | | | | | | | | | |
|--|---|--------|-----------|-------------|-----------|----------|-----------|--------|-----------|-------------|-----------|-------|-----------------|----------|------------|----------|------------|-------------------|------------|
| <pre> "media": [], "progress": 0, "parentId": 0, "exportAttachments": true } </pre> | <table border="1"> <tr><td>status</td><td>(string):</td></tr> <tr><td>createdDate</td><td>(string):</td></tr> <tr><td>dateFrom</td><td>(string):</td></tr> <tr><td>dateTo</td><td>(string):</td></tr> <tr><td>description</td><td>(string):</td></tr> <tr><td>media</td><td>(array:string):</td></tr> <tr><td>progress</td><td>(integer):</td></tr> <tr><td>parentId</td><td>(integer):</td></tr> <tr><td>exportAttachments</td><td>(boolean):</td></tr> </table> | status | (string): | createdDate | (string): | dateFrom | (string): | dateTo | (string): | description | (string): | media | (array:string): | progress | (integer): | parentId | (integer): | exportAttachments | (boolean): |
| status | (string): | | | | | | | | | | | | | | | | | | |
| createdDate | (string): | | | | | | | | | | | | | | | | | | |
| dateFrom | (string): | | | | | | | | | | | | | | | | | | |
| dateTo | (string): | | | | | | | | | | | | | | | | | | |
| description | (string): | | | | | | | | | | | | | | | | | | |
| media | (array:string): | | | | | | | | | | | | | | | | | | |
| progress | (integer): | | | | | | | | | | | | | | | | | | |
| parentId | (integer): | | | | | | | | | | | | | | | | | | |
| exportAttachments | (boolean): | | | | | | | | | | | | | | | | | | |
| 400 | 400 response | | | | | | | | | | | | | | | | | | |
| 404 | 404 response | | | | | | | | | | | | | | | | | | |

Usage

```

curl -X PUT
-H "x-api-key: your_API_key"
-H "Content-Type: application/json"
-H "Authorization: Bearer eyJhbGciOiJSU...afA1Q"
-d '{
  "source": "string",
  "type": "string",
  "title": "string",
  "timeFrame": {
    "all": true,
    "dateFrom": "string",
    "dateTo": "string"
  },
  "description": "string",
  "schedulerParam": {
    "immediately": true,
    "cron": "string",
    "runs": "string",
    "startDate": "string"
  },
  "jobParams": {
    "fileSplitSize": "string",
    "type": "string",
    "media": [
      ],
      "exportAttachments": true
    ],
    "suspended": true
  }
}'
"https://api-demo.com/udm/v10/export/jobs/{id}?"

```

| | |
|--------|-----------------------|
| DELETE | /v10/export/jobs/{id} |
|--------|-----------------------|

This request is intended to delete finished job.

Parameters

| Name | Default | Description | Parameter Type | Data Type | Required |
|---------------|---------|---|----------------|-----------|----------|
| x-api-key | | API key provided by Genesys. UDM deployments are accessed through GAPI-based URLs, for example, https://gapi-use1.genesyscloud.com/udm | header | string | |
| id | | | path | string | true |
| Authorization | | Bearer token in the format, Authorization: Bearer . See details about GAuth token. | header | string | Yes |

Responses

| Code | Reason |
|------|--------------|
| 204 | 204 response |
| 400 | 400 response |

Usage

```
curl -X DELETE
-H "x-api-key: your_API_key"
-H "Content-Type: application/json"
-H "Authorization: Bearer eyJhbGciOiJSU...afA1Q"
"https://api-demo.com/udm/v10/export/jobs/{id}?"
```

| | |
|-----|---------------------|
| GET | /v10/file-metadatas |
|-----|---------------------|

This request is intended to get a list of files data.

Parameters

| Name | Default | Description | Parameter Type | Data Type | Required |
|------------|---------|-------------|----------------|-----------|----------|
| historyId | | | query | string | |
| descAsc | | | query | string | |
| jobTitle | | | query | string | |
| x-api-key | | | query | string | |
| name | | | query | string | |
| type | | | query | string | |
| source | | | query | string | |
| endDate | | | query | string | |
| orderField | | | query | string | |

| Name | Default | Description | Parameter Type | Data Type | Required |
|---------------|---------|--|----------------|-----------|----------|
| startDate | | | query | string | |
| from | | | query | string | |
| size | | | query | string | |
| bgUpdate | | | query | string | |
| Authorization | | Bearer token in the format, Authorization: Bearer . See details about GAAuth token. | header | string | Yes |

Responses

| Code | Reason | | | | | | | | | | | | |
|---|--|-------|--|---------------|--|-------|------------|------|------------|-------|-----------------|------|------------|
| 200 | 200 response | | | | | | | | | | | | |
| <pre>{ "count": 0, "from": 0, "items": [], "size": 0 }</pre> | <table border="1"> <thead> <tr> <th colspan="2">items</th> </tr> <tr> <th colspan="2">PagedResponse</th> </tr> </thead> <tbody> <tr> <td>count</td> <td>(integer):</td> </tr> <tr> <td>from</td> <td>(integer):</td> </tr> <tr> <td>items</td> <td>(array:object):</td> </tr> <tr> <td>size</td> <td>(integer):</td> </tr> </tbody> </table> | items | | PagedResponse | | count | (integer): | from | (integer): | items | (array:object): | size | (integer): |
| items | | | | | | | | | | | | | |
| PagedResponse | | | | | | | | | | | | | |
| count | (integer): | | | | | | | | | | | | |
| from | (integer): | | | | | | | | | | | | |
| items | (array:object): | | | | | | | | | | | | |
| size | (integer): | | | | | | | | | | | | |

Usage

```
curl -X GET
-H "x-api-key: your_API_key"
-H "Content-Type: application/json"
-H "Authorization: Bearer eyJhbGciOiJSU...afA1Q"
"https://api-demo.com/udm/v10/file-metadatas?historyId=string&descAsc=string&jobTitle=string&name=string&type=string&source=string&endDate=string"
```

| | |
|-----|------------|
| GET | /v10/files |
|-----|------------|

This request is intended to get a bunch of links to download files.

Parameters

| Name | Default | Description | Parameter Type | Data Type | Required |
|-----------|---------|--|----------------|-----------|----------|
| filename | | | query | string | |
| x-api-key | | API key provided by Genesys. UDM deployments are accessed through GAPI-based URLs, | header | string | |

| Name | Default | Description | Parameter Type | Data Type | Required |
|---------------|---------|--|----------------|-----------|----------|
| | | for example, https://gapi-use1.genesyscloud.com/udm | | | |
| Authorization | | Bearer token in the format, Authorization: Bearer . See details about GAuth token. | header | string | Yes |

Responses

| Code | Reason | | |
|-----------------------------------|---|--------------|----------------|
| 200 | 200 response | | |
| <pre>{ "path": "string" }</pre> | <table border="1"> <tr> <td>PreSignedUri</td> </tr> <tr> <td>path (string):</td> </tr> </table> | PreSignedUri | path (string): |
| PreSignedUri | | | |
| path (string): | | | |
| 400 | 400 response | | |
| 404 | 404 response | | |
| <pre>{}</pre> | | | |

Usage

```
curl -X GET
-H "x-api-key: your_API_key"
-H "Content-Type: application/json"
-H "Authorization: Bearer eyJhbGciOiJSU...afA1Q"
"https://api-demo.com/udm/v10/files?filename=string"
```

| | |
|--------|------------|
| DELETE | /v10/files |
|--------|------------|

This request is intended to delete a bunch of files.

Parameters

| Name | Default | Description | Parameter Type | Data Type | Required |
|-----------|---------|--|----------------|-----------|----------|
| filename | | | query | string | true |
| x-api-key | | API key provided by Genesys. UDM deployments are accessed through GAPI-based URLs, | header | string | |

| Name | Default | Description | Parameter Type | Data Type | Required |
|---------------|---------|--|----------------|-----------|----------|
| | | for example, https://gapi-use1.genesyscloud.com/udm | | | |
| Authorization | | Bearer token in the format, Authorization: Bearer . See details about GAuth token. | header | string | Yes |

Responses

| Code | Reason |
|------|--------------|
| 204 | 204 response |

Usage

```
curl -X DELETE
-H "x-api-key: your_API_key"
-H "Content-Type: application/json"
-H "Authorization: Bearer eyJhbGciOiJSU...afA1Q"
"https://api-demo.com/udm/v10/files?filename=string"
```

| | |
|-----|-----------------------|
| GET | /v10/files/{filename} |
|-----|-----------------------|

This request is intended to download a file.

Parameters

| Name | Default | Description | Parameter Type | Data Type | Required |
|---------------|---------|---|----------------|-----------|----------|
| filename | | | path | string | true |
| x-api-key | | API key provided by Genesys. UDM deployments are accessed through GAPI-based URLs, for example, https://gapi-use1.genesyscloud.com/udm | header | string | |
| Authorization | | Bearer token in the format, Authorization: Bearer . See details about GAuth token. | header | string | Yes |

Responses

| Code | Reason |
|------|--------------|
| 303 | 303 response |
| 404 | 404 response |

Usage

```
curl -X GET
-H "x-api-key: your_API_key"
-H "Content-Type: application/json"
-H "Authorization: Bearer eyJhbGciOiJSU...afA1Q"
"https://api-demo.com/udm/v10/files/{filename}?"
```

| | |
|--------|-----------------------|
| DELETE | /v10/files/{filename} |
|--------|-----------------------|

This request is intended to delete a file.

Parameters

| Name | Default | Description | Parameter Type | Data Type | Required |
|---------------|---------|---|----------------|-----------|----------|
| filename | | | path | string | true |
| x-api-key | | API key provided by Genesys. UDM deployments are accessed through GAPI-based URLs, for example, https://gapi-use1.genesyscloud.com/udm | header | string | |
| Authorization | | Bearer token in the format, Authorization: Bearer . See details about GAuth token. | header | string | Yes |

Responses

| Code | Reason |
|------|--------------|
| 204 | 204 response |

Usage

```
curl -X DELETE
-H "x-api-key: your_API_key"
-H "Content-Type: application/json"
-H "Authorization: Bearer eyJhbGciOiJSU...afA1Q"
"https://api-demo.com/udm/v10/files/{filename}?"
```

| | |
|-----|-----------------------|
| GET | /v10/resources/labels |
|-----|-----------------------|

This request is intended to get labels and their values.

Responses

| Code | Reason |
|------|--------------|
| 200 | 200 response |

Usage

```
curl -X GET
-H "x-api-key: your_API_key"
-H "Content-Type: application/json"
-H "Authorization: Bearer eyJhbGciOiJSU...afA1Q"
"https://api-demo.com/udm/v10/resources/labels?"
```

| | |
|-----|--------------|
| GET | /v10/version |
|-----|--------------|

This request is intended to get service info.

Parameters

| Name | Default | Description | Parameter Type | Data Type | Required |
|-----------|---------|---|----------------|-----------|----------|
| x-api-key | | API key provided by Genesys. UDM deployments are accessed through GAPI-based URLs, for example, https://gapi-use1.genesyscloud.com/udm | header | string | |

Responses

| Code | Reason |
|------|--------------|
| 200 | 200 response |

```
{
  "version": "string",
  "buildNumber": "string",
  "changeset": "string",
  "name": "string"
}
```

| VersionInfo | |
|-------------|-----------|
| version | (string): |
| buildNumber | (string): |
| changeset | (string): |
| name | (string): |

Usage

```
curl -X GET
-H "x-api-key: your_API_key"
-H "Content-Type: application/json"
"https://api-demo.com/udm/v10/version?"
```

Version 4 API Requests

Important

Although the User Data Management API still supports version 4 API calls documented below, they have been deprecated.

GET
Deprecated /v4/export/history
Get list of jobs info

Parameters

| Name | Default | Description | Parameter Type | Data Type | Required |
|------------|-----------|--|----------------|-----------|----------|
| descAsc | | Specifies the sort order of orderField. False for ascending order, true for descending | query | boolean | |
| orderField | | By which field to order | query | string | |
| title | | Filter that title contains | query | string | |
| fileName | | Filter that file name contains | query | string | |
| type | | Filter that type contains | query | string | |
| status | | Filter that file name contains | query | string | |
| from | 0 | Index of the first item to return | query | integer | |
| size | 999999999 | Maximum number of items to return | query | integer | |

Responses

| Code | Reason | | | | |
|---|---|---------------|--|-------|------------|
| 200 | Ok | | | | |
| <pre>{ "count": 0, "from": 0, }</pre> | <table border="1"><tr><td colspan="2">PagedResponse</td></tr><tr><td>count</td><td>(integer):</td></tr></table> | PagedResponse | | count | (integer): |
| PagedResponse | | | | | |
| count | (integer): | | | | |

| Code | Reason | | | | | | |
|--------------------------------------|--|------|------------|-------|-----------------|------|------------|
| <pre>"items": [], "size": 0 }</pre> | <table border="1"> <tr> <td>from</td> <td>(integer):</td> </tr> <tr> <td>items</td> <td>(array:object):</td> </tr> <tr> <td>size</td> <td>(integer):</td> </tr> </table> | from | (integer): | items | (array:object): | size | (integer): |
| from | (integer): | | | | | | |
| items | (array:object): | | | | | | |
| size | (integer): | | | | | | |
| 204 | No Content | | | | | | |

Usage

```
curl -X GET
-H "x-api-key: your_API_key"
-H "Content-Type: application/json"
```

```
"https://api-demo.com/udm/v4/export/history?descAsc=true&field=string&title=string&fileName=string&type=string&status=string&from=0&size=0"
```

| | |
|-------------------|--------------------------------|
| DELETE | /v4/export/history |
| Deprecated | Delete the specified jobs list |

In case if some jobs cannot be deleted internal server error is returned with a list of jobs that weren't deleted as json array in the body. A job with status in progress cannot be deleted.

Parameters

| Name | Default | Description | Parameter Type | Data Type | Required |
|--------|---------|-----------------------------------|----------------|-----------|----------|
| jobIDs | | A comma-separated list of job IDs | query | string | true |

Responses

| Code | Reason |
|------|-------------|
| 204 | No Content |
| 400 | Bad Request |

Usage

```
curl -X DELETE
-H "x-api-key: your_API_key"
-H "Content-Type: application/json"
```

```
"https://api-demo.com/udm/v4/export/history?jobIDs=string"
```

| | |
|-------------------|----------------------------|
| GET | /v4/export/history/{id} |
| Deprecated | Get specified jobs history |

Parameters

| Name | Default | Description | Parameter Type | Data Type | Required |
|------|---------|-------------------|----------------|-----------|----------|
| id | | The id of the job | path | string | true |

Responses

| Code | Reason | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|---|--|---------|--|----|------------|------|-----------|--------|-----------|-------|-----------|---------------|-----------|----------|-----------|----------|------------|--------|-----------|-------------|-----------|----------|-----------|--------|-----------|-------------|-----------|-------|-----------------|----------|------------|----------|------------|
| 200 | Ok | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <pre>{ "id": 0, "type": "string", "source": "string", "title": "string", "fileSplitSize": "string", "fileName": "string", "fileSize": 0, "status": "string", "createdDate": "string", "dateFrom": "string", "dateTo": "string", "description": "string", "media": [], "progress": 0, "parentId": 0 }</pre> | <table border="1"> <thead> <tr> <th colspan="2">JobInfo</th> </tr> </thead> <tbody> <tr> <td>id</td> <td>(integer):</td> </tr> <tr> <td>type</td> <td>(string):</td> </tr> <tr> <td>source</td> <td>(string):</td> </tr> <tr> <td>title</td> <td>(string):</td> </tr> <tr> <td>fileSplitSize</td> <td>(string):</td> </tr> <tr> <td>filename</td> <td>(string):</td> </tr> <tr> <td>fileSize</td> <td>(integer):</td> </tr> <tr> <td>status</td> <td>(string):</td> </tr> <tr> <td>createdDate</td> <td>(string):</td> </tr> <tr> <td>dateFrom</td> <td>(string):</td> </tr> <tr> <td>dateTo</td> <td>(string):</td> </tr> <tr> <td>description</td> <td>(string):</td> </tr> <tr> <td>media</td> <td>(array:string):</td> </tr> <tr> <td>progress</td> <td>(integer):</td> </tr> <tr> <td>parentId</td> <td>(integer):</td> </tr> </tbody> </table> | JobInfo | | id | (integer): | type | (string): | source | (string): | title | (string): | fileSplitSize | (string): | filename | (string): | fileSize | (integer): | status | (string): | createdDate | (string): | dateFrom | (string): | dateTo | (string): | description | (string): | media | (array:string): | progress | (integer): | parentId | (integer): |
| JobInfo | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| id | (integer): | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| type | (string): | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| source | (string): | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| title | (string): | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| fileSplitSize | (string): | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| filename | (string): | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| fileSize | (integer): | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| status | (string): | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| createdDate | (string): | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| dateFrom | (string): | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| dateTo | (string): | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| description | (string): | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| media | (array:string): | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| progress | (integer): | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| parentId | (integer): | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 400 | Bad Request | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 404 | ManualJob Not Found | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

Usage

```
curl -X GET
-H "x-api-key: your_API_key"
-H "Content-Type: application/json"

"https://api-demo.com/udm/v4/export/history/{id}?"
```

| | |
|------------------------------------|---|
| DELETE Deprecated | /v4/export/history/{id} Delete the specified job |
|------------------------------------|---|

A job in progress can not be deleted.

Parameters

| Name | Default | Description | Parameter Type | Data Type | Required |
|------|---------|-------------------|----------------|-----------|----------|
| id | | The id of the job | path | string | true |

Responses

| Code | Reason |
|------|-------------|
| 204 | No Content |
| 400 | Bad Request |

Usage

```
curl -X DELETE
-H "x-api-key: your_API_key"
-H "Content-Type: application/json"
```

"https://api-demo.com/udm/v4/export/history/{id}?"

| | |
|--------------------------|---|
| GET Deprecated | /v4/export/history/{id}/progress Get currently running job completion progress |
|--------------------------|---|

Return value is between 0 and 100 percent.

Parameters

| Name | Default | Description | Parameter Type | Data Type | Required |
|------|---------|---------------------------|----------------|-----------|----------|
| id | | The id of the job history | path | string | true |

Responses

| Code | Reason | | | | | | |
|--|--|-------------|--|----------|------------|--------|-----------|
| 200 | Ok | | | | | | |
| <pre>{ "progress": 0, "status": "string" }</pre> | <table border="1"> <thead> <tr> <th colspan="2">JobProgress</th> </tr> </thead> <tbody> <tr> <td>progress</td> <td>(integer):</td> </tr> <tr> <td>status</td> <td>(string):</td> </tr> </tbody> </table> | JobProgress | | progress | (integer): | status | (string): |
| JobProgress | | | | | | | |
| progress | (integer): | | | | | | |
| status | (string): | | | | | | |
| 400 | Bad Request | | | | | | |

Usage

```
curl -X GET
-H "x-api-key: your_API_key"
-H "Content-Type: application/json"
```

"https://api-demo.com/udm/v4/export/history/{id}/progress?"

| | |
|--------------------------|--|
| GET Deprecated | /v4/export/jobs Get list of jobs info |
|--------------------------|--|

Parameters

| Name | Default | Description | Parameter Type | Data Type | Required |
|--------------|-----------|--|----------------|-----------|----------|
| descAsc | | Specifies the sort order of orderField. False for ascending order, true for descending | query | boolean | |
| orderField | | By which field to order | query | string | |
| title | | Filter that title contains | query | string | |
| type | | Filter that type contains | query | string | |
| scheduleType | | Filter that file name contains | query | string | |
| suspend | | Filter that schedule type contains | query | boolean | |
| from | 0 | Index of the first item to return | query | integer | |
| size | 999999999 | Maximum number of items to return | query | integer | |

Responses

| Code | Reason | | | | | | | | | | |
|---|--|---------------|--|-------|------------|------|------------|-------|-----------------|------|------------|
| 200 | Ok | | | | | | | | | | |
| <pre>{ "count": 0, "from": 0, "items": [], "size": 0 }</pre> | <table border="1"> <thead> <tr> <th colspan="2">PagedResponse</th> </tr> </thead> <tbody> <tr> <td>count</td> <td>(integer):</td> </tr> <tr> <td>from</td> <td>(integer):</td> </tr> <tr> <td>items</td> <td>(array:object):</td> </tr> <tr> <td>size</td> <td>(integer):</td> </tr> </tbody> </table> | PagedResponse | | count | (integer): | from | (integer): | items | (array:object): | size | (integer): |
| PagedResponse | | | | | | | | | | | |
| count | (integer): | | | | | | | | | | |
| from | (integer): | | | | | | | | | | |
| items | (array:object): | | | | | | | | | | |
| size | (integer): | | | | | | | | | | |
| 204 | No Content | | | | | | | | | | |

Usage

```
curl -X GET
-H "x-api-key: your_API_key"
-H "Content-Type: application/json"
```

```
"https://api-demo.com/udm/v4/export/jobs?descAsc=true&orderField=string&title=string&type=string&scheduleType=string&suspend=true&from=0&size=0"
```

POST

Deprecated

/v4/export/jobs

Save specified manualJob

Parameters

| Name | Default | Description | Parameter Type | Data Type | Required | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|---|--|-------------|---|-----------|----------|-----------|--|--|-----|----------------------|--|----------|---------------------|--|--------|---------------------|--|----------------|--|--|-------------|----------------------|--|------|---------------------|--|------|---------------------|--|-----------|---------------------|--|--------------|--|--|---------------|---------------------|--|------|---------------------|--|-------|---------------------------|--|-----|--|--|--------|-----------------------------------|--|-------|----------------------------------|--|-----------|---|--|---------------|---|--|-------------|-----------------------------------|--|----------------|--|--|-----------|---|--|-----------|-----------------------------------|--|
| body | | | body | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <pre>{ "source": "string", "title": "string", "timeFrame": { "all": true, "dateFrom": "string", "dateTo": "string" }, "fileSplitSize": "string", "description": "string", "schedulerParam": { "immediately": true, "cron": "string", "runs": "string", "startDate": "string" }, "jobParams": { "fileSplitSize": "string", "type": "string", "media": [] }, "suspended": "string" }</pre> | | | <table border="1"> <tbody> <tr> <td colspan="3">TimeFrame</td> </tr> <tr> <td>all</td> <td>(boolean, optional):</td> <td></td> </tr> <tr> <td>dateFrom</td> <td>(string, optional):</td> <td></td> </tr> <tr> <td>dateTo</td> <td>(string, optional):</td> <td></td> </tr> <tr> <td colspan="3">SchedulerParam</td> </tr> <tr> <td>immediately</td> <td>(boolean, optional):</td> <td></td> </tr> <tr> <td>cron</td> <td>(string, optional):</td> <td></td> </tr> <tr> <td>runs</td> <td>(string, optional):</td> <td></td> </tr> <tr> <td>startDate</td> <td>(string, optional):</td> <td></td> </tr> <tr> <td colspan="3">UcsJobParams</td> </tr> <tr> <td>fileSplitSize</td> <td>(string, optional):</td> <td></td> </tr> <tr> <td>type</td> <td>(string, required):</td> <td></td> </tr> <tr> <td>media</td> <td>(array:string, required):</td> <td></td> </tr> <tr> <td colspan="3">Job</td> </tr> <tr> <td>source</td> <td>(string, required): source of job</td> <td></td> </tr> <tr> <td>title</td> <td>(string, required): title of job</td> <td></td> </tr> <tr> <td>timeFrame</td> <td>(TimeFrame, required): export time parameter of job</td> <td></td> </tr> <tr> <td>fileSplitSize</td> <td>(string, optional): size of splitted file</td> <td></td> </tr> <tr> <td>description</td> <td>(string, optional): A description</td> <td></td> </tr> <tr> <td>schedulerParam</td> <td>(SchedulerParam, required): scheduler parameter of job</td> <td></td> </tr> <tr> <td>jobParams</td> <td>(UcsJobParams, required): parameters of job</td> <td></td> </tr> <tr> <td>suspended</td> <td>(string, required): suspended job</td> <td></td> </tr> </tbody> </table> | | | TimeFrame | | | all | (boolean, optional): | | dateFrom | (string, optional): | | dateTo | (string, optional): | | SchedulerParam | | | immediately | (boolean, optional): | | cron | (string, optional): | | runs | (string, optional): | | startDate | (string, optional): | | UcsJobParams | | | fileSplitSize | (string, optional): | | type | (string, required): | | media | (array:string, required): | | Job | | | source | (string, required): source of job | | title | (string, required): title of job | | timeFrame | (TimeFrame, required): export time parameter of job | | fileSplitSize | (string, optional): size of splitted file | | description | (string, optional): A description | | schedulerParam | (SchedulerParam, required): scheduler parameter of job | | jobParams | (UcsJobParams, required): parameters of job | | suspended | (string, required): suspended job | |
| TimeFrame | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| all | (boolean, optional): | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| dateFrom | (string, optional): | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| dateTo | (string, optional): | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| SchedulerParam | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| immediately | (boolean, optional): | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| cron | (string, optional): | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| runs | (string, optional): | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| startDate | (string, optional): | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| UcsJobParams | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| fileSplitSize | (string, optional): | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| type | (string, required): | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| media | (array:string, required): | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Job | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| source | (string, required): source of job | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| title | (string, required): title of job | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| timeFrame | (TimeFrame, required): export time parameter of job | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| fileSplitSize | (string, optional): size of splitted file | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| description | (string, optional): A description | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| schedulerParam | (SchedulerParam, required): scheduler parameter of job | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| jobParams | (UcsJobParams, required): parameters of job | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| suspended | (string, required): suspended job | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

Responses

| Code | Reason | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|---|--|---------|--|----|------------|------|-----------|--------|-----------|-------|-----------|---------------|-----------|----------|-----------|----------|------------|--------|-----------|-------------|-----------|----------|-----------|--------|-----------|-------------|-----------|-------|-----------------|----------|------------|----------|------------|
| 202 | Accepted | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <pre>{ "id": 0, "type": "string", "source": "string", "title": "string", "fileSplitSize": "string", "fileName": "string", "fileSize": 0, "status": "string", "createdDate": "string", "dateFrom": "string", "dateTo": "string", "description": "string", "media": [], "progress": 0, "parentId": 0 }</pre> | <table border="1"> <thead> <tr> <th colspan="2">JobInfo</th> </tr> </thead> <tbody> <tr> <td>id</td> <td>(integer):</td> </tr> <tr> <td>type</td> <td>(string):</td> </tr> <tr> <td>source</td> <td>(string):</td> </tr> <tr> <td>title</td> <td>(string):</td> </tr> <tr> <td>fileSplitSize</td> <td>(string):</td> </tr> <tr> <td>fileName</td> <td>(string):</td> </tr> <tr> <td>fileSize</td> <td>(integer):</td> </tr> <tr> <td>status</td> <td>(string):</td> </tr> <tr> <td>createdDate</td> <td>(string):</td> </tr> <tr> <td>dateFrom</td> <td>(string):</td> </tr> <tr> <td>dateTo</td> <td>(string):</td> </tr> <tr> <td>description</td> <td>(string):</td> </tr> <tr> <td>media</td> <td>(array:string):</td> </tr> <tr> <td>progress</td> <td>(integer):</td> </tr> <tr> <td>parentId</td> <td>(integer):</td> </tr> </tbody> </table> | JobInfo | | id | (integer): | type | (string): | source | (string): | title | (string): | fileSplitSize | (string): | fileName | (string): | fileSize | (integer): | status | (string): | createdDate | (string): | dateFrom | (string): | dateTo | (string): | description | (string): | media | (array:string): | progress | (integer): | parentId | (integer): |
| JobInfo | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| id | (integer): | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| type | (string): | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| source | (string): | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| title | (string): | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| fileSplitSize | (string): | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| fileName | (string): | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| fileSize | (integer): | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| status | (string): | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| createdDate | (string): | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| dateFrom | (string): | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| dateTo | (string): | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| description | (string): | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| media | (array:string): | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| progress | (integer): | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| parentId | (integer): | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 400 | Bad Request | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

Usage

```
curl -X POST
-H "x-api-key: your_API_key"
-H "Content-Type: application/json"
-d '{
  "source": "string",
  "title": "string",
  "timeFrame": {
    "all": true,
    "dateFrom": "string",
    "dateTo": "string"
  },
  "fileSplitSize": "string",
  "description": "string",
  "schedulerParam": {
    "immediately": true,
    "cron": "string",
    "runs": "string",
    "startDate": "string"
  },
  "jobParams": {
    "fileSplitSize": "string",
    "type": "string",
    "media": [

```

```

    ]
  },
  "suspended": "string"
}'
"https://api-demo.com/udm/v4/export/jobs?"

```

| | |
|------------------------------------|---|
| DELETE Deprecated | /v4/export/jobs Delete the specified jobs list |
|------------------------------------|---|

In case if some jobs cannot be deleted internal server error is returned with a list of jobs that weren't deleted as json array in the body. A job with status in progress cannot be deleted.

Parameters

| Name | Default | Description | Parameter Type | Data Type | Required |
|--------|---------|-----------------------------------|----------------|-----------|----------|
| jobIDs | | A comma-separated list of job IDs | query | string | true |

Responses

| Code | Reason |
|------|-------------|
| 204 | No Content |
| 400 | Bad Request |

Usage

```

curl -X DELETE
-H "x-api-key: your_API_key"
-H "Content-Type: application/json"
"https://api-demo.com/udm/v4/export/jobs?jobIDs=string"

```

| | |
|----------------------------------|---|
| POST Deprecated | /v4/export/jobs/cancel/{id} Cancel running |
|----------------------------------|---|

Parameters

| Name | Default | Description | Parameter Type | Data Type | Required |
|------|---------|-------------------|----------------|-----------|----------|
| id | | The id of the job | path | string | true |

Responses

| Code | Reason |
|------|-------------|
| 200 | Ok |
| 400 | Bad Request |
| 404 | Not Found |

Usage

```

curl -X POST
-H "x-api-key: your_API_key"

```

-H "Content-Type: application/json"

"https://api-demo.com/udm/v4/export/jobs/cancel/{id}?"

| | |
|-------------------|-----------------------------|
| POST | /v4/export/jobs/resume/{id} |
| Deprecated | Save specified manualjob |

Parameters

| Name | Default | Description | Parameter Type | Data Type | Required |
|------|---------|-------------------|----------------|-----------|----------|
| id | | The id of the job | path | string | true |

Responses

| Code | Reason |
|---|---------------|
| 200 | Ok |
| <pre>{ "status": { "code": 0, "detail": {}, "message": "successful" } }</pre> | |
| 400 | Bad Request |
| 404 | Job Not Found |

Usage

```
curl -X POST
-H "x-api-key: your_API_key"
-H "Content-Type: application/json"
```

"https://api-demo.com/udm/v4/export/jobs/resume/{id}?"

| | |
|-------------------|------------------------------|
| POST | /v4/export/jobs/suspend/{id} |
| Deprecated | Save specified manualjob |

Parameters

| Name | Default | Description | Parameter Type | Data Type | Required |
|------|---------|-------------------|----------------|-----------|----------|
| id | | The id of the job | path | string | true |

Responses

| Code | Reason |
|------|--------|
| 200 | Ok |

| Code | Reason |
|---|---------------|
| <pre>{ "status": { "code": 0, "detail": {}, "message": "successful" } }</pre> | |
| 400 | Bad Request |
| 404 | Job Not Found |

Usage

```
curl -X POST
-H "x-api-key: your_API_key"
-H "Content-Type: application/json"
```

"https://api-demo.com/udm/v4/export/jobs/suspend/{id}?"

| | |
|-------------------|----------------------|
| GET | /v4/export/jobs/{id} |
| Deprecated | Get specified job |

Parameters

| Name | Default | Description | Parameter Type | Data Type | Required |
|------|---------|-------------------|----------------|-----------|----------|
| id | | The id of the job | path | string | true |

Responses

| Code | Reason |
|--|--------|
| 200 | Ok |
| <pre>{ "id": "", "source": "string", "title": "string", "timeFrame": { "all": true, "dateFrom": "string", "dateTo": "string" }, "fileSplitSize": "string", "description": "string", "schedulerParam": { "immediately": true, "cron": "string", "runs": "string", "startDate": "string" }, "jobParams": {</pre> | |

| Code | Reason |
|---|---------------------|
| <pre> "fileSplitSize": "string", "type": "string", "media": [] }, "suspended": "string" } </pre> | |
| 400 | Bad Request |
| 404 | ManualJob Not Found |

Usage

```

curl -X GET
-H "x-api-key: your_API_key"
-H "Content-Type: application/json"

```

"https://api-demo.com/udm/v4/export/jobs/{id}?"

| | |
|-------------------|--------------------------|
| PUT | /v4/export/jobs/{id} |
| Deprecated | Save specified manualJob |

Parameters

| Name | Default | Description | Parameter Type | Data Type | Required | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|--|---------------------------|-------------|--|-----------|----------|-----------|--|-----|----------------------|----------|---------------------|--------|---------------------|----------------|--|-------------|----------------------|------|---------------------|------|---------------------|-----------|---------------------|--------------|--|---------------|---------------------|------|---------------------|-------|---------------------------|-----|--|
| id | | | path | string | true | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| body | | | body | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <pre> { "source": "string", "title": "string", "type": "string", "timeFrame": { "all": true, "dateFrom": "string", "dateTo": "string" }, "fileSplitSize": "string", "description": "string", "schedulerParam": { "immediately": true, "cron": "string", "runs": "string", "startDate": "string" }, "jobParams": { "fileSplitSize": "string", "type": "string", "media": [] } } </pre> | | | <table border="1"> <tr> <td colspan="2">TimeFrame</td> </tr> <tr> <td>all</td> <td>(boolean, optional):</td> </tr> <tr> <td>dateFrom</td> <td>(string, optional):</td> </tr> <tr> <td>dateTo</td> <td>(string, optional):</td> </tr> <tr> <td colspan="2">SchedulerParam</td> </tr> <tr> <td>immediately</td> <td>(boolean, optional):</td> </tr> <tr> <td>cron</td> <td>(string, optional):</td> </tr> <tr> <td>runs</td> <td>(string, optional):</td> </tr> <tr> <td>startDate</td> <td>(string, optional):</td> </tr> <tr> <td colspan="2">UcsJobParams</td> </tr> <tr> <td>fileSplitSize</td> <td>(string, optional):</td> </tr> <tr> <td>type</td> <td>(string, required):</td> </tr> <tr> <td>media</td> <td>(array:string, required):</td> </tr> <tr> <td colspan="2">Job</td> </tr> </table> | | | TimeFrame | | all | (boolean, optional): | dateFrom | (string, optional): | dateTo | (string, optional): | SchedulerParam | | immediately | (boolean, optional): | cron | (string, optional): | runs | (string, optional): | startDate | (string, optional): | UcsJobParams | | fileSplitSize | (string, optional): | type | (string, required): | media | (array:string, required): | Job | |
| TimeFrame | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| all | (boolean, optional): | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| dateFrom | (string, optional): | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| dateTo | (string, optional): | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| SchedulerParam | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| immediately | (boolean, optional): | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| cron | (string, optional): | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| runs | (string, optional): | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| startDate | (string, optional): | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| UcsJobParams | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| fileSplitSize | (string, optional): | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| type | (string, required): | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| media | (array:string, required): | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Job | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

| Name | Default | Description | Parameter Type | Data Type | Required |
|---|---------|-------------|-----------------------------------|--|----------|
| <pre> }, "suspended": "string" } </pre> | | | source | (string, required): source of job | |
| | | | title | (string, required): title of job | |
| | | | type | (string, required): type of job | |
| | | | timeFrame | (TimeFrame, required): export time parameter of job | |
| | | | fileSplitSize | (string, optional): size of splitted file | |
| | | | description | (string, optional): A description | |
| | | | schedulerParam | (SchedulerParam, required): scheduler parameter of job | |
| | | | jobParams | (UcsJobParams, required): parameters of job | |
| | | suspended | (string, required): suspended job | | |

Responses

| Code | Reason | | | | | | | | | | | | | | | | | | | | | | | | |
|---|--|---------|--|----|------------|------|-----------|--------|-----------|-------|-----------|---------------|-----------|----------|-----------|----------|------------|--------|-----------|-------------|-----------|----------|-----------|--------|-----------|
| 200 | Ok | | | | | | | | | | | | | | | | | | | | | | | | |
| <pre> { "id": 0, "type": "string", "source": "string", "title": "string", "fileSplitSize": "string", "fileName": "string", "fileSize": 0, "status": "string", "createdDate": "string", "dateFrom": "string", "dateTo": "string", "description": "string", "media": [], "progress": 0, "parentId": 0 } </pre> | <table border="1"> <thead> <tr> <th colspan="2">JobInfo</th> </tr> </thead> <tbody> <tr> <td>id</td> <td>(integer):</td> </tr> <tr> <td>type</td> <td>(string):</td> </tr> <tr> <td>source</td> <td>(string):</td> </tr> <tr> <td>title</td> <td>(string):</td> </tr> <tr> <td>fileSplitSize</td> <td>(string):</td> </tr> <tr> <td>fileName</td> <td>(string):</td> </tr> <tr> <td>fileSize</td> <td>(integer):</td> </tr> <tr> <td>status</td> <td>(string):</td> </tr> <tr> <td>createdDate</td> <td>(string):</td> </tr> <tr> <td>dateFrom</td> <td>(string):</td> </tr> <tr> <td>dateTo</td> <td>(string):</td> </tr> </tbody> </table> | JobInfo | | id | (integer): | type | (string): | source | (string): | title | (string): | fileSplitSize | (string): | fileName | (string): | fileSize | (integer): | status | (string): | createdDate | (string): | dateFrom | (string): | dateTo | (string): |
| JobInfo | | | | | | | | | | | | | | | | | | | | | | | | | |
| id | (integer): | | | | | | | | | | | | | | | | | | | | | | | | |
| type | (string): | | | | | | | | | | | | | | | | | | | | | | | | |
| source | (string): | | | | | | | | | | | | | | | | | | | | | | | | |
| title | (string): | | | | | | | | | | | | | | | | | | | | | | | | |
| fileSplitSize | (string): | | | | | | | | | | | | | | | | | | | | | | | | |
| fileName | (string): | | | | | | | | | | | | | | | | | | | | | | | | |
| fileSize | (integer): | | | | | | | | | | | | | | | | | | | | | | | | |
| status | (string): | | | | | | | | | | | | | | | | | | | | | | | | |
| createdDate | (string): | | | | | | | | | | | | | | | | | | | | | | | | |
| dateFrom | (string): | | | | | | | | | | | | | | | | | | | | | | | | |
| dateTo | (string): | | | | | | | | | | | | | | | | | | | | | | | | |

| Code | Reason | | | | | | | | |
|-------------|---|-------------|-----------|-------|-----------------|----------|------------|----------|------------|
| | <table border="1"> <tr> <td>description</td> <td>(string):</td> </tr> <tr> <td>media</td> <td>(array:string):</td> </tr> <tr> <td>progress</td> <td>(integer):</td> </tr> <tr> <td>parentId</td> <td>(integer):</td> </tr> </table> | description | (string): | media | (array:string): | progress | (integer): | parentId | (integer): |
| description | (string): | | | | | | | | |
| media | (array:string): | | | | | | | | |
| progress | (integer): | | | | | | | | |
| parentId | (integer): | | | | | | | | |
| 400 | Bad Request | | | | | | | | |
| 404 | Job Not Found | | | | | | | | |

Usage

```
curl -X PUT
-H "x-api-key: your_API_key"
-H "Content-Type: application/json"
-d '{
  "source": "string",
  "title": "string",
  "timeFrame": {
    "all": true,
    "dateFrom": "string",
    "dateTo": "string"
  },
  "fileSplitSize": "string",
  "description": "string",
  "schedulerParam": {
    "immediately": true,
    "cron": "string",
    "runs": "string",
    "startDate": "string"
  },
  "jobParams": {
    "fileSplitSize": "string",
    "type": "string",
    "media": [
      ]
    },
    "suspended": "string"
  }'
"https://api-demo.com/udm/v4/export/jobs/{id}?"
```

| | |
|------------------------------------|--|
| DELETE Deprecated | /v4/export/jobs/{id} Delete the specified job |
|------------------------------------|--|

A job in progress can not be deleted.

Parameters

| Name | Default | Description | Parameter Type | Data Type | Required |
|------|---------|-------------------|----------------|-----------|----------|
| id | | The id of the job | path | string | true |

Responses

| Code | Reason |
|------|-------------|
| 204 | No Content |
| 400 | Bad Request |

Usage

```
curl -X DELETE
-H "x-api-key: your_API_key"
-H "Content-Type: application/json"
"https://api-demo.com/udm/v4/export/jobs/{id}?"
```

Version 3 API Requests

Important

Although the User Data Management API still supports version 3 API calls documented below, they have been deprecated.

| | |
|--------------------------|---|
| GET Deprecated | /v3/cipher Get certificate information |
|--------------------------|---|

Responses

| Code | Reason |
|------|--------|
| 200 | Ok |

| <pre>{ "ccid": "string", "name": "string", "size": 0, "lastModified": "string" }</pre> | <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th colspan="2">CertificateInfo</th> </tr> </thead> <tbody> <tr> <td style="text-align: right;">ccid</td> <td>(string):</td> </tr> <tr> <td style="text-align: right;">name</td> <td>(string):</td> </tr> <tr> <td style="text-align: right;">size</td> <td>(integer):</td> </tr> <tr> <td style="text-align: right;">lastModified</td> <td>(string):</td> </tr> </tbody> </table> | CertificateInfo | | ccid | (string): | name | (string): | size | (integer): | lastModified | (string): |
|--|--|-----------------|--|------|-----------|------|-----------|------|------------|--------------|-----------|
| CertificateInfo | | | | | | | | | | | |
| ccid | (string): | | | | | | | | | | |
| name | (string): | | | | | | | | | | |
| size | (integer): | | | | | | | | | | |
| lastModified | (string): | | | | | | | | | | |

Usage

```
curl -X GET
-H "x-api-key: your_API_key"
-H "Content-Type: application/json"
"https://api-demo.com/udm/v3/cipher?"
```

| | |
|---------------------------|--|
| POST Deprecated | /v3/cipher/{certificatefilename} POST the specified certificate |
|---------------------------|--|

Parameters

| Name | Default | Description | Parameter Type | Data Type | Required |
|---------------------|---------|-------------|----------------|-----------|----------|
| certificatefilename | | | path | string | true |
| file | | | formData | file | |

Responses

| Code | Reason |
|----------|-------------|
| 201 | Created |
| "string" | |
| 400 | Bad Request |

Usage

```
curl -X POST
-H "x-api-key: your_API_key"
-H "Content-Type: application/json"
```

"https://api-demo.com/udm/v3/cipher/{certificatefilename}?"

| | |
|--------------------------|---|
| GET Deprecated | /v3/data/job-statuses Get list of job statuses |
|--------------------------|---|

Responses

| Code | Reason | | | | | | |
|---|--|--------------|--|-------|-----------|-------|-----------|
| 200 | Ok | | | | | | |
| <pre>[{ "label": "string", "value": "string" }]</pre> | <table border="1"> <thead> <tr> <th colspan="2">KeyValueItem</th> </tr> </thead> <tbody> <tr> <td>label</td> <td>(string):</td> </tr> <tr> <td>value</td> <td>(string):</td> </tr> </tbody> </table> | KeyValueItem | | label | (string): | value | (string): |
| KeyValueItem | | | | | | | |
| label | (string): | | | | | | |
| value | (string): | | | | | | |

Usage

```
curl -X GET
-H "x-api-key: your_API_key"
-H "Content-Type: application/json"
```

"https://api-demo.com/udm/v3/data/job-statuses?"

| | |
|--------------------------|---|
| GET Deprecated | /v3/data/sources Get list of sources |
|--------------------------|---|

Responses

| Code | Reason |
|------|--------|
| 200 | Ok |

| Code | Reason | | | | | | |
|---|--|--------------|--|-------|-----------|-------|-----------|
| <pre>[{ "label": "string", "value": "string" }]</pre> | <table border="1"> <thead> <tr> <th colspan="2">KeyValueltem</th> </tr> </thead> <tbody> <tr> <td>label</td> <td>(string):</td> </tr> <tr> <td>value</td> <td>(string):</td> </tr> </tbody> </table> | KeyValueltem | | label | (string): | value | (string): |
| KeyValueltem | | | | | | | |
| label | (string): | | | | | | |
| value | (string): | | | | | | |
| 204 | No Content | | | | | | |

Usage

```
curl -X GET
-H "x-api-key: your_API_key"
-H "Content-Type: application/json"
```

"https://api-demo.com/udm/v3/data/sources?"

| | |
|-------------------|---------------------------|
| GET | /v3/data/sub-types |
| Deprecated | Get list of data subtypes |

Parameters

| Name | Default | Description | Parameter Type | Data Type | Required |
|----------|---------|---------------------------------|----------------|-----------|----------|
| source | | Filter data sub types by source | query | string | |
| dataType | | Filter data types by type | query | string | |

Responses

| Code | Reason | | | | | | | | | | | | |
|---|--|---------|--|------|-----------|-------------|-----------|--------|-----------|----------|-----------|---------|------------|
| 200 | Ok | | | | | | | | | | | | |
| <pre>[{ "name": "string", "displayName": "string", "source": "string", "dataType": "string", "enabled": true }]</pre> | <table border="1"> <thead> <tr> <th colspan="2">SubType</th> </tr> </thead> <tbody> <tr> <td>name</td> <td>(string):</td> </tr> <tr> <td>displayName</td> <td>(string):</td> </tr> <tr> <td>source</td> <td>(string):</td> </tr> <tr> <td>dataType</td> <td>(string):</td> </tr> <tr> <td>enabled</td> <td>(boolean):</td> </tr> </tbody> </table> | SubType | | name | (string): | displayName | (string): | source | (string): | dataType | (string): | enabled | (boolean): |
| SubType | | | | | | | | | | | | | |
| name | (string): | | | | | | | | | | | | |
| displayName | (string): | | | | | | | | | | | | |
| source | (string): | | | | | | | | | | | | |
| dataType | (string): | | | | | | | | | | | | |
| enabled | (boolean): | | | | | | | | | | | | |
| 204 | No Content | | | | | | | | | | | | |
| 400 | Bad Request | | | | | | | | | | | | |

Usage

```
curl -X GET
-H "x-api-key: your_API_key"
```

-H "Content-Type: application/json"

"https://api-demo.com/udm/v3/data/sub-types?source=string&dataType=string"

| | |
|--------------------------|-------------------------------------|
| GET Deprecated | /v3/data/types Get list of types |
|--------------------------|-------------------------------------|

Parameters

| Name | Default | Description | Parameter Type | Data Type | Required |
|--------|---------|-----------------------------|----------------|-----------|----------|
| source | | Filter data types by source | query | string | |

Responses

| Code | Reason | | | | | | |
|---|--|----------|--|------|-----------|--------|-----------|
| 200 | Ok | | | | | | |
| <pre>[{ "name": "string", "source": "string" }]</pre> | <table border="1"><thead><tr><th colspan="2">DataType</th></tr></thead><tbody><tr><td>name</td><td>(string):</td></tr><tr><td>source</td><td>(string):</td></tr></tbody></table> | DataType | | name | (string): | source | (string): |
| DataType | | | | | | | |
| name | (string): | | | | | | |
| source | (string): | | | | | | |
| 204 | No Content | | | | | | |

Usage

```
curl -X GET
-H "x-api-key: your_API_key"
-H "Content-Type: application/json"
```

"https://api-demo.com/udm/v3/data/types?source=string"

| | |
|--------------------------|--|
| GET Deprecated | /v3/file-metadatas Get list of files metadata |
|--------------------------|--|

Parameters

| Name | Default | Description | Parameter Type | Data Type | Required |
|------------|---------|--|----------------|-----------|----------|
| descAsc | | Specifies the sort order of orderField. False for ascending order, true for descending | query | boolean | |
| orderField | | By which field to order | query | string | |
| startDate | | startDate | query | string | |

| Name | Default | Description | Parameter Type | Data Type | Required |
|----------|-----------|-----------------------------------|----------------|-----------|----------|
| endDate | | Filter to which upload date | query | string | |
| name | | Filter that file name contains | query | string | |
| jobTitle | | Filter that job title contains | query | string | |
| type | | Filter that file type contains | query | string | |
| from | 0 | Index of the first item to return | query | integer | |
| size | 999999999 | Maximum number of items to return | query | integer | |

Responses

| Code | Reason |
|------|--------|
| 200 | Ok |

```

{
  "count": 0,
  "from": 0,
  "items": [
  ],
  "size": 0
}

```

| PagedResponse | |
|---------------|-----------------|
| count | (integer): |
| from | (integer): |
| items | (array:object): |
| size | (integer): |

Usage

```

curl -X GET
-H "x-api-key: your_API_key"
-H "Content-Type: application/json"

```

"https://api-demo.com/udm/v3/file-metadatas?descAsc=true&field=string&startDate=string&endDate=string&name=string&jobTitle=string&type=string&from=0&size=100"

| | |
|-------------------|---|
| GET | /v3/files |
| Deprecated | Get the list of pre-signed url for specified files list |

The maximum number of files is limited to 100. Also if some files cannot be found HTTP 404 is returned with a list of the files that weren't found as json array in the body

Parameters

| Name | Default | Description | Parameter Type | Data Type | Required |
|----------|---------|-------------|----------------|-----------|----------|
| filename | | A comma- | query | string | |

| Name | Default | Description | Parameter Type | Data Type | Required |
|------|---------|------------------------------|----------------|-----------|----------|
| | | separated list of file names | | | |

Responses

| Code | Reason | | |
|---|---|--------------|----------------|
| 200 | Ok | | |
| <pre>{ "path": "string" }</pre> | <table border="1"> <tr> <td>PreSignedUri</td> </tr> <tr> <td>path (string):</td> </tr> </table> | PreSignedUri | path (string): |
| PreSignedUri | | | |
| path (string): | | | |
| 400 | Bad Request | | |
| 404 | File Not Found | | |
| <pre>[{ "path": "string" }]</pre> | <table border="1"> <tr> <td>PreSignedUri</td> </tr> <tr> <td>path (string):</td> </tr> </table> | PreSignedUri | path (string): |
| PreSignedUri | | | |
| path (string): | | | |

Usage

```
curl -X GET
-H "x-api-key: your_API_key"
-H "Content-Type: application/json"
```

"https://api-demo.com/udm/v3/files?filename=string"

| | |
|------------------------------------|--|
| DELETE Deprecated | /v3/files Delete the specified files list |
|------------------------------------|--|

In case if some files cannot be deleted internal server error is returned with a list of files that weren't deleted as json array in the body.

Parameters

| Name | Default | Description | Parameter Type | Data Type | Required |
|----------|---------|--------------------------------------|----------------|-----------|----------|
| filename | | A comma-separated list of file names | query | string | true |

Responses

| Code | Reason |
|------|------------|
| 204 | No Content |

Usage

```
curl -X DELETE
-H "x-api-key: your_API_key"
-H "Content-Type: application/json"

"https://api-demo.com/udm/v3/files?filename=string"
```

| | |
|--------------------------|--|
| GET Deprecated | /v3/files/{filename} Get the specified file |
|--------------------------|--|

Parameters

| Name | Default | Description | Parameter Type | Data Type | Required |
|----------|---------|----------------------|----------------|-----------|----------|
| filename | | The name of the file | path | string | true |

Responses

| Code | Reason |
|------|----------------|
| 303 | See Other |
| 404 | File Not Found |

Usage

```
curl -X GET
-H "x-api-key: your_API_key"
-H "Content-Type: application/json"

"https://api-demo.com/udm/v3/files/{filename}?"
```

| | |
|-----------------------------|---|
| DELETE Deprecated | /v3/files/{filename} Delete the specified file |
|-----------------------------|---|

Parameters

| Name | Default | Description | Parameter Type | Data Type | Required |
|----------|---------|----------------------|----------------|-----------|----------|
| filename | | The name of the file | path | string | true |

Responses

| Code | Reason |
|------|------------|
| 204 | No Content |

Usage

```
curl -X DELETE
-H "x-api-key: your_API_key"
-H "Content-Type: application/json"

"https://api-demo.com/udm/v3/files/{filename}?"
```

| | |
|--------------------------|--|
| GET Deprecated | /v3/version Get version information |
|--------------------------|--|

Responses

| Code | Reason | | | | | | | | | | |
|--|--|-------------|--|---------|-----------|-------------|-----------|-----------|-----------|------|-----------|
| 200 | Ok | | | | | | | | | | |
| <pre>{ "version": "string", "buildNumber": "string", "changeset": "string", "name": "string" }</pre> | <table border="1"> <thead> <tr> <th colspan="2">VersionInfo</th> </tr> </thead> <tbody> <tr> <td>version</td> <td>(string):</td> </tr> <tr> <td>buildNumber</td> <td>(string):</td> </tr> <tr> <td>changeset</td> <td>(string):</td> </tr> <tr> <td>name</td> <td>(string):</td> </tr> </tbody> </table> | VersionInfo | | version | (string): | buildNumber | (string): | changeset | (string): | name | (string): |
| VersionInfo | | | | | | | | | | | |
| version | (string): | | | | | | | | | | |
| buildNumber | (string): | | | | | | | | | | |
| changeset | (string): | | | | | | | | | | |
| name | (string): | | | | | | | | | | |

Usage

```
curl -X GET
-H "x-api-key: your_API_key"
-H "Content-Type: application/json"
"https://api-demo.com/udm/v3/version?"
```