

GENESYS

This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

Genesys CX Insights 9.0 Projects Reference Guide

Agent metrics

Contents

- 1 Folder: Agent
- 2 Folder: Agent > Activity
- 3 Folder: Agent > Activity > Activity Call Survey
- 4 Folder: Agent > Activity > Activity User Data Example
- 5 Folder: Agent > Activity > Queue
- 6 Folder: Agent > Detail
- 7 Folder: Agent > Detail > Ixn State
- 8 Folder: Agent > Detail > Session
- 9 Folder: Agent > Detail > State
- 10 Folder: Agent > Group Membership
- 11 Folder: Agent > State and Reason
- 12 Folder: Agent > State and Reason > Interaction State
- 13 Folder: Agent > State and Reason > Interaction State > Interaction Predictive Routing
- 14 Folder: Agent > State and Reason > Summarized State

Use metrics in the Agent folder to build agent-related reports.

Related documentation:

•

Note the following:

- Unless other wise noted, metrics that show time, display a whole integer representing the number of seconds.
- For detailed information about the different metric types, see Project terminology and concepts.

Important

Objects in each folder or subfolder are designed to be used together to create reports. Avoid mixing attributes and metrics from multiple folders into your reports. One exception to this rule is objects in the Time folder; Time attributes can be used in any report, and most reports include at least one attribute from the Time folder.

Important

Use this document for Genesys CX Insights Multicloud deployments. For information relevant to Genesys CX Insights on-premises deployments, see the corresponding page in the *Genesys CX Insights on-premises Projects Reference Guide*.

The following Metrics are available in this folder and are described on this page.

Agent

Start Date Time Key

Agent > Activity

- % Abandoned Inviting
- · % Transfer Initiated
- % Transfer Received Accepted
- Abandoned Inviting

- Accepted
- Accepted Thread
- Accepted Unique
- Actionability
- Agent Queue A Group Combination
- Agent Queue Q Group Combination

- Agent Disconnect First
- Avg Actionability Score
- Avg Conference Accepted Handle Time
- Avg Consult Initiated Time
- Avg Consult Received Time
- Avg Consult Received Warm Time

- Avg Consult Received Warm Wrap Time
- Avg Consult Received Wrap Time
- · Avg Engage Time
- · Avg Handle Time
- · Avg Hold Time
- · Avg Influence Score
- · Avg Invite Time
- Avg Revenue
- · Avg Satisfaction
- · Avg Sentiment Score
- Avg Transfer Accepted Handle Time
- Avg Transfer Initiated Handle Time
- Avg Wrap Time
- Conference Accepted Time
- · Conference Initiated
- · Conference Offered
- Conference Received Accepted
- · Consult Initiated
- · Consult Initiated Time
- · Consult Offered
- · Consult Received Accepted
- Consult Received Accepted Warm
- · Consult Received Hold
- · Consult Received Time
- · Consult Received Warm Hold
- · Consult Received Warm Time
- · Consult Received Warm Wrap
- Consult Received Warm Wrap Time
- Consult Received Wrap
- · Consult Received Wrap Time

- Consult Responses
- Engage
- · Engage Time
- Focus
- Focus Time
- Group Combination
- · Handle Time
- Hold
- Hold Time
- Influence Score
- Invite
- Invite Time
- Not Accepted
- Offered
- Offered with Actionability
- · Offered with Influence
- · Offered with Revenue
- · Offered with Satisfaction
- · Offered with Sentiment
- Rejected
- Responded Unique
- Responses
- Revenue
- Satisfaction
- · Sentiment Score
- Short
- Start Date Time Key
- · Transfer Accepted Cold
- Transfer Accepted Time
- Transfer Accepted Warm
- Transfer Initiated Agent
- · Transfer Initiated Agent Cold
- Transfer Initiated Agent Warm
- · Transfer Initiated Time
- · Transfer Offered

- Transfer Received Accepted
- Wrap
- Wrap Time

Agent > Activity > Activity Call Survey

• There are no metrics in this folder

Agent > Activity > Activity User Data Example

There are no metrics in this folder

Agent > Activity > Queue

- % Abandoned Inviting
- % Accepted
- % Transfer Initiated
- % Transfer Initiated Agent
- % Transfer Received Accepted
- Abandoned Inviting
- Accepted
- Accepted Others
- Accepted Thread
- · Accepted Unique
- Actionability
- Agent Disconnect First
- · Avg Actionability Score
- Avg Consult Initiated Time
- · Avg Consult Received Time
- Avg Consult Received Warm Time
- Avg Consult Received Warm Wrap Time
- Avg Consult Received Wrap Time
- · Avg Engage Time
- Avg Handle Time

- · Avg Hold Time
- · Avg Influence Score
- · Avg Invite Time
- · Avg Revenue
- Avg Satisfaction
- · Avg Sentiment Score
- · Avg Wrap Time
- Conference Initiated
- Conference Received Accepted
- · Consult Initiated
- Consult Initiated Time
- · Consult Received Accepted
- Consult Received Accepted Warm
- · Consult Received Hold
- · Consult Received Time
- · Consult Received Warm Hold
- Consult Received Warm Time
- Consult Received Warm Wrap
- Consult Received Warm Wrap Time
- Consult Received Wrap
- Consult Received Wrap Time
- Consult Responses
- Engage
- · Engage Time
- Focus
- Focus Time
- Handle Time
- Hold
- · Hold Time
- Influence Score
- Invite
- Invite Time
- Not Accepted

- Offered
- Offered with Actionability
- · Offered with Influence
- · Offered with Revenue
- Offered with Satisfaction
- · Offered with Sentiment
- Rejected
- · Responded Unique
- Responses
- Revenue
- Satisfaction
- Sentiment Score
- Short
- Start Date Time Key
- Transfer Initiated Agent
- Transfer Received Accepted
- Wrap
- Wrap Time

Agent > Detail

There are no metrics in this folder

Agent > Detail > Ixn State

- Duration
- Start DateTime Key

Agent > Detail > Session

- Active Time
- Group Combination Detail Session
- Start DateTime Key

Agent > Detail > State

- Duration
- · Reason Time

Agent > Group Membership

Start Date Time Key

Agent > State and Reason

There are no metrics in this folder

Agent > State and Reason > Interaction State

- % Consult Received Time
- % Engage Time
- % Hold Time
- % Invite Time
- % Ixn Wrap Time
- % Not Ready In Time
- % Not Ready Out Time
- % Wrap In Time
- % Wrap Out Time
- Accepted
- Accepted Eventually
- · Consult Received Accepted
- Consult Received Time
- · Consult Received Wrap Time
- Engage Time
- Group Combination
- Hold
- Hold Time
- Invite Time
- Ixn Busy Time
- Ixn Wrap
- Ixn Wrap Time
- Not Accepted
- Not Ready In
- · Not Ready In Time
- · Not Ready Out
- Not Ready Out Time

- Offered
- Wrap In
- · Wrap In Time
- · Wrap Out
- · Wrap Out Time

Agent > State and Reason > Interaction State > Interaction Predictive Routing

- Active
- Agent Score
- · Avg Agent Score

Agent > State and Reason > Summarized State

- % Busy Time
- % Not Ready Reason Time
- % Not Ready Time
- % Occupancy

- % Omni Busy Time
- % Omni Not Ready Time
- % Omni Occupancy
- % Omni Other State Time
- % Omni Ready Time
- % Omni Wrap Time
- % Other State Time
- % Ready TIme
- % Wrap Time
- · Active Time
- Busy
- Busy Time
- Not Ready
- Not Ready Reason Count
- · Not Ready Reason Time
- Not Ready Time
- · Omni Active Time
- Omni Busy

- · Omni Busy Time
- · Omni Not Ready
- · Omni Not Ready Time
- Omni Other State Time
- Omni Ready
- · Omni Ready Time
- · Omni Wrap
- Omni Wrap Time
- Other State Time
- Ready
- · Ready Time
- Start Date Time Key
- State Reason
- · State Reason Time
- Wrap
- Wrap Time

Folder: Agent

Metric name: Start Date Time	e Key	Folder: Agent
Description: This metric is reserved for internal use to employ a key for a particular date and time from the AG2_AGENT, AG2_AGENT_GRP, or AG2_AGENT_QUEUE hierarchies.		
Calculation:		
Media type: All		Used in:
Data type: Number Metric type:		This metric is not used in any reports.

Folder: Agent > Activity

Folder: Metric name: % Abandoned Inviting Agent > Activity **Description:** The percentage of interactions that entered the contact center, were distributed to a resource, and subsequently abandoned while alerting/ringing at an agent's DN. This count includes shortabandoned interactions, and relies on the value of the short-abandoned threshold as configured in the [agg-gim-thld-ID-IXN] section. Calculation: Calculated based on the Abandoned Inviting and Offered Business Attribute metrics. Used in: Media type: Voice, Chat, Open (sync) This metric is not used in any reports. Data type: Number Metric type: Disposition Folder: **Metric name: % Transfer Initiated** Agent > Activity **Description:** The description of this metric depends on attributes and filters in the report query: · Agent Attribute: The percentage of accepted customer interactions that were transferred (warm or blind) by this agent. · Agent Group Attribute: The percentage of accepted customer interactions that were transferred (warm or blind) by agents who belong to this agent group. Calculation: Calculated based on the Transfer Initiated and Used in: Accepted Activity metrics. Agent Group Business Attribute Report Agent Group Interaction Handling Report Agent Performance Dashboard Media type: All Agent Report Data type: Number · Agent Task Dashboard Metric type: Disposition · Agent Utilization Email Report · Agent Utilization Report Task Routing Agent Activity • Task Routing Agent Group Activity **Metric name: % Transfer Received Accepted** Folder:

Agent > Activity

Description: The description of this metric depends on the attributes and filters in the report query:

- Agent Attribute: The percentage of accepted customer interactions that were successfully transferred (warm or blind) to this agent.
- Agent Group Attribute: The percentage of accepted customer interactions that were successfully transferred (warm or blind) to agents who belong to this agent group.

Calculation: Calculated based on the Transfer Initiated Agent and Accepted Agent Queue metrics.

Media type: All

Data type: Number Metric type: Disposition

Used in:

 Agent Group Interaction Handling Report

Metric name: Abandoned Inviting

Folder:

Agent > Activity

Description: The total number of times that interactions were abandoned/dropped while the interactions were alerting/ringing (for Agent, Group, or Agent and Queue, depending on GCXI Project attributes).

Calculation:

Media type: Voice, Chat,

Open (sync)

Data type: Number **Metric type:** Disposition

Used in:

- Agent Conduct Report
- · Agent Performance Dashboard
- Agent Report

Metric name: Accepted

Folder:

Agent > Activity

Description: The description of this metric varies depending on attributes and filters in the report query:

- Agent Attributes: The total number of times that customer interactions or warm consultations were accepted, answered, pulled, or initiated by this agent.
- Agent Group Attributes: The total number of times that customer interactions or warm consultations were accepted, answered, pulled, or initiated by agents who belong to this agent group.

For voice media, this metric is identical to Activity\Responses.

Calculation:

Used in:

Media type: All

Data type: Number Metric type: Disposition

- Agent Activity
- Agent Conduct Report
- Agent Group Business Attribute Report

- Agent Group Interaction handling Report
- Agent Interval Based Report
- · Agent Performance Dashboard
- Agent Report
- Agent Social Engagement Report
- · Agent Task Dashboard
- · Agent Utilization Email Report
- Agent Utilization Report
- Predictive Routing Agent Dashboard
- Predictive Routing Agent Occupancy Report (Active Time & Predictive)
- Survey Statistics Report
- Task Routing Agent Activity
- Task Routing Agent Group Activity

Metric name: Accepted Thread

Folder:

Agent > Activity

Description: The description of this metric varies depending on attributes and filters in the report query:

- Agent Attributes: The total number of customer-interaction threads that were accepted, pulled, or initiated for the first time by this agent.
- Agent Group Attributes: The total number of customer-interaction threads that were accepted, pulled, or initiated for the first time by agents who belong to this agent group.

This metric includes an agent's first participation in outbound replies to inbound interactions, and, for media other than email, yields the same values as the metric Accepted Unique.

Calculation:

Media type: Async

Data type: Number Metric type: Disposition

Used in:

• Agent Interaction Hierarchy Report

Metric name: Accepted Unique

Folder:

Agent > Activity

Description: The description of this metric varies depending on attributes and filters in the report query:

Agent Attributes: The total number of logical interactions that were accepted, pulled, or initiated for

the first time by this agent.

• Agent Group Attributes: The total number of logical interactions that were accepted, pulled, or initiated for the first time by agents who belong to this agent group.

Calculation:	
Media type: All	Used in:
Data type: Number Metric type: Disposition	Agent Interaction Hierarchy Report

Metric name: Actionability

Folder:

Agent > Activity

Description: The description of this metric varies depending on attributes and filters in the report query:

- Agent Attributes: The total score, assigned to interactions that were handled by this agent, that measures the degree to which interactions required agent attention.
- Agent Group Attributes: The total score, assigned to interactions that were handled by agents who belong to this agent group, that measures the degree to which interactions required agent attention.

This metric includes an agent's first participation in outbound replies to inbound interactions, and, for media other than email, yields the same values as the metric Accepted Unique.

Calculation:	
Media type: All	Used in:
Data type: Number Metric type: Disposition	This metric is not used in any reports.

Folder:

Description: This metric is reserved for internal use to employ a key for a particular agent-group combination from the AG2_AGENT_QUEUE aggregate table(s) only.

Calculation:

Media type: All

Data type: Number Metric type:

Description: This metric is not used in any reports.

Metric name: Agent - Queue Q Group Combination

Folder:

Agent > Activity

Description: This metric is reserved for internal use to employ a key for a particular agent-group combination from the AG2_AGENT_QUEUE aggregate table(s) only.

Calculation: Used in:

Metric name: Agent - Queue A Group Combination

Media type: All	
Data type: Number Metric type:	This metric is not used in any reports.

Metric name: Agent Disconnect First Folder: Agent > Activity

Description: The value presented in this metric varies depending on the attributes and filters used in a report:

- Agent Attribute: For voice interactions, the total number of times during the reporting interval that this agent released customer interactions before the other party did. For multimedia interactions, serves as a flag to indicate whether the interaction was stopped by one of the parties or by some outside entity (for example, Interaction Server or a Media Server).
- Agent Group Attribute: For voice interactions, the total number of times during the reporting interval that agents from this group released customer interactions before the other party did. For multimedia interactions, serves as a flag to indicate whether the interaction was stopped by one of the parties or by some outside entity (for example, Interaction Server or a Media Server).

The tally is incremented only when the system (such as the switch) provides such information.

Calculation:	Used in:
Media type: Chat, Open (sync), Voice Data type: Number Metric type: Disposition	Agent Conduct ReportAgent Performance DashboardAgent Report

Metric name: Avg Actionability Score Folder: Agent > Activity

Description: The value presented in this metric varies depending on the attributes and filters used in a report:

- Agent Attribute: The average score, assigned to interactions that were handled by this agent, measuring the degree to which interactions required agent attention.
- Agent Group Attribute: The average score, assigned to interactions that were handled by agents belonging to this agent group, measuring the degree to which interactions

The average considers only those interactions for which an Actionability Score was assigned.

Calculation: Calculated as AG2_AGENT_[*].ACTIONABILITY divided by AG2_AGENT_[*].ACTIONABILITY_OFFERED, or AG2_AGENT_GRP_[*].ACTIONABILITY divided by AG2_AGENT_GRP_[*].ACTIONABILITY_OFFERED

Media type: All

Data type: Number

Metric type: Disposition

Used in:

• Agent Social Engagement Report

Metric name: Avg Conference Accepted Handle Time

Introduced: 100.0.027.0001

Folder:

Agent > Activity

Description: Average Handle Time for conference interactions in which the agent participated. This metric includes time spent by all agents who participated in handling the interaction after this agent joined.

Calculation: Calculated based on the Conference Accepted

Time and Conference Received Accepted metrics.

Media type: All

Data type: Number Metric type: Disposition

Used in:

- Agent Transfer Summary Report
- · Transfer Dashboard

Metric name: Avg Consult Initiated Time

Folder:

Agent > Activity

Description: The value presented in this metric varies depending on the attributes and filters used in a report:

- Agent Attribute: The average amount of time that this agent was engaged on collaborations or simple consult interactions that the agent initiated, where the collaborations/consultations were associated with customer interactions.
- Agent Group Attribute: The average amount of time that agents who belong to this agent group were engaged on collaborations or simple consult interactions that the agents initiated, where the collaborations/consultations were associated with customer interactions.

Calculation: Calculated based on the Consult Initiated Time and Consult Initiated Activity metrics.

Media type: All (except

Chat)

Data type: Number Metric type: Disposition

Used in:

- · Agent Performance Dashboard
- Agent Report
- · Agent Utilization Report

Metric name: Avg Consult Received Time

Folder:

Agent > Activity

Description: The value presented in this metric varies depending on the attributes and filters used in a report:

- Agent Attribute: The average amount of time that this agent was engaged on collaborations or simple consultations that the agent received, where the collaborations/consultations were associated with customer interactions.
- · Agent Group Attribute: The average amount of time that agents who belong to this agent group were

engaged on collaborations or simple consultations that agents received, where the collaborations/consultations were associated with customer interactions.

Calculation: Calculated based on the Consult Received Time and Consult Received Accepted Activity metrics.

Media type: All (except

Chat)

Data type: Number **Metric type:** Disposition

Used in:

- Agent Group Business Attribute Report
- Agent Performance Dashboard
- Agent Report
- · Agent Utilization Report

Metric name: Avg Consult Received Warm Time

Folder:

Agent > Activity

Description: The value presented in this metric varies depending on the attributes and filters used in a report:

- Agent Attribute: The average amount of time that this agent was engaged as a recipient in collaborations or consultations, including related hold durations, where the collaborations/ consultations were associated with customer interactions.
- Agent Group Attribute: The average amount of time, in seconds, that agents who belong to this agent group were engaged as a recipient in collaborations or consultations, including related hold durations, where the collaborations/consultations were associated with customer interactions.

This metric is attributed to the interval in which the consult interaction is offered to the receiving agent. This metric excludes alert (ring) and ACW (Wrap) durations associated with the consult interactions.

Calculation: Calculated based on the Consult Received Warm Time and Consult Received Accepted Warm Activity metrics.

Media type: Voice

Data type: Number **Metric type:** Disposition

Used in:

- · Agent Performance Dashboard
- · Agent Report
- · Agent Utilization Report

Metric name: Avg Consult Received Warm Wrap Time

Folder:

Agent > Activity

Discontinued: 9.0

Description: This metric is no longer populated.

Calculation: Calculated based on the Consult Received Warm Wrap Time and Consult Received Warm Wrap Activity metrics.

Media type: Voice

Data type: Number Metric type: Dispostion

Used in:

- · Agent Performance Dashboard
- Agent Report
- · Agent Utilization Report

Metric name: Avg Consult Received Wrap Time

Folder:

Agent > Activity

Description: The value presented in this metric varies depending on the attributes and filters used in a report:

- Agent Attribute: The average amount of time that this agent was in ACW (Wrap) state following simple consultations that the agent accepted, where the consultations were associated with customer calls.
- Agent Group Attribute: The average amount of time that agents who belong to this agent group were
 in ACW state following simple consultations that the agents accepted, where the consultations were
 associated with customer calls.

This duration does not stop if the agents received or made calls while in ACW state. This metric is attributed to the interval in which this agent was offered the consult interaction for which ACW was invoked.

Calculation: Calculated based on the Consult Received Wrap Time and Consult Received Wrap Activity metrics.

Media type: Voice

Data type: Number Metric type: Disposition

Used in:

- · Agent Performance Dashboard
- Agent Report
- · Agent Utilization Report

Metric name: Avg Engage Time

Folder:

Agent > Activity

Description: The description of this metric varies depending on attributes and filters in the report query:

- Agent Attributes: The average amount of time that this agent was engaged with customers.
- Agent Group Attributes: The average amount of time that agents who belong to this agent group were engaged with customers.

Calculation: Calculated as Engage Time divided by Accepted Agent metrics.

Used in:

- Agent Activity
- Agent Group Business Attribute Report
- Agent Group Interaction Handling Report
- Agent Outbound Campaign Report
- Agent Performance Dashboard
- Agent Report
- Agent Task Dashboard
- · Agent Utilization Report
- Supervisor Dashboard

Media type: All

Data type: Number Metric type: Disposition

 Task Routing Agent Activity Task Routing Agent Group Activity
lask Routing Agent Group Activity

Metric name: Avg Handle Time Folder: Agent > Activity

Description: The description of this metric varies depending on attributes and filters in the report query:

- Agent Attribute: The average amount of time that this agent spent handling interactions that the agent received.
- Agent Group Attribute: The average amount of time that agents who belong to this agent group spent handling interactions that the agents received.

This metric is computed as handle time divided by the sum of accepted interactions and received consultations.

Calculation: Calculated as Handle Time divided by of Accepted Interactions and Received Consultations	
	Agent Activity
	Agent Conduct Report
	 Agent Group Business Attribute Report
	 Agent Group Interaction Handling Report
	Agent Interaction Hierarchy Report
Media type: All	Agent Outbound Campaign Report
Data type: Number Metric type: Disposition	Agent Performance Dashboard
	Agent Report
	Agent Task Dashboard
	Agent Utilization Email Report
	Agent Utilization Report
	Supervisor Dashboard
	Task Routing Agent Activity
	Task Routing Agent Group Activity

Metric name: Avg Hold Time	Folder:
	Agent > Activity

Description: The description of this metric varies depending on attributes and filters in the report query:

- · Agent Attribute: The average amount of time that this agent had customer interactions on hold.
- Agent Group Attribute: The average amount of time that agents who belong to this group had customer interactions on hold.

This metric is attributed to the interval in which interactions arrived at the agent (which can differ from the interval in which the interactions were placed on hold).

Calculation: Calculated based on the Hold and Hold Activity metrics.	Time Used in: • Agent Activity
Media type: Voice Data type: Number Metric type: Disposition	 Agent Conduct Report Agent Group Business Attribute Report Agent Group Interaction Handling Report Agent Outbound Campaign Report Agent Performance Dashboard Agent Report Agent Task Dashboard Agent Utilization Report Supervisor Dashboard Task Routing Agent Activity Task Routing Agent Group Activity

Metric name: Avg Influence Score Folder: Agent > Activity

Description: The description of this metric varies according to the attributes and filters in the report query:

Agent Attribute: The average score representing the clout amassed on social networks for interactions handled by this agent. Agent Group Attribute: The average score representing the clout amassed on social networks for interactions handled by agents belonging to this agent group. The average considers only those interactions for which an actionability score was assigned.

Media type: All Data type: Number Metric type: Disposition Used in: • Agent Social Engagement Report	Calculation:	Hand to
Buttu typer itamber	Media type: All	Used in:
		Agent Social Engagement Report

Metric name: Avg Invite Time	Folder:
	Agent > Activity

Description: The average amount of time that customer interactions alerted or rang at agent resources before the interactions were accepted, plus the average duration of dialing that agents performed, where the calls were successfully established.

This metric is attributed to the interval in which the interactions began. Note: The dialing component of this metric applies to voice media only.

Calculation: Calculated based on the Invite Time and Invite
Business Attribute metrics.

Media type: All

Data type: Number
Metric type: Disposition

Used in:

This metric is not used in any reports.

Agent > Activity

Agent > Activity

Metric name: Avg Revenue Folder:

Description: The description of this metric varies according to the attributes and filters in the report query:

- Agent Attribute: The average amount of revenue that is generated for interactions handled by this agent.
- Agent Group Attribute: The average amount of revenue that is generated for interactions handled by agents of this agent group.

The average considers only those interactions for which revenue was generated.

Calculation: Calculated based on the Revenue and Offered with Revenue Activity metrics.

Media type: All

Data type: Number Metric type: Dispotion

Metric type: Dispotion

Data type: Dispotion

Data type: Number Activity

Task Routing Agent Activity

Task Routing Agent Group Activity

Metric name: Avg Satisfaction Folder:

Description: The description of this metric varies according to the attributes and filters in the report query:

- Agent Dimension: The average customer-satisfaction score of interactions handled by this agent.
- Agent Group Dimension: The average customer-satisfaction score of interactions handled by agents who belong to this agent group.

The tally considers only those interactions for which customer satisfaction was recorded.

Calculation: Calculated based on the Satisfaction and Offered with Satisfaction Activity metrics.

Media type: All

Used in:

Agent Activity

Data type: Number **Metric type:** Disposition

- Task Routing Agent Activity
- Task Routing Agent Group Activity

Metric name: Avg Sentiment Score

Folder:

Agent > Activity

Description: The description of this metric varies according to the attributes and filters in the report query:

Agent Attribute: The average score reflecting the attitude expressed by customers for interactions that were handled by this agent. Agent Group Attribute: The average score reflecting the attitude expressed by customers for interactions that were handled by agents belonging to this agent group. The average considers only those interactions for which a sentiment score was assigned.

Calculation:

Media type: All

Data type: Number **Metric type:** Disposition

Used in:

• Agent Social Engagement Report

Metric name: Avg Transfer Accepted Handle Time

Introduced: 100.0.027.0001

Folder:

Agent > Activity

Description: Average Handle Time for interactions that arrived by transfer and were handled during the reporting interval. This metric includes only the time spent by the receiving agent, and includes both HOLD and ENGAGE times.

Calculation: Calculated based on the Transfer Accepted Time and Transfer Received Accepted metrics.

and mansier neceived Accepts

Data type: Number Metric type: Disposition

Media type: All

Used in:

- Agent Transfer Summary Report
- · Transfer Dashboard

Metric name: Avg Transfer Initiated Handle Time

Introduced: 100.0.027.0001

Folder:

Agent > Activity

Description: Average amount of time that the agent spent handling customer interactions that the agent later transferred, during the reporting interval.

Calculation: Calculated based on the Transfer Initiated Time

and Transfer Initiated Agent metrics.

Data type: Number Metric type: Disposition

Media type: All

Used in:

- Agent Transfer Summary Report
- Transfer Dashboard

Metric name: Avg Wrap Time

Folder:

Agent > Activity

Description: The description of this metric varies according to the attributes and filters in the report query:

- Agent Attribute: The average amount of time that this agent spent on customer interactions while in ACW (Wrap) state.
- Agent Group Attribute: The average amount of time that agents who belong to this agent group, spent on customer interactions while in ACW state.

Calculation:	Used in:
	Agent Activity
	Agent Conduct Report
	 Agent Group Business Attribute Report
	 Agent Group Interaction Handling Report
Media type: Voice	Agent Outbound Campaign Report
Data type: Number	Agent Performance Dashboard
Metric type: Disposition	Agent Report
	Agent Task Dashboard
	Agent Utilization Report
	Supervisor Dashboard
	Task Routing Agent Activity
	Task Routing Agent Group Activity

Metric name: Conference A Introduced: 100.0.027.0001	ccepted Time	Folder: Agent > Activity
Description: The amount of time that agent spent in conference interactions. This metric includes time spent by all agents who participated in handling the interaction after this agent joined.		
Calculation:		
Media type: All (except Email) Data type: Number Metric type: Disposition		Used in: This metric is not used in any reports.

Metric name: Conference Initiated Folder: Introduced: 100.0.027.0001 Agent > Activity **Description:** Total number of times that this Agent, Agent Group, or Agent and Queue, (depending on the relevant GCXI Project attributes for this metric) successfully initiated conferences for received customer interactions. Calculation: Used in: Media type: All (except • Agent Transfer Summary Report Email) · Agent Utilization Report Data type: Number Metric type: Disposition · Transfer Dashboard Metric name: Conference Offered Folder: Introduced: 100.0.027.0001 Agent > Activity **Description:** The total number of Conference interactions offered to the agent / agent group (depending on the relevant GCXI Project attributes for this metric) during the reporting interval. Calculation: Used in: Media type: Agent Transfer Summary Report Data type: · Transfer Dashboard Metric type: Disposition Folder: **Metric name: Conference Received Accepted** Agent > Activity **Description:** The description of this metric varies according to the attributes and filters in the report • Agent Attribute: The total number of times that this agent joined conferences to participate in customer interactions. · Agent Group Attribute: The total number of times that agents from this agent group joined conferences to participate in customer interactions. **Calculation:** Used in: Media type: All (except Email) · Agent Utilization Report Data type: Number Metric type: Disposition

Folder:

Metric name: Consult Initiated

Agent > Activity

Description: The description of this metric varies according to the attributes and filters in the report query:

- Agent Attribute: The total number of times that this agent initiated requests for collaboration or simple consultation, where the collaborations/consultations were established and associated with customer interactions.
- Agent Group Attribute: The total number of times that agents who belong to this agent group, initiated requests for collaboration or simple consultation, where the collaborations/consultations were established and associated with customer interactions.

Calculation:	Used in:
Media type: All (except Chat) Data type: Number Metric type: Disposition	Agent Conduct ReportAgent ReportAgent Utilization Report

Metric name: Consult Initiated Time

Folder:

Agent > Activity

Description: The description of this metric varies according to the attributes and filters in the report query:

- Agent Attribute: The total amount of time that this agent was engaged in collaborations or simple
 consultations that the agent requested, where the collaborations/consultations were associated with
 customer interactions.
- Agent Group Attribute: The total amount of time that agents who belong to this agent group were engaged in collaborations or simple consultations that the agents requested where the collaborations/consultations were associated with customer interactions.

Calculation: Media type: All (except Chat) Data type: Number Metric type: Disposition Used in: This metric is not used in any reports.

Metric name: Consult Offered Introduced: 100.0.027.0001 Agent > Activity

Description: The total number of consult interactions offered to the agent / agent group (depending on the relevant GCXI Project attributes for this metric) during the reporting interval.

Calculation:	Used in:
Media type: Data type: Metric type: Disposition	Agent Transfer Summary ReportTransfer Dashboard

Metric name: Consult Received Accepted Folder: Agent > Activity

Description: The description of this metric varies according to the attributes and filters in the report query:

- Agent Attribute: The total number of times that this agent received and accepted collaborations or simple consultations that were associated with customer interactions.
- Agent Group Attribute: The total number of times that agents who belong to this agent group received and accepted collaborations or simple consultations that were associated with customer interactions.

Calculation:	Used in:
Media type: All (except Chat) Data type: Number	 Agent Group Business Attribute Report Agent Interval Based Report
Metric type: Disposition	Agent Utilization Report

Metric name: Consult Received Accepted Warm Folder: Agent > Activity

Description: The description of this metric varies according to the attributes and filters in the report query:

- Agent Attribute: The total number of times that this agent participated in consultations that the agent received, where the consultations were associated with customer interactions that were transferred to or conferenced with the agent.
- Agent Group Attribute: The total number of times that agents who belong to this agent group participated in consultations that the agents received, where the consultations were associated with customer interactions that were transferred to or conferenced with the agents.

Calculation:	Used in:
Media type: Voice	osed III.
Data type: Number Metric type: Disposition	Agent Utilization Report
Metric name: Consult Received Hold	Folder:

Metric name: Consult Received Hold Folder: Agent > Activity

Description: The description of this metric varies according to the attributes and filters in the report query:

- Agent Attribute: The total number of times that this agent was on hold during simple consultations that the agent received where the consultations were associated with customer interactions.
- Agent Group Attribute: The total number of times that agents from this agent group were on hold during simple consultations that they received where the consultations were associated with customer interactions.

Calculation:	
Media type: Voice	Used in:
Data type: Number Metric type: Disposition	This metric is not used in any reports.

Metric name: Consult Received Time Folder: Agent > Activity

Description: The description of this metric varies according to the attributes and filters in the report query:

- Agent Attribute: The total amount of time that this agent was engaged as a recipient in collaborations or simple consultations, including related hold durations, where the collaborations/consultations were associated with customer interactions.
- Agent Group Attribute: The total amount of time that agents who belong to this agent group were engaged as recipients in collaboration or simple consultation, including related hold durations, where the collaborations/consultations were associated with customer interactions.

This metric is attributed to the interval in which this agent was offered the collaboration/consultation request.

Calculation: Calculated as the sum of AG2_AGENT_[*].CONSULT_RECEIVED_ENGAGE_TIME and AG2_AGENT_[*].CONSULT_RECEIVED_HOLD_TIME, or AG2_AGENT_GRP_[*].CONSULT_RECEIVED_ENGAGE_TIME and AG2_AGENT_GRP_[*].CONSULT_RECEIVED_HOLD_TIME

Media type: All (except

Chat)

Data type: Number Metric type: Disposition

Used in:

- Agent Group Business Attribute Report
- · Agent Interval Based Report
- Agent Performance Dashboard
- Agent Report
- Agent Summary Activity Report (Interaction)

Metric name: Consult Received Warm Hold

Folder:

Agent > Activity

Description: The description of this metric varies according to the attributes and filters in the report query:

- Agent Attribute: The total number of consultations that this agent had on hold where the consultations
 were associated with customer interactions, the agent was the recipient of the consultation requests,
 and the interactions were transferred to or conferenced with the agent.
- Agent Group Attribute: The total number of consultations that agents, who belong to this agent group, had on hold where the consultations were associated with customer interactions, the agents were the recipients of the consultation requests, and the interactions were transferred to or conferenced with the agents.

Calculation:	
Media type: Voice	Used in:
Data type: Number Metric type: Disposition	This metric is not used in any reports.

Metric name: Consult Received Warm Time Folder: Agent > Activity

Description: The description of this metric varies according to the attributes and filters in the report query:

- Agent Attribute: The total amount of time that this agent was engaged as a recipient in collaborations or consultations, including related hold durations, where the collaborations/consultations were associated with customer interactions.
- Agent Group Attribute: The total amount of time that agents who belong to this agent group were
 engaged as a recipient in collaborations or consultations, including related hold durations, where the
 collaborations/consultations were associated with customer interactions.

This metric is attributed to the interval in which the consult interaction is offered to the receiving agent. Time begins when the consult interaction is received and ends when the customer interaction is transferred to or conferenced with this agent. This metric excludes alert (ring) and ACW (Wrap) durations associated with the consult interactions.

Calculation: Calculated as the sum of AG2_AGENT_[*].CONSULT_RCV_WARM_ENGAGE_TIME and AG2_AGENT_[*].CONSULT_RCV_WARM_HOLD_TIME, or AG2_AGENT_GRP_[*].CONSULT_RCV_WARM_ENGAGE_TIME and AG2_AGENT_GRP_[*].CONSULT_RCV_WARM_HOLD_TIME

Media type: Voice

Data type: Number

Metric type: Disposition

Used in:

- Agent Performance Dashboard
- · Agent Report

Metric name: Consult Received Warm Wrap	Folder:	
Discontinued: 9.0	Agent > Activity	
Description: This metric is no longer populated.		
Calculation:	Used in:	
Media type: Voice	oseu III.	

Data type: Number
Metric type: Dispostion

This metric is not used in any reports.

Metric name: Consult Received Warm Wrap Time

Discontinued: 9.0

Description: This metric is no longer populated.

Calculation:

Media type: Voice
Data type: Number Metric type: Dispostion

Metric type: Dispostion

Folder:

Agent > Activity

Used in:

Agent Performance Dashboard

Agent Report

Metric name: Consult Received Wrap

Folder:

Agent > Activity

Description: The description of this metric varies depending on attributes and filters in the report query:

- Agent Attibute: The total number of times that this agent was in ACW (Wrap) state after requests for simple consultation that the agent accepted where the consultations were associated with customer interactions.
- Agent Group Attibute: The total number of times that agents who belong to this agent group were in ACW state after requests for simple consultation that they accepted where the consultations were associated with customer interactions.

Calculation:

Media type: Voice

Data type: Number Metric type: Disposition

Used in:

This metric is not used in any reports.

Metric name: Consult Received Wrap Time

Folder:

Agent > Activity

Description: The description of this metric varies depending on attributes and filters in the report query:

- Agent Attribute: The total amount of time that this agent was in ACW (Wrap) state after simple consultations that the agent accepted, where the consultations were associated with customer calls.
- Agent Group Attribute: The total amount of time that agents who belong to this agent group were in ACW state after simple consultations that the agents accepted, where the consultations were associated with customer calls.

This duration does not stop if the agents received or made calls while in ACW state. This metric is attributed to the interval in which this agent was offered the consult interaction for which ACW was invoked.

Calculation:	Used in:
Media type: Voice Data type: Number Metric type: Disposition	Agent Performance DashboardAgent Report

Metric name: Consult Responses Folder: Agent > Activity

Description: The description of this metric varies depending on attributes and filters in the report query:

- Agent Attribute: For email, the total number of collaboration replies that were initiated by this agent. For voice, this metric is the same as Agent > Activity > Consult Received Accepted.
- Agent Group Attribute: For email, the total number of collaboration replies that were initiated by agents who belong to this agent group. For voice, this metric is the same as Agent > Activity > Consult Received Accepted.

Calculation:	
Media type: All (except Chat) Data type: Number Metric type: Disposition	• Agent Utilization Report

Metric name: Engage
Introduced: 100.0.029.0000

Agent > Activity

Description: The number of times that agents were engaged with a customer during the reporting period. This metric is useful in calculating custom values such as Average Handle Time.

Calculation:

Media type: All

Data type: Number Metric type: Disposition

Used in:

This metric is not used in any reports.

Metric name: Engage Time

Folder:

Agent > Activity

Description: The description of this metric varies depending on attributes and filters in the report query:

- Agent Attribute: The total amount of time that this agent was engaged with customers on interactions that the agent received.
- Agent Group Attribute: The total amount of time that agents who belong to this agent group were engaged with customers on interactions that the agents received.

This metric excludes other interaction-related durations, such as hold time, ACW (Wrap) time, alert (ring) time, and time that is spent in collaboration or consultation.

Calculation:		Used in:
Media type: All Data type: Number Metric type: Disposition		 Agent Group Business Attribute Report Agent Interaction State Agent Interval Based Report Agent Outbound Campaign Report Agent Performance Dashboard Agent Report Agent Summary Activity Report (Interaction) Supervisor Dashboard
Metric name: Focus		Folder: Agent > Activity
Description: The total number of times that the agent was in the focus state while working on media sessions. Includes only cases where the agent was actively working on the interaction that is the subject of the IRF, and requires WDE is configured to report focus time.		
Calculation:		
Media type: Data type: Metric type: Disposition		Used in: This metric is not used in any reports.
Metric name: Focus Time		Folder: Agent > Activity
Description: The total amount of time that this agent spent in the focus state while working on media sessions. Includes only time that the agent spent actively processing the interaction, as reported by the agent desktop.		
Calculation:		
Media type: Data type: Metric type: Disposition		Used in: This metric is not used in any reports.
Metric name: Group Combi	nation	Folder: Agent > Activity

Description: This metric is reserved for internal use to employ a key for a particular agent-group combination from the AG2 AGENT hierarchy. Calculation: Used in: Media type: All This metric is not used in any reports. Data type: Number Metric type: Folder: Metric name: Handle Time Agent > Activity **Description:** The total amount of time that agents who belong to this agent group spent handling interactions that the agents received. Handle time is measured as the sum of engagement time (for example, talk time), hold time, ACW (Wrap) time, all consult time for interactions that the agent received, and all ACW time for consultations the agent received. Some of these components return zero values for some media types. Calculation: Calculated based on the Engage Time, Hold Used in: Time, Wrap Time, Consult Received Time, Consult Received Wrap Time, Consult Received Warm Time activity metrics. • Agent Group Business Attribute Report Media type: All · Agent Performance Dashboard Data type: Number Metric type: Disposition Agent Report Folder: **Metric name: Hold** Agent > Activity **Description:** The total number of times within the interval that this agent (or agents in this agent group) had customer calls on hold. **Calculation:** Used in: · Agent Interval Based Report Media type: Voice · Agent Performance Dashboard Data type: Number Agent Report Metric type: Disposition · Agent Utilization Report Folder: **Metric name: Hold Time** Agent > Activity **Description:** The total amount of time that this agent (or agents in this agent group) had customer interactions on hold. This metric counts all held durations for interactions, whether they were placed on hold once or more than once. Calculation: Used in:

Agent Group Business Attribute
Report
 Agent Interval Based Report
 Agent Outbound Campaign Report
 Agent Performance Dashboard
 Agent Report
 Agent Summary Activity Report
(Interaction)
 Supervisor Dashboard

Metric name: Influence Score

Folder:

Agent > Activity

Description: The total score that represents the customer's clout that has amassed on social networks for customer interactions that were handled by this agent (or by agents who are members of this agent group).

Calculation:

Media type: All

Data type: Number Metric type: Disposition

Used in:

This metric is not used in any reports.

Metric name: Invite

Folder:

Agent > Activity

Description: The total number of customer interactions that alerted or rang at this agent (or at agents who belong to this agent group) before the interactions were accepted plus the total number of dials that agents performed, where the calls were successfully established.

This metric is attributed to the interval in which the alerting/dialing first occurred.

Calculation:

Media type: All

Data type: Number Metric type: Disposition

Used in:

This metric is not used in any reports.

Metric name: Invite Time

Folder:

Agent > Activity

Description: The total amount of time that customer interactions alerted at this agent (or at agents who belong to this agent group), plus the total duration of the dialing that the agents performed.

- For the alerting component of this metric, interactions do not have to be established for this metric to be incremented.
- For the dialing component, dial duration is measured for established calls only.

This metric is attributed to the interval in which the alerting/dialing first occurred.

Calculation:	Used in:
Media type: All Data type: Number Metric type: Disposition	 Agent Interaction State Agent Summary Activity Report (Interaction) Supervisor Dashboard

Metric name: Not Accepted Folder:

Agent > Activity

Description: The total number of times that customer interactions were redirected to another resource upon no answer by this agent (or by agents who belong to this agent group), or were otherwise not accepted by such agents.

Calculation:	Used in:
Media type: All Data type: Number Metric type: Disposition	Agent Performance DashboardAgent ReportAgent Utilization Report

Metric name: Offered Folder: Agent > Activity

Description: The total number of times that interactions were received or initiated by this agent (for Agent reporting), or agents who belong to this agent group (for Agent Group reporting).

The count includes interactions that were abandoned while inviting, handling attempts that the agent rejected, and warm consultations and conferences that the agent received. This count excludes simple consultations, whether they were initiated or received. For AGT_AGENT_QUEUE records, this metric relies on the value of the **short-abandoned threshold** as configured in the **[agg-gim-thld-ID-IXN]** section.

 Agent Activity Agent Interaction Hierarchy Report Agent Performance Dashboard Agent Report Agent Report Agent Task Dashboard 	Calculation:	Used in:
Data type: Number Metric type: Disposition • Agent Performance Dashboard • Agent Report		Agent Activity
Metric type: Disposition • Agent Report	Media type: All	Agent Interaction Hierarchy Report
Agent Report		Agent Performance Dashboard
Agent Task Dashboard		Agent Report
		Agent Task Dashboard

· Agent Utilization Email Report • Agent Utilization Report • Predictive Routing Agent Dashboard Predictive Routing Agent Occupancy Report (Active Time and Predictive) · Supervisor Dashboard · Task Routing Agent Activity • Task Routing Agent Group Activity Folder: Metric name: Offered with Actionability Agent > Activity **Description:** The total number of customer interactions that were offered to this agent, (or to agents who belong to this agent group), for which actionability scores were recorded. **Calculation:** Used in: Media type: All This metric is not used in any reports. Data type: Number Metric type: Disposition Folder: Metric name: Offered with Influence Agent > Activity Description: The total number of customer interactions that were offered to this agent (or by agents who belong to this agent group), for which customer-influence scores were recorded. **Calculation:** Used in: Media type: All This metric is not used in any reports.

Metric name: Offered with	Revenue	Folder: Agent > Activity
Description: The total number of customer interactions that entered or began within the contact center, were handled by this agent (or by agents who belong to this agent group), and had associated revenue.		
Calculation:		
Media type: All		Used in:
Data type: Number Metric type: Disposition		This metric is not used in any reports.

Data type: Number **Metric type:** Disposition

Folder: Metric name: Offered with Satisfaction Agent > Activity **Description:** The total number of customer interactions handled by this agent (or by agents who belong with this agent group) for which customer-satisfaction scores were recorded. Calculation: Used in: Media type: All This metric is not used in any reports. Data type: Number Metric type: Disposition Folder: Metric name: Offered with Sentiment Agent > Activity **Description:** The total number of customer interactions handled by this agent (or by agents who belong with this agent group) for which sentiment scores were recorded. **Calculation:** Used in: Media type: All This metric is not used in any reports. Data type: Number Metric type: Disposition Folder: **Metric name: Rejected** Agent > Activity Description: The total number of times that customer interactions alerted at this agent (or an agent that belongs to this agent group) and were not accepted. **Calculation:** Used in: Agent Conduct Report · Agent Performance Dashboard Media type: All · Agent Task Dashboard Data type: Number Agent Utilization Email Report Metric type: Disposition Task Routing Agent Activity Task Routing Agent Group Activity

Metric name: Responded Unique Folder: Agent > Activity

Description: The total number of first-time outbound replies in which this agent (or an agent in this group) participated in response to customer interactions.

Any number of replies could be prepared in response to a customer interaction. This metric attributes only the first-connected reply to this agent, regardless of whether the reply was sent. This metric excludes outbound replies to consultations, outbound replies that the agent pulled from his/her personal workbin or rejected, and system-generated responses.

Calculation:	
Media type: All	Used in:
Data type: Number Metric type: Disposition	Agent Interaction Hierarchy Report

Metric name: Responses Folder: Agent > Activity

Description: For voice and chat media, this metric represents the total number of times that customer interactions or warm consultations were accepted by this agent or by an agent in this group.

For email, this metric represents the total number of times that the agent prepared an outbound reply. For voice media, this metric is identical to Activity\Accepted; it returns positive values when agents initiate calls.

Calculation:	Used in:
Media type: All Data type: Number Metric type: Disposition	 Agent Conduct Report Agent Group Business Attribute Report Agent Group Interaction Handling Report
,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	 Agent Interaction Hierarchy Report Agent Utilization Report

Metric name: Revenue	Folder:
	Agent > Activity

Description: The total revenue that is generated during the interval by customer interactions handled by agents who belong to this agent group.

Calculation:	Used in:
Media type: All Data type: Number Metric type: Disposition	Agent Group Business Attribute Report

Metric name: Satisfaction	Folder:
	Agent > Activity

Description: The sum of numerical scores of customer satisfaction that were attributed to customer interactions handled by this agent, or by agents who belong to this agent group.

Calculation:		Head in	
Media type: All		Used in:	
Data type: Number Metric type: Disposition		This metric is not used in any reports.	
		Falden	
Metric name: Sentiment Sc	ore	Folder:	
		Agent > Activity	
	flecting the attitude expressed b ents belonging to this agent grou	by customers for interactions that were p.	
Calculation:			
Media type: All		Used in:	
Data type: Number Metric type: Disposition		This metric is not used in any reports.	
Metric name: Short		Folder:	
		Agent > Activity	
Description: The total number of times that customer interactions were accepted by this agent (or by and agents who belongs to this agent group) and then released, transferred, or stopped within the shortengagement threshold.			
Calculation:			
Media type: All		Used in:	
Data type: Number Metric type: Disposition		Agent Conduct Report	
Metric name: Start Date Tir	me Key	Folder:	
		Agent > Activity	
	Description: This metric is reserved for internal use to employ a key for a particular date and time from the AG2_AGENT, AG2_AGENT_GRP, or AG2_AGENT_QUEUE hierarchies.		
Calculation:			
Media type: All		Used in:	
Data type: Number Metric type:		This metric is not used in any reports.	
Metric name: Transfer Acce	pted Cold	Folder:	
Introduced: 100.0.027.0001		Agent > Activity	

Description: The total number of times that customer interactions were successfully cold transferred and accepted by the agent / agent group (depending on the relevant GCXI Project attributes for this metric) during the reporting interval. **Calculation:** Calculated as the difference between the Transfer Received Accepted and Transfer Received Accepted Used in: Warm metrics. Agent Transfer Summary Report Media type: All · Transfer Dashboard Data type: Number Metric type: Disposition **Metric name: Transfer Accepted Time** Folder: Introduced: 100.0.027.0001 Agent > Activity **Description:** Total number of seconds spent handling customer interactions following transfer. The count includes both HOLD and ENGAGE times. Calculation: Used in: Media type: All This metric is not used in any reports. Data type: Number Metric type: Disposition **Metric name: Transfer Accepted Warm** Folder: Introduced: 100.0.027.0001 Agent > Activity **Description:** The total number of times that customer interactions were successfully warm transferred and accepted by the agent / agent group (depending on the relevant GCXI Project attributes for this metric) during the reporting interval. Calculation: Used in: Media type: All • Agent Transfer Summary Report Data type: Number · Transfer Dashboard Metric type: Disposition Folder: **Metric name: Transfer Initiated Agent** Agent > Activity Description: The total number of times that this agent (or an agent from this queue) transferred customer interactions. Both warm and blind transfers are reflected in this metric. **Calculation:** Used in: Media type: All Agent Group Business Attribute Report Data type: Number

Metric type: Disposition	 Agent Group Interaction Handling Report Agent Performance Dashboard Agent Report Agent Task Dashboard Agent Utilization Email Report Agent Utilization Report Task Routing Agent Activity Task Routing Agent Group Activity Transfer Dashboard
Metric name: Transfer Initiated Agent Cold Introduced: 100.0.027.0001	Folder: Agent > Activity
Description: Total number of cold transfers initiated by the agent / agent group (depending on the relevant GCXI Project attributes for this metric) during the reporting interval	

Description: Total number of cold transfers initiated by the agent / agent group (depending on the relevant GCXI Project attributes for this metric) during the reporting interval.		
Used in:		
 Agent Transfer Summary Report Transfer Dashboard 		

Metric name: Transfer Initi	ated Agent Warm	Folder:
Introduced: 100.0.027.0001		Agent > Activity
Description: Total number of warm transfers initiated by the agent / agent group (depending on the relevant GCXI Project attributes for this metric) during the reporting interval.		
Calculation:		Used in:
Media type: All Data type: Number Metric type: Disposition		Agent Transfer Summary ReportTransfer Dashboard

Metric name: Transfer Initiated Time	Folder:
Introduced: 100.0.027.0001	Agent > Activity

Description: Total number of seconds that the transferring agent spent handling customer interactions that were transferred and handled during the reporting interval. Calculation: AG2_AGENT_*.XFER_INITIATED_ENGAGE_TIME + XFER INITIATED HOLD TIME Used in: Media type: All This metric is not used in any reports. Data type: Number Metric type: Disposition **Metric name: Transfer Offered** Folder: Introduced: 100.0.027.0001 Agent > Activity **Description:** Total number of times that customer interactions were arrived by transfer and were offered (for this Agent or Agent Group, depending on the relevant GCXI Project attributes for this metric). **Calculation:** Used in: Media type: All • Agent Transfer Summary Report Data type: Number · Transfer Dashboard Metric type: Disposition Folder: **Metric name: Transfer Received Accepted** Agent > Activity **Description:** The total number of times that this agent (or an agent who belongs to this agent group) received customer interactions that were successfully transferred to the agents. Both warm and blind transfers are reflected in this metric. Calculation: Used in: Media type: All Agent Group Interaction Handling Data type: Number Report Metric type: Disposition Folder: **Metric name: Wrap** Agent > Activity **Description:** The total number of times that this agent (or an agent from this group) was in ACW (Wrap) state for customer interactions that the agent received. This metric is attributed to the interval in which the agent was offered the interactions for which ACW was invoked. Used in: **Calculation:**

Media type: Voice Data type: Number Metric type: Disposition		This metric is not used in any reports.
Metric name: Wrap Time		Folder: Agent > Activity
Description: The total amount of time, in seconds attributed to the ACW (Wrap) state for customer interactions (for this Agent, Agent Group, or Agent and Queue, depending on GCXI Project attributes).		
Calculation:		Used in:
Media type: Voice Data type: Number Metric type: Disposition		 Agent Group Business Attribute Report Agent Outbound Campaign Report Agent Performance Dashboard Agent Report

Folder: Agent > Activity > Activity Call Survey

There are no metrics in this folder.

Folder: Agent > Activity > Activity User Data Example

There are no metrics in this folder.

Folder: Agent > Activity > Queue

Metric name: % Abandoned Inviting	Folder: Agent > Activity > Queue
Description: The percentage of interactions that entered this queue, were distributed to a resource, and were subsequently abandoned while they were alerting/ringing at an agent's DN to the total number of interactions that entered this queue and were subsequently offered to a resource. This metric relies on the value of the short-abandoned threshold as configured in the [agg-gim-thld-QUEUE-IXN] section.	
Calculation: Calculated based on the (Agent > Activity >	Used in:

Queue) Abandoned Inviting and Offered metrics. Media type: Voice, Chat, Open (sync) This metric is not used in any reports. Data type: Number Metric type: Disposition Folder: Metric name: % Accepted Agent > Activity > Queue **Description:** The percentage of customer interactions of this business attribute that were distributed from this queue and accepted, relative to the total number of interactions that were distributed from this queue and offered to a handling resource. For voice media, this metric is identical to Activity\Responses. **Calculation:** Used in: Media type: All This metric is not used in any reports. Data type: Number Metric type: Disposition Folder: Metric name: % Transfer Initiated Agent > Activity > Queue **Description:** The percentage of accepted customer interactions that were distributed from this queue, and later were transferred (warm or blind). **Calculation:** Calculated based on the (Agent > Activity > Queue) Transfer Initiated and Accepted metrics. Used in: Media type: All This metric is not used in any reports. Data type: Number Metric type: Disposition Folder: **Metric name: % Transfer Initiated Agent** Agent > Activity > Queue Description: The percentage of customer interactions that entered this queue, were distributed, were accepted, and subsequently were transferred (warm or blind) by agents to the total number of interactions that entered this queue and were distributed and accepted by agents. Calculation: Calculated based on the (Agent > Activity > Queue) Transfer Initiated Agent and Accepted Agent metrics. Used in: Media type: All This metric is not used in any reports. Data type: Number Metric type: Disposition

Folder: **Metric name: % Transfer Received Accepted** Agent > Activity > Queue **Description:** The percentage of accepted customer interactions that were successfully transferred (warm or blind) to this agent. **Calculation:** Calculated based on the (Agent > Activity > Queue) Transfer Received Accepted and Accepted metrics. Used in: Media type: All This metric is not used in any reports. Data type: Number Metric type: Disposition Folder: Metric name: Abandoned Inviting Agent > Activity > Queue **Description:** The total number of times that customer interactions that were distributed or pulled from this queue, were abandoned or dropped for any reason while the interactions were alerting at this agent. Calculation: Media type: Voice, Chat, Used in: Open (sync) This metric is not used in any reports. Data type: Number Metric type: Disposition Folder: **Metric name: Accepted** Agent > Activity > Queue **Description:** The total number of times that customer interactions or warm consultations that were distributed from this gueue were accepted, answered, pulled, or initiated by this agent. For voice media, this metric is identical to Activity\Responses. **Calculation:** Used in: Media type: All Agent Group Queue Business Attribute Report Data type: Number Metric type: Disposition • Agent Queue Report Folder: **Metric name: Accepted Others** Agent > Activity > Queue **Description:** The total number of interactions that were distributed from this agent gueue, and subsequently accepted, answered, or pulled by a resource other than an agent, place DN, or extension DN.

Used in:

Calculation: Calculated based on the (Agent > Activity >

Queue) Accepted and Accepted Agent Queue metrics. Media type: All This metric is not used in any reports. Data type: Number Metric type: Disposition Folder: **Metric name: Accepted Thread** Agent > Activity > Queue **Description:** The total number of customer-interaction threads that were accepted, pulled, or initiated from this gueue for the first time by this agent. This metric includes an agent's first participation in outbound replies to inbound interactions, and, for media other than email, yields the same values as the metric Accepted Unique. **Calculation:** Used in: Media type: All This metric is not used in any reports. Data type: Number Metric type: Disposition Folder: Metric name: Accepted Unique Agent > Activity > Queue **Description:** The total number of logical interactions that were distributed by this queue and accepted, initiated, or pulled by this agent. This metric includes an agent's first participation in outbound replies to inbound interactions. **Calculation:** Used in: Media type: All This metric is not used in any reports. Data type: Number Metric type: Disposition Folder: **Metric name: Actionability** Agent > Activity > Queue **Description:** The total score, assigned to interactions that were handled by this agent and distributed from this queue, that measures the degree to which interactions required agent attention. This metric includes an agent's first participation in outbound replies to inbound interactions, and, for media other than email, yields the same values as the metric Accepted Unique. **Calculation:** Used in: Media type: All This metric is not used in any reports. Data type: Number Metric type: Disposition

Metric name: Agent Disconnect First

Folder:

Agent > Activity > Queue

Description:

Agent and Queue Attributes: For voice interactions, the total number of times during the reporting interval that this agent released customer interactions, distributed from this queue, before the other party did. For multimedia interactions, serves as a flag to indicate whether the interaction was stopped by one of the parties or by some outside entity (for example, Interaction Server or a Media Server). The tally is incremented only when the system (such as the switch) provides such information.

Calculation:

Media type: Chat, Open

(svnc). Voice

Data type: Number Metric type: Disposition

Used in:

This metric is not used in any reports.

Metric name: Avg Actionability Score

Folder:

Agent > Activity > Queue

Description: The average score, assigned to interactions that were distributed from this queue and handled by this agent, measuring the degree to which interactions required agent attention.

The average considers only those interactions for which an Actionability Score was assigned.

Calculation: Calculated as

AG2_AGENT_QUEUE_[*].ACTIONABILITY divided by AG2_AGENT_QUEUE_[*].ACTIONABILITY_OFFERED.

Media type: All

Data type: Number Metric type: Disposition

Used in:

This metric is not used in any reports.

Metric name: Avg Consult Initiated Time

Folder:

Agent > Activity > Queue

Description: The average amount of time that this agent was engaged on collaborations or simple consult interactions that the agent initiated, where the collaborations/consultations were distributed from this gueue and were associated with customer interactions.

Calculation: Calculated based on the (Activity > Queue) Consult Initiated Time and Consult Initiated metrics.

Media type: All (except Chat)

Data type: Number Metric type: Disposition

Used in:

This metric is not used in any reports.

Metric name: Avg Consult Received Time

Folder:

Description: The average amount of time that agents were engaged on collaboration calls or simple consultations that agents received, where the collaborations/consultations were associated with customer interactions.

Calculation: Calculated based on the (Activity > Queue) the Consult Received Time and Consult Received Accepted metrics.

Media type: All (except Chat)

Data type: Number Metric type: Disposition

Media type: Disposition

Metric name: Avg Consult Received Warm Time

Folder:

Agent > Activity > Queue

Description: The average amount of time that this agent was engaged as a recipient in collaborations or consultations, including related hold durations, where the collaborations/consultations were distributed or pulled from this queue and associated with customer interactions.

This metric is attributed to the interval in which the consult interaction is offered to the receiving agent. This metric excludes alert (ring) and ACW (Wrap) durations associated with the consult interactions.

Calculation: Calculated based on the (Activity > Queue)
Consult Received Warm Time and Consult Received Accepted
Warm metrics.

Media type: Voice
Data type: Number
Metric type: Disposition

Data type: Disposition

Used in:
This metric is not used in any reports.

Metric name: Avg Consult Received Warm Wrap Time

Discontinued: 9.0

Description: This metric is no longer populated.

Calculation: Calculated based on the (Activity > Queue)
Consult Received Wrap Time and Consult Received Wrap metrics.

Media type: Voice
Data type: Number Metric type: Disposition

Folder:
Agent > Activity > Queue
Used in:
This metric is not used in any reports.

Metric name: Avg Consult Received Wrap Time

Folder:

Agent > Activity > Queue

Description: The average amount of time that this agent spent in ACW state following simple consultations that the agent accepted, where the consultations were distributed from this queue and were associated with customer calls. This duration does not stop if the agents received or made calls while in ACW state. This metric is attributed to the interval in which this agent was offered the consult interaction for which ACW was invoked. **Calculation:** Calculated based on the (Activity > Queue) Consult Received Wrap Time and Consult Received Wrap metrics. Used in: Media type: Voice This metric is not used in any reports. Data type: Number Metric type: Disposition Folder: Metric name: Avg Engage Time Agent > Activity > Queue Description: For interactions that were distributed or pulled from this queue, the average amount of time that this agent was engaged with customers. **Calculation:** Calculated based on the (Activity > Queue) Engage Time and Accepted metrics. Used in: Media type: All · Agent Queue Report Data type: Number Metric type: Disposition Folder: Metric name: Avg Handle Time Agent > Activity > Queue **Description:** Queue Attribute: The average amount of time that agents spent handling customer interactions or warm consultations that were distributed or pulled from this queue. Queue Group Attribute: The average amount of timethat agents spent handling customer interactions or warm consultations that were distributed or pulled from queues that belong to this queue group. This metric is attributed to the interval in which interactions entered the gueue. **Calculation:** Calculated as (Activity > Queue) Handle Time divided by the sum of Accepted Interactions and Received Used in: Consultations. Media type: All · Agent Queue Report Data type: Number Metric type: Disposition Folder: Metric name: Avg Hold Time Agent > Activity > Queue

Description: The average amount of time that agents had customer interactions, distributed from this queue, on hold.

This metric is attributed to the interval in which interactions arrived at the agent (which can differ from the interval in which the interactions were placed on hold).

Calculation: Calculated based on the (Activity > Queue) Hold

and Hold Time metrics.

Media type: All

Data type: Number Metric type: Disposition

Used in:

· Agent Queue Report

Metric name: Avg Influence Score

Folder:

Agent > Activity > Queue

Description: The average score representing the clout amassed on social networks for interactions that were distributed from this queue and handled by this agent.

The average considers only those interactions for which an actionability score was assigned.

Calculation: Calculated as

AG2_AGENT_QUEUE_[*].INFLUENCE divided by AG2_AGENT_QUEUE [*].INFLUENCE_OFFERED.

Media type: All

Data type: Number Metric type: Disposition

Used in:

This metric is not used in any reports.

Metric name: Avg Invite Time

Folder:

Agent > Activity > Queue

Description: The average amount of time that customer interactions (that were distributed from this queue) alerted or rang at an agent before being accepted plus the average duration of dialing that agents performed, where the calls were successfully established.

Calculation: Calculated based on the (Activity > Queue)

Invite Time and Invite Queue metrics.

Used in:

This metric is not used in any reports.

Media type: All

Data type: Number **Metric type:** Disposition

Metric name: Avg Revenue

Folder:

Agent > Activity > Queue

Description: The average amount of revenue that is generated for interactions distributed from this

queue and handled by this agent. The average considers only those interactions for which revenue was generated. **Calculation:** Calculated based on the (Activity > Queue) Revenue and Offered with Revenue metrics. Used in: Media type: All This metric is not used in any reports. Data type: Number Metric type: Disposition Folder: **Metric name: Avg Satisfaction** Agent > Activity > Queue Description: The average customer-satisfaction score of interactions distributed from this queue and handled by this agent. The tally considers only those interactions for which customer satisfaction was recorded. **Calculation:** Calculated based on the (Activity > Queue) Satisfaction and Offered with Satisfaction metrics. Used in: Media type: All This metric is not used in any reports. Data type: Number Metric type: Disposition Folder: **Metric name: Avg Sentiment Score** Agent > Activity > Queue **Description:** The average score reflecting the attitude expressed by customers for interactions that were distributed from this queue and handled by this agent. The average considers only those interactions for which a sentiment score was assigned. Calculation: Calculated as: AG2_AGENT_QUEUE_[*].SENTIMENT divided by Used in: AG2 AGENT QUEUE [*]. SENTIMENT OFFERED Media type: All Agent Social Engagement Report Data type: Number Metric type: Disposition Folder: **Metric name: Avg Wrap Time** Agent > Activity > Queue

Description: The average amount of time that this agent spent on customer interactions while in ACW

Used in:

Genesys CX Insights 9.0 Projects Reference Guide

Calculation:

(Wrap) state, where the interactions were distributed from this queue.

Media type: Voice · Agent Queue Report Data type: Number Metric type: Disposition Folder: Metric name: Conference Initiated Agent > Activity > Queue **Description:** The total number of times that this agent initiated conferences for customer interactions that the agent received, where the interactions were distributed or pulled from this gueue and, where the conferences were established. The count includes the number of established conferences that were initiated for transferred interactions that the agent received. Calculation: Media type: All (Except Used in: email) This metric is not used in any reports. Data type: Number Metric type: Disposition Folder: **Metric name: Conference Received Accepted** Agent > Activity > Queue **Description:** The total number of times that this agent joined conferences to participate in interactions that were distributed or pulled from this queue. Calculation: Used in: Media type: All This metric is not used in any reports. Data type: Number Metric type: Disposition Folder: Metric name: Consult Initiated Agent > Activity > Queue **Description:** The total number of times that this agent initiated requests for collaboration or simple consultation, where the collaborations/consultations were established and associated with customer interactions. **Calculation:** Media type: All (except Used in: Chat) This metric is not used in any reports. Data type: Number Metric type: Disposition **Metric name: Consult Initiated Time** Folder:

Agent > Activity > Queue **Description:** The total amount of time that this agent was engaged in collaborations or simple consultations that the agent requested, where the collaborations/consultations were associated with customer interactions that were distributed or pulled from this queue. Calculation: Media type: All (except Used in: Chat) This metric is not used in any reports. Data type: Number Metric type: Disposition Folder: **Metric name: Consult Received Accepted** Agent > Activity > Queue **Description:** The total number of times that this agent received and accepted collaborations or simple consultations that were distributed or pulled from this queue and associated with customer interactions. **Calculation:** Used in: Media type: This metric is not used in any reports. Data type: Metric type: Folder: **Metric name: Consult Received Accepted Warm** Agent > Activity > Queue **Description:** The total number of times that this agent participated in consultations that the agent received, where the consultations were distributed or pulled from this queue, associated with customer interactions, and transferred to or conferenced with the agent. **Calculation:** Used in: Media type: Voice This metric is not used in any reports. Data type: Number Metric type: Disposition Folder: Metric name: Consult Received Hold Agent > Activity > Queue **Description:** The total number of times that this agent was on hold during simple consultations that the agent received where the consultations were associated with customer interactions and were distributed from this queue. **Calculation:** Used in: Media type: Voice This metric is not used in any reports. Data type: Number

Metric type: Disposition

Metric name: Consult Received Time

Folder:

Agent > Activity > Queue

Description: The total amount of time that this agent was engaged as a recipient in collaboration or simple consultation, including related hold durations, where the collaborations/consultations were distributed or pulled from this queue and associated with customer interactions.

This metric is attributed to the interval in which this agent was offered the collaboration/consultation request distributed from this queue.

Calculation: Calculated as the sum of

AG2_AGENT_QUEUE_[*].CONSULT_RECEIVED_ENGAGE_TIME and AG2_AGENT_QUEUE_[*].CONSULT_RECEIVED_HOLD_TIME

Media type: All (except

Chat)

Data type: Number **Metric type:** Disposition

Used in:

This metric is not used in any reports.

Metric name: Consult Received Warm Hold

Folder:

Agent > Activity > Queue

Description: The total number of consultations distributed from this queue that this agent had on hold, where the consultations were associated with customer interactions, the agent was the recipient of the consultation requests, and the interactions were transferred to or conferenced with the agent.

Calculation:

Media type: Voice

Data type: Number

Metric type: Disposition

Used in:

This metric is not used in any reports.

Metric name: Consult Received Warm Time

Folder:

Agent > Activity > Queue

Description: The total amount of time that this agent was engaged as a recipient in collaborations or consultations, including related hold durations, where the collaborations/consultations were distributed or pulled from this queue and associated with customer interactions.

This metric is attributed to the interval in which the consult interaction is offered to the receiving agent. Time begins when the consult interaction is received and ends when the customer interaction is transferred to or conferenced with this agent. This metric excludes alert (ring) and ACW (Wrap) durations associated with the consult interactions.

Calculation: Calculated as the sum of

Used in:

This metric is not used in any reports.

Media type: Voice

Data type: Number
Metric type: Disposition

Metric name: Consult Received Warm Wrap

Discontinued: 9.0

Description: This metric is no longer populated.

Calculation:

Media type: Voice

Data type: Number Metric type: Dispostion

Folder:

Agent > Activity > Queue

Used in:

This metric is not used in any reports.

Metric name: Consult Received Warm Wrap Time

Discontinued: 9.0

Description: This metric is no longer populated.

Calculation:

Media type: Voice

Data type: Number Metric type: Dispostion

Folder:

Agent > Activity > Queue

Used in:

This metric is not used in any reports.

Metric name: Consult Received Wrap

Agent > Activity > Queue

Description: The total number of times that this agent was in ACW state after requests for simple consultation that the agent accepted and that were distributed from this queue where the consultations were associated with customer interactions.

Calculation:

Media type: Voice

Data type: Number Metric type: Disposition

Used in:

This metric is not used in any reports.

Metric name: Consult Received Wrap Time

Folder:

Agent > Activity > Queue

Description: The total amount of time that this agent spent in ACW state after simple consultations that the agent accepted, where the consultations were distributed from this queue and were associated with customer calls.

This duration does not stop if the agents received or made calls while in ACW state. This metric is attributed to the interval in which this agent was offered the consult interaction for which ACW was invoked. **Calculation:** Used in: Media type: Voice This metric is not used in any reports. Data type: Number Metric type: Disposition Folder: **Metric name: Consult Responses** Agent > Activity > Queue Description: For email, the total number of collaboration replies that were initiated by this agent for customer interactions that were distributed from this queue. For voice, this metric is the same as Agent > Activity > Consult Received Accepted. **Calculation:** Media type: All (except Used in: Chat) This metric is not used in any reports. Data type: Number Metric type: Disposition Metric name: Engage Folder: Introduced: 100.0.029.0000 Agent > Activity > Queue Description: The number of times that agents were engaged with a customer during the reporting period. This metric is useful in calculating custom values such as Average Handle Time. **Calculation:** Used in: Media type: All This metric is not used in any reports. Data type: Number Metric type: Disposition Folder: **Metric name: Engage Time** Agent > Activity > Queue **Description:** For interactions that were distributed or pulled from this queue, the total amount of time that this agent was engaged with customers on interactions that the agent received. This metric excludes other interaction-related durations, such as hold time, ACW (Wrap) time, alert (ring) time, and time that is spent in collaboration or consultation. **Calculation:** Used in:

Media type: All

Data type: Number · Agent Queue Report Metric type: Disposition Folder: **Metric name: Focus** Agent > Activity > Queue **Description:** Total number of times that the agent was in the focus state while working on media sessions. Includes only cases where the agent was actively working on the interaction that is the subject of the IRF, and requires WDE is configured to report focus time. **Calculation:** Used in: Media type: This metric is not used in any reports. Data type: Metric type: Disposition Folder: **Metric name: Focus Time** Agent > Activity > Queue **Description:** The total time that the agent spent in the focus state while working on media sessions. Includes only time that the agent spent actively processing the interaction, as reported by the agent desktop. **Calculation:** Used in: Media type: This metric is not used in any reports. Data type: Metric type: Disposition Folder: **Metric name: Handle Time** Agent > Activity > Queue **Description:** The total amount of time that this agent spent handling interactions that were distributed or pulled from this queue for those interactions that the agent received. Calculation: Calculated based on (Activity > Queue) Engage Time, Hold Time, Wrap Time, Consult Received Time, Consult Received Wrap Time, Consult Received Warm Time metrics. Used in: Media type: All This metric is not used in any reports. Data type: Number Metric type: Disposition

Metric name: Hold Folder: Agent > Activity > Queue

Description: The total number of times within the interval that this agent had customer calls (that were

distributed from this queue) on hold. **Calculation:** Used in: Media type: Voice This metric is not used in any reports. Data type: Number Metric type: Disposition Folder: Metric name: Hold Time Agent > Activity > Queue **Description:** The total amount of time that agents had customer interactions distributed from this queue on hold. This metric counts all held durations for interactions, whether they were placed on hold once or more than once. **Calculation:** Used in: Media type: Voice · Agent Queue Report Data type: Number Metric type: Disposition Folder: Metric name: Influence Score Agent > Activity > Queue Description: The total score that represents the customer clout that has amassed on social networks for customer interactions that were distributed from this queue and handled by this agent. Calculation: Used in: Media type: All This metric is not used in any reports. Data type: Number Metric type: Disposition Folder: Metric name: Invite Agent > Activity > Queue **Description:** The total number of customer interactions that were distributed from this queue that alerted or rang at this agent before the interactions were accepted plus the total number of dials that the agent performed, where the calls were successfully established. This metric is attributed to the interval in which the alerting/dialing first occurred. The dialing component of this metric applies to voice media only. **Calculation:** Used in: Media type: All This metric is not used in any reports. Data type: Number Metric type: Disposition Folder:

Metric name: Invite Time

Agent > Activity > Queue

Description: The total amount of time, in seconds, that customer interactions alerted at this agent plus the total duration of the dialing that the agent performed for calls that were distributed or pulled from this queue.

For the alerting component of this metric, interactions do not have to be established for this metric to be incremented. For the dialing component, dial duration is measured for established calls only. This metric is attributed to the interval in which the alerting/dialing first occurred.

Calculation:

Media type: All

Data type: Number **Metric type:** Disposition

Used in:

This metric is not used in any reports.

Metric name: Not Accepted

Folder:

Agent > Activity > Queue

Description: The total number of times that customer interactions, that were distributed from this queue were redirected to another resource upon no answer by this agent or were otherwise not accepted by the agent.

This metric includes interactions that the customer abandoned while they were alerting at the agent.

Calculation:

Media type: All

Data type: Number Metric type: Disposition

Used in:

This metric is not used in any reports.

Metric name: Offered

Folder:

Agent > Activity > Queue

Description: The total number of times that interactions were received or initiated by this agent (for Agent reporting), or agents who belong to this agent group (for Agent Group reporting).

The count includes interactions that were abandoned while inviting, handling attempts that the agent rejected, and warm consultations and conferences that the agent received. This count excludes simple consultations, whether they were initiated or received. For AGT_AGENT_QUEUE records, this metric relies on the value of the **short-abandoned threshold** as configured in the **[agg-gim-thld-ID-IXN]** section.

Calculation:

Media type: All

Data type: Number **Metric type:** Disposition

Used in:

 Agent Group Queue Business Attribute Report

Folder:

Metric name: Offered with Actionability Agent > Activity > Queue **Description:** The total number of customer interactions that were offered to this agent and distributed from this queue, for which actionability scores were recorded. Calculation: Used in: Media type: All This metric is not used in any reports. Data type: Number Metric type: Disposition Folder: Metric name: Offered with Influence Agent > Activity > Queue **Description:** The total number of customer interactions that were offered to this agent and distributed from this gueue, for which customer-influence scores were recorded. Calculation: Used in: Media type: All This metric is not used in any reports. Data type: Number Metric type: Disposition Folder: Metric name: Offered with Revenue Agent > Activity > Queue **Description:** The total number of customer interactions that entered or began within the contact center, were distributed from this queue, had associated revenue, and were handled by this agent. **Calculation:** Used in: Media type: All This metric is not used in any reports. Data type: Number Metric type: Disposition Folder: Metric name: Offered with Satisfaction Agent > Activity > Queue **Description:** The total number of customer interactions that were distributed from this queue and handled by this agent for which customer-satisfaction scores were recorded. **Calculation:** Used in: Media type: All This metric is not used in any reports. Data type: Number Metric type: Disposition

Metric name: Offered with Sentiment

Folder:

Agent > Activity > Queue

Description: The total number of customer interactions that were distributed from this queue and handled by this agent for which sentiment scores were recorded.

Calculation:

Media type: All

Data type: Number

Metric type: Disposition

Used in:

This metric is not used in any reports.

Metric name: Rejected

Folder:

Agent > Activity > Queue

Description: The total number of times that customer interactions were distributed from this queue, alerted at this agent, and were not accepted.

Calculation:

Media type: All

Data type: Number

Metric type: Disposition

Used in:

This metric is not used in any reports.

Metric name: Responded Unique

Folder:

Agent > Activity > Queue

Description: The total number of first-time outbound replies in which this agent participated in response to customer interactions distributed from this queue.

Any number of replies could be prepared in response to a customer interaction. This metric attributes only the first-connected reply to this agent, regardless of whether the reply was sent. This metric excludes outbound replies to consultations, outbound replies that the agent pulled from his/her personal workbin or rejected, and system-generated responses.

Calculation:

Media type: All

Data type: Number

Metric type: Disposition

Used in:

This metric is not used in any reports.

Metric name: Responses

Folder:

Agent > Activity > Queue

Description: For interactions distributed from this queue, this metric represents:

• For voice and chat media, this metric represents the total number of times that customer interactions or warm consultations were accepted by this agent. For voice media, this metric is identical to Activity\Accepted; it returns positive values when agents initiate calls.

· For email, this metric represents the total number of times that the agent prepared an outbound reply. **Calculation:** Used in: Media type: All This metric is not used in any reports. Data type: Number Metric type: Disposition Folder: Metric name: Revenue Agent > Activity > Queue **Description:** The total revenue that is generated during the interval by customer interactions that were distributed from this queue and handled by this agent. **Calculation:** Used in: Media type: All This metric is not used in any reports. Data type: Number Metric type: Disposition Folder: **Metric name: Satisfaction** Agent > Activity > Queue **Description:** The sum of numerical scores of customer satisfaction that were attributed to customer interactions that were distributed from this gueue and handled by this agent. Calculation: Used in: Media type: All This metric is not used in any reports. Data type: Number Metric type: Disposition Folder: **Metric name: Sentiment Score** Agent > Activity > Queue Description: The total score reflecting the attitude expressed by customers for interactions that were distributed from this queue and handled by this agent. **Calculation:** Used in: Media type: All This metric is not used in any reports. Data type: Number Metric type: Disposition Folder: **Metric name: Short** Agent > Activity > Queue

Description: The total number of times that customer interactions were accepted by this agent and then released, transferred, or stopped within the short-engagement threshold.

This metric relies on the value of the **short-engagement** (short-talk) option as configured in the **[agg-gim-thld-AGENT-IXN]** section.

Calculation:	
Media type: All	Used in:
Data type: Number Metric type: Disposition	This metric is not used in any reports.

Metric name: Start Date Tir	me Key	Folder:
		Agent > Activity > Queue
Description: This metric is reserved for internal use to employ a key for a particular date and time from the AG2_AGENT_QUEUE hierarchy.		
Calculation:		
Media type: All		Used in:
Data type: Number Metric type:		This metric is not used in any reports.

Metric name: Transfer Initiated Agent	Folder:
	Agent > Activity > Queue

Description: The total number of times that this agent transferred customer interactions that were distributed by this queue. Both warm and blind transfers are reflected in this metric.

Calculation:	Used in:	
Media type: All Data type: Number Metric type: Disposition	Agent Group Que Attribute Report	

Metric name: Transfer Received Accepted	Folder:
	Agent > Activity > Queue

Description: The total number of times that agents received customer interactions from this queue that were successfully transferred to the agents.

Both warm and blind transfers are reflected in this metric.

Calculation:	Used in:
Media type: All Data type: Number Metric type: Disposition	Agent Group Queue Business Attribute Report

Metric name: Wrap Folder:

Agent > Activity > Queue

Description: The total number of times that this agent was in ACW state for customer interactions that the agent received from this queue.

This metric is attributed to the interval in which the agent was offered the interactions for which ACW was invoked.

Calculation:

Media type: Voice

Data type: Number Metric type: Disposition Used in:

This metric is not used in any reports.

Metric name: Wrap Time Folder:

Agent > Activity > Queue

Description: The total amount of time that agents spent in ACW state for customer interactions that the agents received from this queue.

This metric is attributed to the interval in which the agent was offered the interaction for which ACW was invoked.

Calculation:

Media type: Voice

Data type: Number **Metric type:** Disposition

Used in:

· Agent Queue Report

Folder: Agent > Detail

There are no metrics in this folder.

Folder: Agent > Detail > Ixn State

Metric name: Duration Folder:

Agent > Detail > Ixn State

Description: The difference between the beginning and end of the agent's state.

Calculation: Calculated as

IXN_RESOURCE_STATE_FACT_GI2.END_TS minus IXN RESOURCE STATE FACT GI2.START TS.

Used in:

This metric is not used in any reports.

Media type: All Data type: Number Metric type: Detail		
Metric name: Start DateTir	me Key	Folder: Agent > Detail > Ixn State
Description: This metric is resthe AG2_QUEUE or AG2_QUEUE		a key for a particular date and time from
Calculation:		
Media type: All		Used in:
Data type: Number Metric type:		This metric is not used in any reports.

Folder: Agent > Detail > Session

Metric name: Active Time	Folder: Agent > Detail > Session	
Description: The total amount of time that elapsed between the beginning and end of this agent's login session(s) on a particular media channel, irrespective of the intervals in which the resource session occurs. If an agent logs into multiple DNs, login duration is measured from the moment at which the agent logs in to the first DN to the moment at which the agent is no longer logged in to any DN. If the agent's session was still active when the data was compiled, the agent's session duration appears as null in the reports.		
If the agent is not forcibly logged out when the calendar dates ends, login dura	tion is split over both days.	
Calculation: Media type: All Data type: Number Metric type: Detail	Used in:Agent Login-Logout Details Report	
Metric name: Group Combination Detail Session	Folder: Agent > Detail > Session	
Description: This metric is reserved for internal use to employ a key for a particular resource-group combination from the SM_RES_SESSION_FACT table.		
Calculation: Media type: All	Used in:	

	This metric is not used in any reports.
ne Key	Folder: Agent > Detail > Session
erved for internal use to employ	a key for a particular date and time from
	Used in:
	This metric is not used in any reports.
	·

Folder: Agent > Detail > State

Metric name: Duration		Folder: Agent > Detail > State
Description: The difference be	etween the beginning and end of	the agent's interaction-related state.
Calculation:		Used in:
Media type: All		osea III.
Data type: Number Metric type: Detail		Agent State Details Report
Metric name: Reason Time	Folder:	
		Agent > Detail > State
Description: The total amount of time that this agent was in a specific state for a specific reason, irrespective of the interval(s) in which the state-reason combination endures.		
This time is measured from the moment at which the agent enters this state-reason combination to the moment at which the agent exits this state or state-reason combination. If the agent's state was still active when the data was compiled, the duration of the agent in this state appears as null in the reports.		
Calculation:		Hand to
Media type: All		Used in:
Data type: Number Metric type: Detail		Agent State Details Report

Folder: Agent > Group Membership

Metric name: Start Date Ti	me Key	Folder: Agent > Group Membership
Description: This metric is res the RESOURCE_GROUP_FACT hi		a key for a particular date and time from
Calculation:		Used in:
Media type: All Data type: Number Metric type:		Agent Group Membership Details Report

Folder: Agent > State and Reason

There are no metrics in this folder.

Folder: Agent > State and Reason > Interaction State

Metric name: % Consult Received Time	Folder: Agent > State and Reason > Interaction State	
Description: The percentage of time within the interval that this agent spent on collaborations or consult interactions that the agent received, relative to the total duration within the interval of this agent's active session on a particular media channel.		
Calculation: Calculated based on the Interaction State > Consult Received Time and Summarized State > Active Time metrics.	Used in: • Agent Interval Based Report	
Media type: All (Except Chat) Data type: Number Metric type: Interval	Agent Summary Activity Report (Interaction)	
	Folder:	
Metric name: % Engage Time	Agent > State and Reason > Interaction State	

Description: The percentage of time within the interval that this agent was engaged with customers, relative to the total duration within the interval of the agent's active session on a particular media channel.

Calculation: Calculated based on the Interaction State > Engage Time and Summarized State > Active Time metrics.

Media type: All Data type: Number Metric type: Interval

Used in:

- Agent Interaction State
- · Agent Interval Based Report
- · Agent Summary Activity Report (Interaction)
- · Supervisor Dashboard

Metric name: % Hold Time

Folder:

Agent > State and Reason > Interaction State

Description: The percentage of time that this agent had customer interactions on hold within the interval, relative to the total duration of the agent's active session within the interval.

Calculation: Calculated based on the Interaction State > Hold Time and Summarized State > Active Time metrics.

Used in:

- · Agent Interaction State
- · Agent Interval Based Report
- Agent Summary Activity Report (Interaction)
- Supervisor Dashboard

Media type: Voice

Data type: Number Metric type: Interval

Metric name: % Invite Time

Folder:

Agent > State and Reason > Interaction State

Description: The percentage of time that customer interactions spent in Invite Time relative to the total duration of the agent's active session within the interval.

Calculation: Calculated based on the Invite Time Interaction State and Active Time Summarized State metrics.

Media type: All

Data type: Number Metric type: Interval

Used in:

- · Agent Interaction State
- · Agent Summary Activity Report (Interaction)

Metric name: % Ixn Wrap Time

Folder:

Agent > State and Reason > Interaction State

Description: The percentage of time within the interval that this agent spent in ACW (Wrap) state

associated with customer calls, relative to the total duration of the agent's active session within the interval. **Calculation:** Calculated based on the Ixn Wrap Time Used in: Interaction State and Active Time Summarized State metrics. · Agent Interaction State Media type: Voice · Agent Interval Based Report Data type: Number · Agent Summary Activity Report Metric type: Interval (Interaction) Folder: **Metric name: % Not Ready In Time** Agent > State and Reason > Interaction State **Description:** The percentage of time that this agent spent on customer interactions that were accepted within the interval while the agent was in the NotReady state, relative to the agent's total NotReady duration within the interval for a particular media channel. Consultations and collaborations that the agent receives while in the NotReady state are excluded from this percentage. **Calculation:** Used in: Media type: All Agent Not Ready Report Data type: Number Metric type: Interval Folder: Metric name: % Not Ready Out Time Agent > State and Reason > Interaction State **Description:** The percentage of time that this agent spent on customer interactions that were dialed within the interval while the agent was in the NotReady state, relative to the agent's total NotReady duration within the interval. Calculation: Calculated based on the Not Ready Out Time Interaction State and the Not Ready Time Summarized State Used in: metrics. Media type: All · Agent Not Ready Report Data type: Number Metric type: Interval Folder: Metric name: % Wrap In Time Agent > State and Reason > Interaction State **Description:** The percentage of time that this agent spent on customer interactions received within the interval while the agent DNs were in ACW (Wrap) state, relative to the DN's total ACW state duration within the interval.

Used in:

State and the Wrap Time Summarized State metrics.

Calculation: Calculted based on the Wrap In Time Interaction

Media type: Voice, Chat

Data type: Number
Metric type: Disposition

• Agent Wrap Report

Metric name: Accepted

Folder:

Agent > State and Reason > Interaction State

Description: The description of this metric varies depending on attributes and filters in the report query:

- Agent Attributes: The total number of times that customer interactions or warm consultations were accepted, answered, pulled, or initiated by this agent.
- Agent Group Attributes: The total number of times that customer interactions or warm consultations were accepted, answered, pulled, or initiated by agents who belong to this agent group.

For voice media, this metric is identical to Activity\Responses.

Data type: Number **Metric type:** Interval

Calculation:	Used in:
	Agent Activity
	Agent Conduct Report
	 Agent Group Business Attribute Report
Media type: All	 Agent Group Interaction handling Report
Data type: Number Metric type: Disposition	Agent Interval Based Report
	Agent Performance Dashboard
	Agent Report
	Agent Social Engagement Report
	Agent Task Dashboard

Agent Utilization Email Report
Agent Utilization Report
Predictive Routing Agent Dashboard
 Predictive Routing Agent Occupancy Report (Active Time & Predictive)
Survey Statistics Report
Task Routing Agent Activity
Task Routing Agent Group Activity

Metric name: Accepted Eventually	Folder: Agent > State and Reason > Interaction State	
Description: The total number of customer interactions and consultations (warm or simple) that were accepted by this agent.		
Calculation:		
Media type: All	Used in:	
Data type: Number Metric type: Interval	This metric is not used in any reports.	

Metric name: Consult Received Accepted	Folder:
	Agent > State and Reason > Interaction State

Description: The description of this metric varies according to the attributes and filters in the report query:

- Agent Attribute: The total number of times that this agent received and accepted collaborations or simple consultations that were associated with customer interactions.
- Agent Group Attribute: The total number of times that agents who belong to this agent group received and accepted collaborations or simple consultations that were associated with customer interactions.

Calculation:	Used in:
Media type: All (except Chat) Data type: Number Metric type: Disposition	 Agent Group Business Attribute Report Agent Interval Based Report Agent Utilization Report
Metric name: Consult Received Time	Folder:

Agent > State and Reason > Interaction State

Description: The description of this metric varies according to the attributes and filters in the report query:

- Agent Attribute: The total amount of time that this agent was engaged as a recipient in collaborations or simple consultations, including related hold durations, where the collaborations/consultations were associated with customer interactions.
- Agent Group Attribute: The total amount of time that agents who belong to this agent group were engaged as recipients in collaboration or simple consultation, including related hold durations, where the collaborations/consultations were associated with customer interactions.

This metric is attributed to the interval in which this agent was offered the collaboration/consultation request.

Calculation: Calculated as the sum of AG2_AGENT_[*].CONSULT_RECEIVED_ENGAGE_TIME and AG2_AGENT_[*].CONSULT_RECEIVED_HOLD_TIME, or AG2_AGENT_GRP_[*].CONSULT_RECEIVED_ENGAGE_TIME and AG2_AGENT_GRP_[*].CONSULT_RECEIVED_HOLD_TIME

Media type: All (except

Chat)

Data type: Number **Metric type:** Disposition

Used in:

- Agent Group Business Attribute Report
- Agent Interval Based Report
- · Agent Performance Dashboard
- Agent Report
- Agent Summary Activity Report (Interaction)

Metric name: Consult Received Wrap Time

Folder:

Agent > State and Reason > Interaction State

Description: The description of this metric varies depending on attributes and filters in the report query:

- Agent Attribute: The total amount of time that this agent was in ACW (Wrap) state after simple consultations that the agent accepted, where the consultations were associated with customer calls.
- Agent Group Attribute: The total amount of time that agents who belong to this agent group were in ACW state after simple consultations that the agents accepted, where the consultations were associated with customer calls.

This duration does not stop if the agents received or made calls while in ACW state. This metric is attributed to the interval in which this agent was offered the consult interaction for which ACW was invoked.

Calculation:	Used in:
Media type: Voice Data type: Number Metric type: Disposition	Agent Performance DashboardAgent Report

Metric name: Engage Time Folder: Agent > State and Reason > Interaction State

Description: The description of this metric varies depending on attributes and filters in the report query:

- Agent Attribute: The total amount of time that this agent was engaged with customers on interactions that the agent received.
- Agent Group Attribute: The total amount of time that agents who belong to this agent group were engaged with customers on interactions that the agents received.

This metric excludes other interaction-related durations, such as hold time, ACW (Wrap) time, alert (ring) time, and time that is spent in collaboration or consultation.

Calculation:	Used in:
	 Agent Group Business Attribute Report
	Agent Interaction State
	Agent Interval Based Report
Media type: All	Agent Outbound Campaign Report
Data type: Number Metric type: Disposition	Agent Performance Dashboard
	Agent Report
	 Agent Summary Activity Report (Interaction)
	Supervisor Dashboard
Metric name: Group Combination	Folder:
	Agent > State and Reason > Interaction State
Description: This metric is reserved for internal use to combination from the SM_RES_STATE_FACT table.	employ a key for a particular resource-group
Calculation:	
Media type: All	Used in:
Data type: Number Metric type:	This metric is not used in any reports.
Metric name: Hold	Folder:
	Agent > State and Reason > Interaction State
Description: The total number of times within the interhad customer calls on hold.	rval that this agent (or agents in this agent group)
Calculation:	Used in:
Media type: Voice	Agent Interval Based Report
Data type: Number	Agent Performance Dashboard
Metric type: Disposition	Agent Report

		Agent Utilization Report
		Folder:
Metric name: Hold Time		
		Agent > State and Reason > Interaction State
Description: The total amount of time that this agent (or agents in this agent group) had customer interactions on hold. This metric counts all held durations for interactions, whether they were placed on hold once or more than once.		
Calculation:		Used in:
		 Agent Group Business Attribute Report
		Agent Interval Based Report
Media type: Voice		Agent Outbound Campaign Report
Data type: Number		Agent Performance Dashboard
Metric type: Disposition		Agent Report
		 Agent Summary Activity Report (Interaction)
		Supervisor Dashboard
Metric name: Invite Time		Folder:
Metric name. mvite rime		Agent > State and Reason > Interaction State
	of time that customer interactions the total duration of the dialing	ns alerted at this agent (or at agents who that the agents performed.
 For the alerting component of this metric, interactions do not have to be established for this metric to be incremented. 		
For the dialing component, or	dial duration is measured for esta	ablished calls only.
This metric is attributed to the interval in which the alerting/dialing first occurred.		
Calculation:		Used in:
		Agent Interaction State
Media type: All		Agent Summary Activity Report
Data type: Number Metric type: Disposition		(Interaction)
		Supervisor Dashboard
Metric name: Ixn Busy Time	e	Folder:
Metric name: IXII basy Tilli		Agent > State and Reason > Interaction State

Description: The total amount of time within the interval that this agent was busy processing interactions.

The time that an agent is busy is calculated as the sum of dialing for established interactions and alerting duration (Invite Time), engage/talk duration, hold duration, ACW (Wrap) duration (for interaction-related ACW), and amount of time that the agent spent processing consult interactions that the agent received. This metric excludes Ringing Time, Consult Ixn Wrap Time, Consult Invite Time, and Invite Time for Abandoned Inviting.

Calculation: Calculated based on the Invite Time, Engage Time, Hold Time, Ixn Wrap Time, and Consult Received Time Interaction State metrics.

Media type: All

Data type: Number **Metric type:** Interval

Used in:

- · Agent Interaction State
- Agent Summary Activity Report (Interaction)
- · Supervisor Dashboard

Metric name: Ixn Wrap

Folder:

Agent > State and Reason > Interaction State

Description: The total number of times within the interval that this agent was in ACW (Wrap) state for customer interactions that the agent received.

Calculation:

Media type: All

Data type: Number Metric type: Interval

Used in:

• Agent Interval Based Report

Metric name: Ixn Wrap Time

Folder:

Agent > State and Reason > Interaction State

Description: The total amount of time within the interval that this agent spent in ACW (Wrap) state for customer calls that the agent received.

Calculation:

Used in:

Media type: All

Data type: Number **Metric type:** Interval

- Agent Interaction State
- Agent Interval Based Report
- Agent Summary Activity Report (Interaction)
- Supervisor Dashboard

Metric name: Not Accepted

Folder:

Agent > State and Reason > Interaction State

Description: The total number of customer interactions that were offered to or dialed by this agent within the interval or within a prior interval and ensued in this interval, but which were not accepted by this agent as customer interactions or consultations.

Calculated as the difference between:

• The total number of customer interactions that were offered to or dialed by this agent within the interval or within a prior interval and ensued in this interval,

and

• The total number of customer interactions and consultations (warm or simple) that were accepted by this agent.

Calculation: Calculated based on the Offered Interaction
State and AG2_I_AGENT_[*].ACCEPTED_EVENTUALLY metrics.

Media type: All

Data type: Number
Metric type: Interval

Data type: Interval

Media type: Number

Metric name: Not Ready In

Folder:

Agent > State and Reason > Interaction State

Description: The total number of times that this agent was handling customer calls that were accepted while the agent was in the NotReady state.

Calculation:

Media type: All

Data type: Number Metric type: Interval

Used in:

• Agent Not Ready Report

Metric name: Not Ready In Time

Folder:

Agent > State and Reason > Interaction State

Description: The total amount of time that this agent was handling customer interactions that the agent received while the agent was in the NotReady state. This time includes the alert (ring) time of the accepted interactions.

Calculation:

Media type: All

Data type: Number Metric type: Interval

Used in:

Agent Not Ready Report

Metric name: Not Ready Out

Agent > State and Reason > Interaction State

Description: The total number of times that this agent initiated outbound or internal interactions while

in the NotReady state. The count excludes consultations that the agent participated in while in NotReady state.

Calculation:

Media type: All

Data type: Number Metric type: Interval

Used in:

• Agent Not Ready Report

Metric name: Not Ready Out Time

Folder:

Agent > State and Reason > Interaction State

Description: The total amount of time that this agent spent handling outbound or internal interactions that the agent initiated while in the NotReady state. This duration includes dial time, engagement time, and hold time and excludes consultations that the agent participated in while in NotReady state.

Calculation:

Media type: All

Data type: Number Metric type: Interval

Used in:

Agent Not Ready Report

Metric name: Offered

Folder:

Agent > State and Reason > Interaction State

Description: The total number of times that interactions were received or initiated by this agent (for Agent reporting), or agents who belong to this agent group (for Agent Group reporting).

The count includes interactions that were abandoned while inviting, handling attempts that the agent rejected, and warm consultations and conferences that the agent received. This count excludes simple consultations, whether they were initiated or received. For AGT_AGENT_QUEUE records, this metric relies on the value of the **short-abandoned threshold** as configured in the **[agg-gim-thld-ID-IXN]** section.

Calculation: Used in: Agent Activity • Agent Interaction Hierarchy Report · Agent Performance Dashboard Agent Report Media type: All Agent Task Dashboard Data type: Number · Agent Utilization Email Report Metric type: Disposition · Agent Utilization Report • Predictive Routing Agent Dashboard Predictive Routing Agent Occupancy Report (Active Time and Predictive) · Supervisor Dashboard

		 Task Routing Agent Activity Task Routing Agent Group Activity
Metric name: Wrap In		Folder: Agent > State and Reason > Interaction State
Description: The total number state.	r of times that this agent received	d customer calls while in ACW (Wrap)
Calculation:		Used in:
Media type: Voice		Agent Utilization
Data type: Number Metric type: Interval		Agent Wrap Report
Metric name: Wrap In Time		Folder: Agent > State and Reason > Interaction State
		ndling customer calls that the agent t (ring) time, hold time, and time of
Calculation:		
Media type: Voice		Used in:
Data type: Number Metric type: Interval		Agent Wrap Report
		Folder:
Metric name: Wrap Out		Agent > State and Reason > Interaction State
Description: The total number of times that this agent placed calls while in ACW (Wrap) state. Consultations that the agent participated in while in ACW state are excluded from this metric.		
Calculation:		Head in
Media type: Voice		Used in:
Data type: Number Metric type: Interval		Agent Wrap Report
Metric name: Wrap Out Tin	ne	Folder:
		Agent > State and Reason > Interaction State

Description: The total amount of time that this agent spent handling internal or outbound interactions that the agent initiated while in ACW (Wrap) state. This duration includes dial time, hold time, and time of

engagement, but excludes consultations that the agent participated in while in ACW state.

Calculation:	
Media type: Voice	Used in:
Data type: Number Metric type: Interval	Agent Wrap Report

Folder: Agent > State and Reason > Interaction State > Interaction Predictive Routing

Metric name: Active		Folder: Agent > State and Reason > Interaction State > Interaction Predictive Routing
Description: The total amount agent(s) login session(s) on a p		val between the beginning and end of the
Calculation:		
Media type:		Used in:
Data type: Metric type: Interval		Agent Utilization Report
		Folder:
Metric name: Agent Score		Agent > State and Reason > Interaction State > Interaction Predictive Routing
Description: The sum of the score of the agents to whom the interactions were routed.		
Calculation:		
Media type:		Used in:
Data type: Number Metric type: Interval		This metric is not used in any reports.
		Folder:
Metric name: Avg Agent So	core	Agent > State and Reason > Interaction State > Interaction Predictive Routing
Description: The average agent score during the period when Predictive Routing was active.		
Calculation: Calculated based (gpmAgentScore), divided by th where Predictive Routing was a	ne total number of interactions	Used in:Predictive Routing Agent Occupancy
Media type:		Dashboard
Data type:		Predictive Routing Agent Occupancy

Metric type: Interval

Report (Active Time and Predictive)

Folder: Agent > State and Reason > Summarized State

Metric name: % Busy Time	Folder: Agent > State and Reason > Summarized State	
Description: The percentage of the agent's time accounted for activities.	by the sum of all interaction-processing	
Calculation: Calculated based on the Busy Time and Active Time Summarized State metrics. Media type: All Data type: Number Metric type: Interval	 Agent Summarized State Agent Summary Activity Email Report Agent Summary Activity Report (Email) Agent Task Dashboard Agent Utilization Predictive Routing Agent Occupancy Predictive Routing Agent Occupancy Report (Interaction Time) Supervisor Dashboard Task Routing Agent Group Summary Activity Task Routing Agent Summary Activity 	
Metric name: % Not Ready Reason Time	Folder: Agent > State and Reason > Summarized State	
Description: The percentage of time within the interval that this agent was in the NotReady state that can be attributed to a specific hardware or software reason code, relative to the agent's total NotReady duration within the interval for a particular media channel. If no reason codes have been set up in your environment, this metric returns 0.		
Calculation: Calculated based on the Not Ready Reason Time and Not Ready Time Summarized State metrics.	Used in:	
Media type: All Data type: Number	Agent Not Ready Reason Code Report	

Metric type: Interval		
Metric name: % Not Ready	Time	Folder:
		Agent > State and Reason > Summarized State
		nis agent's state was NotReady, relative to on on a particular media channel.
Calculation: Calculated based Active Time Summarized State		Used in:
Active Time Summarized State	metrics.	Agent Not Ready Reason Code Report
		Agent Not Ready Report
		Agent Summarized State
		Agent Summary Activity Email Report
		 Agent Summary Activity Report (Active)
Media type: All		Agent Task Dashboard
Data type: Number Metric type: Interval		Predictive Routing Agent Occupancy
,		 Predictive Routing Agent Occupancy Report (Interaction Time)
		Supervisor Dashboard
		 Task Routing Agent Group Summary Activity
		Task Routing Agent Summary Activity
Metric name: % Occupancy		Folder:
Metric name. 70 occupancy		Agent > State and Reason > Summarized State
Description: The percentage of time that this agent's state was Busy within the interval, relative to the total duration within the interval of the agent's active session on a particular media channel.		
This metric reflects the percentage of time that agents actually spent handling interactions against their available or idle time.		
Calculation: Calculated as Active Time minus Ready and Not- Used in:		
Ready time, divided by the difference between Active and		
Not-Ready time.		 Agent Summarized State Agent Summary Activity Email Report
Modin turner All		
Media type: All		 Agent Summary Activity Report (Active)
Data type: Number Metric type: Interval		Agent Task Dashboard
		Agent Utilization

- Predictive Routing Agent Occupancy
- Predictive Routing Agent Occupancy Report (Active Time & Predictive)
- · Supervisor Dashboard
- Task Routing Agent Group Summary Activity
- Task Routing Agent Summary Activity

Metric name: % Omni Busy Time

Folder:

Agent > State and Reason > Summarized State

Description: The percentage of time of all of interaction-processing activities including the time that is associated with requests for consultation that the agent received and excluding the time spent processing after-call work.

Calculation:

Media type:

Data type:

Metric type: Interval

Used in:

Agent Omnichannel Activity Report

Metric name: % Omni Not Ready Time

Folder:

Agent > State and Reason > Summarized State

Description: The percentage of time within the interval that this agent was in the NotReady state, irrespective of media channel (including Do Not Disturb duration, if configured) regardless of whether a reason was indicated.

Calculation:

Media type:

Data type:

Metric type: Interval

Used in:

· Agent Omnichannel Activity Report

Metric name: % Omni Occupancy

Folder:

Agent > State and Reason > Summarized State

Description: The percentage of time that this agent's state was Busy within the reporting interval, relative to the total duration within the interval of the agent's active session, regardless of media channel.

This metric reflects the percentage of time that agents actually spent handling interactions against their available or idle time.

Calculation: Calculated as

AGT_I_MN_SESS_STATE.ACTIVE_TIME minus AGT_I_MN_SESS_STATE.READY_TIME and

Used in:

This metric is not used in any reports.

AGT I MN SESS STATE.NOT READY TIME, divided by the difference between AGT I MN SESS STATE.ACTIVE TIME and AGT I MN SESS STATE.NOT READY TIME. Media type: All Data type: Number Metric type: Interval Folder: Metric name: % Omni Other State Time Agent > State and Reason > Summarized State **Description:** The percentage of time within the interval that this agent's state was unknown (that is, neither Ready nor NotReady) after login, relative to the total duration within the reporting interval of the agent's active session, regardless of media channel. An agent's state can be neither Ready nor NotReady can occur, for instance, if the switch does not force agent DNs into the Ready state upon login. Calculation: Calculated based on the the Other State Time and AGT I MN SESS STATE.ACTIVE TIME metric. Used in: Media type: All · Agent Omnichannel Activity Report Data type: Number Metric type: Interval Folder: Metric name: % Omni Ready Time Agent > State and Reason > Summarized State Description: The percentage of time within the interval that this agent's state was Ready, relative to the total duration within the interval of the agent's active session, regardless of media channel. **Calculation:** Used in: Media type: Agent Omnichannel Activity Report Data type: Metric type: Interval Folder: **Metric name: % Omni Wrap Time** Agent > State and Reason > Summarized State **Description:** The percentage of time that this agent spent in ACW (Wrap) state within the interval, relative to the total duration of the agent's active session within the interval, regardless of media channel. Calculation: Calculated based on the the Wrap Time and AGT_I_MN_SESS_STATE.ACTIVE_TIME metrics. Used in: Media type: Agent Omnichannel Activity Report Data type:

Metric type: Interval

Metric name: % Other State Time

Folder:

Agent > State and Reason > Summarized State

Description: The percentage of time within the interval that this agent's state was unknown (that is, neither Ready nor NotReady) after login, relative to the total duration within the interval of the agent's active session on a particular media channel.

The situation in which an agent's state is neither Ready nor NotReady can occur if the switch, for instance, does not force agents' DNs into the Ready state upon login.

Calculation: Calculated based on the Other State Time and Active Time Summarized State metrics.

Used in:

- · Agent Summarized State
- Agent Summary Activity Report (Active)
- Predictive Routing Agent Occupancy
- Predictive Routing Agent Occupancy Report (Interaction Time)
- Task Routing Agent Group Summary Activity
- Task Routing Agent Summary Activity

Media type: All

Data type: Number Metric type: Interval

Metric name: % Ready TIme

Folder:

Agent > State and Reason > Summarized State

Description: The percentage of time within the interval that this agent's state was Ready, relative to the total duration within the interval of the agent's active session on a particular media channel.

Calculation: Calculated based on the Ready Time and Active Time Summarized State metrics.

Used in:

- · Agent Summarized State
- Agent Summary Activity Email Report
- Agent Summary Activity Report (Email)
- · Agent Task Dashboard
- Agent Utilization
- Predictive Routing Agent Occupancy
- Predictive Routing Agent Occupancy Report (Interaction Time)
- · Supervisor Dashboard
- Task Routing Agent Group Summary Activity

Media type: All

Data type: Number Metric type: Interval

		Task Routing Agent Summary Activity	
Metric name: % Wrap Time	.	Folder:	
		Agent > State and Reason > Summarized State	
	Description: The percentage of time that this agent spent in ACW (Wrap) state within the interval, relative to the total duration of the agent's active session within the interval.		
Calculation: Calculated based Time Summarized State metric		Used in:	
		Agent Summarized State	
		 Agent Summary Activity Report (Active) 	
		Agent Wrap Report	
Media type: Voice		Predictive Routing Agent Occupancy	
Data type: Number Metric type: Interval		 Predictive Routing Agent Occupancy Report (Interaction Time) 	
		 Task Routing Agent Group Summary Activity 	
		Task Routing Agent Summary Activity	

Metric name: Active Time Folder: Agent > State and Reason > Summarized State

Description: The total amount of time that elapsed between the beginning and end of this agent's login session(s) on a particular media channel, irrespective of the intervals in which the resource session occurs. If an agent logs into multiple DNs, login duration is measured from the moment at which the agent logs in to the first DN to the moment at which the agent is no longer logged in to any DN. If the agent's session was still active when the data was compiled, the agent's session duration appears as null in the reports.

If the agent is not forcibly logged out when the calendar dates ends, login duration is split over both days.

Calculation:	Used in:
	Agent Interval Based Report
	Agent Not Ready Report
Media type: All	Agent Summarized State
Data type: Number Metric type: Interval	Agent Summary Activity Email Report
Metric type: interval	 Agent Summary Activity Report (Active)
	Agent Task Dashboard

 Agent Wrap Report Predictive Routing Agent Occupancy Predictive Routing Agent Occupancy Report (Active Time & Predictive)
 Predictive Routing Agent Occupancy Report (Interaction Time)
Supervisor Dashboard
 Task Routing Agent Group Summary Activity
Task Routing Agent Summary Activity

Metric name: Busy		Folder:
,		Agent > State and Reason > Summarized State
	of times that this agent was in t g consultations and excluding aft	the Busy state within the interval in order ter-call work.
Calculation:		
Media type: All		Used in:
Data type: Number Metric type: Interval		This metric is not used in any reports.

Metric name: Busy Time	Folder:
	Agent > State and Reason > Summarized State

Description: The total duration of all of interaction-processing activities including the time that is associated with requests for consultation that the agent received and excluding the time spent processing after-call work.

processing after-call work.	
Calculation:	Used in:
Media type: All Data type: Number Metric type: Interval	 Agent Summarized State Agent Summary Activity Email Report Agent Summary Activity Report (Active) Agent Task Dashboard Predictive Routing Agent Occupancy Predictive Routing Agent Occupancy Report (Interaction Time) Supervisor Dashboard Task Routing Agent Group Summary

		Activity • Task Routing Agent Summary Activity
Metric name: Not Ready		Folder: Agent > State and Reason > Summarized State
Description: The total number a particular media channel.	of times within the interval that	this agent was in the NotReady state on
Calculation:		
Media type: All		Used in:
Data type: Number Metric type: Interval		This metric is not used in any reports.
Metric name: Not Ready Re	eason Count	Folder:
		Agent > State and Reason > Summarized State
	of times within the interval that luding instances of Do Not Distur	this agent was in the NotReady state on b, if configured) for this reason.
Calculation:		
Media type: All		Used in:
Data type: Number Metric type: Interval		Agent Not Ready Reason Code Report
Metric name: Not Ready Re	eason Time	Folder:
		Agent > State and Reason > Summarized State
Description: The total amount of time within the interval that this agent was in the NotReady state on a particular media channel (including Do Not Disturb duration, if configured) for the specified reason.		
Calculation:		
Media type: All		Used in:
Data type: Number Metric type: Interval		Agent Not Ready Reason Code Report
Metric name: Not Ready Ti	me	Folder: Agent > State and Reason > Summarized State
	Description: The total amount of time within the interval that this agent was in the NotReady state for a particular media channel (including Do Not Disturb duration, if configured) regardless of whether a reason was indicated	

was indicated.

Calculation:		Used in:
Media type: All Data type: Number Metric type: Interval		 Agent Not Ready Reason Code Report Agent Summarized State Agent Summary Activity Email Report Agent Summary Activity Report (Active) Agent Task Dashboard Agent Wrap Report Predictive Routing Agent Occupancy Predictive Routing Agent Occupancy Report (Interaction Time) Supervisor Dashboard Task Routing Agent Group Summary Activity Task Routing Agent Summary Activity
Metric name: Omni Active	Time	Folder: Agent > State and Reason > Summarized State
agent's login session(s), regard switches, DNs, and/or queues, DN/queue (if this login falls witl	lless of media channel. In the sce this metric starts the moment at	val between the beginning and end of this enario in which an agent logs into multiple which the agent logs in to the first switch/moment at which the agent is no longer erval).
Calculation:		Used in:
Media type: Data type: Metric type:		Agent Omnichannel Activity Report
Metric name: Omni Busy		Folder: Agent > State and Reason > Summarized State
Description: The number of ti	mes the agent entered the Busy	state, regardless of media channel
Calculation:		Used in:
Media type:		
Data type: Metric type:		Agent Omnichannel Activity Report

Metric name: Omni Busy Time		Folder: Agent > State and Reason > Summarized State
	nsultation that the agent receive	activities, including the time that is d and excluding the time spent
Calculation:		
Media type:		Used in:
Data type: Metric type:		Agent Omnichannel Activity Report
Metric name: Omni Not Re	ady	Folder:
		Agent > State and Reason > Summarized State
Description: The number of ti	mes the agent entered the Not R	eady state, regardless of media channel.
Calculation:		
Media type:		Used in:
Data type: Metric type:		Agent Omnichannel Activity Report
Metric name: Omni Not Re	ady Time	Folder: Agent > State and Reason > Summarized State
Metric name: Omni Not Re	ady Time	
Description: The total amount	t of time within the interval that t	
Description: The total amount regardless of media channel (ir	t of time within the interval that t	Agent > State and Reason > Summarized State this agent was in the NotReady state, if configured) regardless of whether a
Description: The total amount regardless of media channel (ir reason was indicated.	t of time within the interval that t	Agent > State and Reason > Summarized State this agent was in the NotReady state,
Description: The total amount regardless of media channel (ir reason was indicated. Calculation:	t of time within the interval that t	Agent > State and Reason > Summarized State this agent was in the NotReady state, if configured) regardless of whether a
Description: The total amount regardless of media channel (in reason was indicated. Calculation: Media type: Data type:	t of time within the interval that t	Agent > State and Reason > Summarized State this agent was in the NotReady state, if configured) regardless of whether a Used in:
Description: The total amount regardless of media channel (in reason was indicated. Calculation: Media type: Data type:	t of time within the interval that t ncluding Do Not Disturb duration,	Agent > State and Reason > Summarized State this agent was in the NotReady state, if configured) regardless of whether a Used in:
Description: The total amount regardless of media channel (in reason was indicated. Calculation: Media type: Data type: Metric type:	t of time within the interval that t ncluding Do Not Disturb duration,	Agent > State and Reason > Summarized State this agent was in the NotReady state, if configured) regardless of whether a Used in: Agent Omnichannel Activity Report
Description: The total amount regardless of media channel (in reason was indicated. Calculation: Media type: Data type: Metric type: Metric name: Omni Other S Description: The total amount regardless of media channel. T	t of time within the interval that the cluding Do Not Disturb duration, State Time t of time that the agent state was the situation in which the state of	Agent > State and Reason > Summarized State this agent was in the NotReady state, if configured) regardless of whether a Used in: Agent Omnichannel Activity Report Folder:
Description: The total amount regardless of media channel (in reason was indicated. Calculation: Media type: Data type: Metric type: Metric name: Omni Other S Description: The total amount regardless of media channel. Tusually occurs upon first login in	t of time within the interval that the cluding Do Not Disturb duration, State Time t of time that the agent state was the situation in which the state of	Agent > State and Reason > Summarized State this agent was in the NotReady state, if configured) regardless of whether a Used in: • Agent Omnichannel Activity Report Folder: Agent > State and Reason > Summarized State s neither Ready nor NotReady after login, an agent is neither Ready nor NotReady

Data type: Metric type:		
Metric name: Omni Ready		Folder: Agent > State and Reason > Summarized State
Calculation: Media type:	mes the agent entered the Ready	y state, regardless of media channel.Used in:Agent Omnichannel Activity Report
Data type: Metric type:		
Metric name: Omni Ready	Time	Folder: Agent > State and Reason > Summarized State
Description: The total amount channel.	t of time that this agent was in th	ne Ready state, regardless of media
Calculation:		Used in:
Media type: Data type: Metric type:		Agent Omnichannel Activity Report
Metric name: Omni Wrap		Folder: Agent > State and Reason > Summarized State
-	mes the agent entered the Wrap	state, regardless of media channel.
Calculation:		Used in:
Media type: All Data type: Number Metric type:		Agent Omnichannel Activity Report
		Folder:
Metric name: Omni Wrap T	ime	Agent > State and Reason > Summarized State
		this agent spent in ACW (Wrap) state an interaction, regardless of media
Calculation:		Used in:
Media type: All		Agent Omnichannel Activity Report

Data type: Number Metric type: Interval			
Metric name: Other State	Гіте	Folder:	
		Agent > State and Reason > Summarized State	
Description: The total amount of time that the state of this agent was neither Ready nor NotReady after login to a particular media channel. The situation in which the state of an agent is neither Ready nor NotReady usually occurs upon first login if the switch, for instance, does not force agents into the Ready state upon login.			
Calculation: Calculated based		Used in:	
Time, Ready Time, Not Ready T Summarized State metrics.	ime, and Wrap Time	Agent Summarized State	
		 Agent Summary Activity Report (Active) 	
		Agent Task Dashboard	
		Predictive Routing Agent Occupancy	
Media type: All Data type: Number		Predictive Routing Agent Occupancy Report (Interaction Time)	
Metric type: Interval		Supervisor Dashboard	
		Task Routing Agent Group Summary	
		Activity	
		Task Routing Agent Summary Activity	
Metric name: Ready		Folder:	
,		Agent > State and Reason > Summarized State	
Description: The total numbe particular media channel.	r of times within the interval that	this agent was in the Ready state on a	
Calculation:			
Media type: All		Used in:	
Data type: Number Metric type: Interval		This metric is not used in any reports.	
Metric name: Ready Time		Folder:	
		Agent > State and Reason > Summarized State	
Description: The total amount of time that this agent was in the Ready state for a particular media type.			
Calculation:			
Media type:		Used in:	

Data type: Metric type: Interval		 Agent Summarized State Agent Summary Activity Email Report Agent Summary Activity Report (Active) Agent Task Dashboard Predictive Routing Agent Occupancy Predictive Routing Agent Occupancy Report (Interaction Time) Supervisor Dashboard Task Routing Agent Group Summary Activity Task Routing Agent Summary Activity
Metric name: Start Date Ti	me Key	Folder: Agent > State and Reason > Summarized State
	erved for internal use to employ GRP, or AG2_AGENT_QUEUE hiera	a key for a particular date and time from rchies.
Calculation:		
Media type: All		Used in:
Data type: Number Metric type:		This metric is not used in any reports.
Metric name: State Reason		Folder:
		Agent > State and Reason > Summarized State
Description: Total number of t the interval(s) in which the state	imes this agent was in a specific e-reason combination endures.	state for a specific reason, irrespective of
Calculation:		
Media type:		Used in:
Data type:		This metric is not used in any reports.

Metric name: State Reason Time	Folder:
	Agent > State and Reason > Summarized State

Description: The total amount of time that this agent was in a specific state for a specific reason, irrespective of the interval(s) in which the state-reason combination endures.

Data type: Metric type: Interval This time is measured from the moment at which the agent enters this state-reason combination to the moment at which the agent exits this state or state-reason combination. If the agent's state was still active when the data was compiled, the duration of the agent in this state appears as null in the reports.

Calculation:

Media type: All

Data type: Number Metric type: Interval

Used in:

This metric is not used in any reports.

Metric name: Wrap

Folder:

Agent > State and Reason > Summarized State

Description: The total number of times that the state of this agent was neither Ready nor NotReady after login to a particular media channel. The situation in which the state of an agent is neither Ready nor NotReady usually occurs upon first login if the switch, for instance, does not force agents into the Ready state upon login.

Calculation: Calculated based on the Active Time, Busy Time, Ready Time, Not Ready Time, and Wrap Time Summarized State metrics.

Media type: All

Data type: Number Metric type: Interval

Data type: Interval

Lead in:

Agent Summary Activity Report

Metric name: Wrap Time

Folder:

Agent > State and Reason > Summarized State

Description: The total amount of time, in seconds, within the interval that this agent spent in ACW (Wrap) state whether or not the reason for entering this state was related to an interaction.

Calculation: Used in: · Agent Summarized State Agent Summary Activity Report (Active) · Agent Task Dashboard Agent Wrap Report Media type: • Predictive Routing Agent Occupancy Data type: Metric type: Interval • Predictive Routing Agent Occupancy Report (Interaction Time) Supervisor Dashboard Task Routing Agent Group Summary Activity Task Routing Agent Summary Activity

Genesys CX Insights 9.0 Projects Reference Guide	