



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

Work with Genesys CX Insights Reports

Callback Details Report

Contents

- [1 Understanding the Callback Details Report](#)
- [2 Prompts for the Callback Details Report](#)
- [3 Attributes used in the Callback Details Report](#)
- [4 Metrics used in the Callback Details Report](#)
- [5 Customize the report to filter by Desired Time and Dial Result](#)
 - [5.1 Attributes used in this procedure](#)



- Administrator
- Supervisor

View detailed information about Callback usage in your contact center.

Related documentation:

-
-
-
-
-

RSS:

- [For private edition](#)

The (**Callback** folder) **Callback Details Report** shows detailed information about the number and percentage of offered callbacks that were successful, versus how many were declined, canceled, or abandoned.

Understanding the Callback Details Report

Callback Det

To get a better idea of what this report looks like, view sample output from the report:
HRCXICallbackDetailsReport.pdf

Prompts for the Callback Details Report

Work with Genesys CX Insights Reports

Prompt	Description
	where callback was dialed, or enter 0 to include all scheduled Callbacks, even if they were never dialed.
Queue	Select one or more queues from which to gather data into the report. Default: ALL
Customer Phone Number	Select one or more customer phone numbers for which to gather data into the report. Default: ALL
Tenant	Select one or more tenants to include in the report. Default: ALL

Attributes used in the Callback Details Report

Attribute	Description
Tenant	Enables data within the reporting interval to be organized by tenant. For multi-tenant environments, the universe connection that you define points to only one tenant schema in the Info Mart. New connections are required for access to other tenant schemas.
Queue	Enables data within the reporting interval to be organized based on the name of the virtual queue.
Service ID	Enables data within the reporting interval to be organized based on the original SCXML/GMS session ID.
Customer Phone Number	Enables data to be organized based on the phone number provided by the customer for callback. This number is used to dial out (CUSTOMER_TERMINATED scenario) or used to execute match by ANI (CUSTOMER_ORIGINATED scenario).
Forced Dialed	Enables data to be organized based on whether the callback queue is being flushed, and dialing (or push notification) is being forced regardless of actual agent availability. (0 = No, 1 = Yes). A value of 1 (yes) might occur at the end of the day, when contact center personnel are trying to close the queue for the day and do not want to leave any callbacks for the next day.

Metrics used in the Callback Details Report

Metric	Description
Offered	Indicates whether callback was offered to the customer. (0=no, 1=yes)

Metric	Description
Accepted	Indicates whether callback was accepted by the customer. (0=no, 1=yes)
Service Start Timestamp	The date and time (UTC) when the Callback service started.
Ready To Start Timestamp	Either: The time when the contact center was ready to start the outbound dial attempt for CUSTOMER_TERMINATED scenarios. or: The time when the contact center sent push notification to the user device in CUSTOMER_ORIGINATED scenarios.
Customer Connected Timestamp	The time when the customer started waiting to be connected to an agent.
Callback Offered Timestamp	The time when the customer was first offered callback during the session.
Last Callback Offered Timestamp	The date and time of the last callback offered to a customer during the session.
Callback Accepted Timestamp	The time when the customer accepted callback during the session.
Push Delivery Confirmed Timestamp	The time when the application confirmed that push notification was received. This is used for CUSTOMER_ORIGINATED scenarios.
Customer Ready to Start Timestamp	The time when the customer was ready to start media interaction for CUSTOMER_ORIGINATED scenarios. This value is typically set when the application sends a request for an access number to dial and access code for match function.
Desired TimeStamp	The callback time that was promised to the customer when callback was scheduled.
Callback Attempts	The number of times the system attempted to call the customer back.
Expected Wait Time (Fmt)	The customer expected wait time when the callback dial attempt was ready to begin.
Callback Offer Time (Fmt)	The amount of time that elapsed between the instant when a callback was offered to the customer, and the instant when the customer accepted or declined the offer.
Last Callback Offer Time (Fmt)	The duration (in seconds) of the last callback offered to a customer during the session.
Offline Waiting Time (Fmt)	The amount of time that elapsed between when the customer accepted a callback offer and the time when they were connected to an agent after callback.
Establish Time (Fmt)	The amount of time required to establish the outbound call.
Connect Waiting Time (Fmt)	The amount of time that elapsed between when

Metric	Description
	the customer connected to the callback call and when an agent was connected.
Position in Queue	The customer's position in the queue when the callback outbound dial attempt was ready to begin.
Transfer Failed	The number of failed attempts to transfer the callback interaction to the agent.
Added Agent	Indicates whether an agent was successfully added to the callback call. (0=no, 1=yes)
Abandon Waiting	Indicates whether the call was abandoned by the customer while waiting for an agent to connect. (0=no, 1=yes)
Timeout Waiting (Fmt)	The number of times that a customer was disconnected because the max timeout limit was reached.
Requested Agent Assistance	The number of callbacks that were offered to customers who had requested agent assistance. (0=no, 1=yes)
Callback Offers per Session	The number of times callback was offered, per single interaction.

Customize the report to filter by Desired Time and Dial Result

Use this procedure to customize this report to organize callback information based on the callback time customers requested, and result of the callback attempt.

Important

Note that filtering by Desired Time can decrease SQL performance. Genesys recommends running a report with this modification over a limited period of time, such as one day or less.

1. Log in with an account having Administrator privileges.
2. Open and run the Callback Details report.
3. In the **Save As** editor:
 1. Click **Report Home > Save As**.
 2. In the **Save in** field, choose either: **Shared Reports > Custom** — to make the new report accessible to other users, or **My Reports** — to make the new report accessible only to you.
 3. Enter a **Name** for the report, such as **Callback Details - By Desired Time**, and optionally modify the **Description**, or **Advanced Options**.
 4. Click **OK**.
4. In the **Report Saved** editor, click **Run newly saved report**.
5. The prompts page opens; make appropriate selections and click **Run Report**.
You can now modify the report:
6. In the menu, click **Grid > Design** to view the Report Objects Editor (if it's not already visible).
7. Click **All Objects**, and browse to **GCXI > Callback**. Note that objects in the folder are sorted alphabetically; use the controls at the bottom of the list to see additional objects.
8. To organize the data based on the callback time that customers requested:
 1. From the list of available objects, drag the attribute **Desired Time** into the filter panel, and set the input value for it to **Between (enter value 1;value2)**.
 2. Drag the existing **Pre-set and Day and Time Range** and **Pre-set and Day and Time Range(Callback)** filters out of the panel, to remove them from the report.
9. To organize the data based on the result of the callback attempt:
 1. From the list of available objects, drag the attribute **Dial Result** into the report grid.
 2. Select forms if required.
10. Once you have finished editing the report, click **Save**, and re-run the report to test your changes.

For more information about customizing Genesys CX Insights, see [Customize reports](#).

Attributes used in this procedure

Attribute	Description
Dial Result	Enables data to be organized based on the dialing result. Values=BUSY, NO_ANSWER, ANSWERING_MACHINE, ERROR_TONE, FAX, PERSON, REDIAL_LIMIT_REACHED.

Attribute	Description
Desired Time	Enables data to be organized based on the callback time requested by the customer.

For more information about objects you can use to customize Callback reports, see Callback in the *Genesys CX Insights Projects Reference Guide*.