



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.


## Work with Genesys CX Insights Reports

[Predictive Routing Detail Report](#)

---

## Contents

- 1 Prompts in the Predictive Routing Detail Report
- 2 Attributes in the Predictive Routing Detail Report
- 3 Metrics in the Predictive Routing Detail Report



- Administrator
- Supervisor

Find out how Genesys Predictive Routing (GPR) is used in your contact center, and how enabling GPR impacts Key Performance Indicators (KPI).

### **Related documentation:**

- 
- 
- 
- 

### **RSS:**

- [For private edition](#)

Tenant	Media Type	Interaction ID	Start Timestamp	End Timestamp	From	To	GUID	Interaction Handling Attempt ID	Interaction Type	Customer ID	Handling Attempt Start	Handling Attempt End	Service Type	Service Sub
		19	12/5/2017 4:10:00 PM	12/5/2017 4:10:00 PM	3600	1030	88EGLMS9110B594D9AF013B800000001	113	Inbound	DEFAULT_CUSTOMER_ID	12/5/2017 4:10:00 PM	12/5/2017 4:10:00 PM	DEFAULT_SERVICE_TYPE	DEFAULT
		25	12/6/2017 9:20:00 AM	12/6/2017 9:40:00 AM	3600	1030	363116200L8UNJ50B540000001	149	Inbound	DEFAULT_CUSTOMER_ID	12/6/2017 9:40:00 AM	12/6/2017 9:40:00 AM	DEFAULT_SERVICE_TYPE	DEFAULT
		36	12/1/2017 1:24:00 PM	12/1/2017 1:24:00 PM	3600	1030	M1G00MLP0B654V50NE013A000001	193	Inbound	DEFAULT_CUSTOMER_ID	12/1/2017 1:24:00 PM	12/1/2017 1:24:00 PM	DEFAULT_SERVICE_TYPE	DEFAULT
		37	12/1/2017 1:24:00 PM	12/1/2017 1:24:00 PM	3600	1030	620FVQJSPHTB3AL1F055FNC000001	265	Inbound	DEFAULT_CUSTOMER_ID	12/1/2017 1:24:00 PM	12/1/2017 1:24:00 PM	DEFAULT_SERVICE_TYPE	DEFAULT
		39	12/1/2017 4:08:00 PM	12/1/2017 4:08:00 PM	3600	1030	EFPPNHCPLS0LN6NPUTNGP5000001	217	Inbound	DEFAULT_CUSTOMER_ID	12/1/2017 4:08:00 PM	12/1/2017 4:08:00 PM	DEFAULT_SERVICE_TYPE	DEFAULT
		41	12/1/2017 4:15:00 PM	12/1/2017 4:15:00 PM	3600	1030	IFPVOCH3H4T010PNK0616000001	229	Inbound	DEFAULT_CUSTOMER_ID	12/1/2017 4:15:00 PM	12/1/2017 4:15:00 PM	DEFAULT_SERVICE_TYPE	DEFAULT
		43	12/1/2017 4:21:00 PM	12/1/2017 4:21:00 PM	3600	1030	601191990537N9K519NLT800001	241	Inbound	DEFAULT_CUSTOMER_ID	12/1/2017 4:21:00 PM	12/1/2017 4:21:00 PM	DEFAULT_SERVICE_TYPE	DEFAULT
		45	12/1/2017 4:28:00 PM	12/1/2017 4:28:00 PM	3600	1030	42V10B8CH10414M529YQ00AC000001	253	Inbound	DEFAULT_CUSTOMER_ID	12/1/2017 4:28:00 PM	12/1/2017 4:28:00 PM	DEFAULT_SERVICE_TYPE	DEFAULT
		47	12/1/2017 4:36:00 PM	12/1/2017 4:36:00 PM	3601	1021	1608071L85640W910KUCL950000001	265	Inbound	DEFAULT_CUSTOMER_ID	12/1/2017 4:36:00 PM	12/1/2017 4:36:00 PM	DEFAULT_SERVICE_TYPE	DEFAULT
		49												
		51												
		53												
		55												
		57												
		59												
		61												
		63												
		65												
		67												
		68												
		71												
		73												
		75												
		77												
		81												
		85												
		89												
		91												
		93												
		95												
		97												
		99												
		101												
		103												
		105												
		107												
		109												
		111												
		113												
		115												
		117												
		119												
		121												
		123												
		125												
		127												
		129												
		131												
		133												
		135												
		137												
		139												
		141												
		143												
		145												
		147												
		149												
		151												
		153												
		155												
		157												
		159												
		161												
		163												
		165												
		167												
		169												
		171												
		173												
		175												
		177												
		179												
		181												
		183												
		185												
		187												
		189												
		191												
		193												
		195												
		197												
		199												
		201												
		203												
		205												
		207												
		209												
		211												
		213												
		215												
		217												
		219												
		221												
		223												
		225												
		227												
		229												
		231												
		233												
		235												
		237												
		239												
		241												
		243												
		245												
		247												
		249												
		251												
		253												
		255												
		257												
		259												
		261												
		263												
		265												
		267												
		269												
		271												
		273												
		275												
		277												
		279												
		281												
		283												
		285												
		287												
		289												
		291												
		293												
		295												
		297												
		299												
		301												
		303												
		305												
		307												
		309												
		311												
		313												
		315												
		317												
		319												
		321												
		323												
		325			</td									

---

The following tables explain the prompts, attributes, and metrics used in this report:

## Prompts in the Predictive Routing Detail Report

<b>Prompt</b>	<b>Description</b>
Preset Day Filter	From the list of preset options, choose the day on which to report. Default: Today
Start Time	Choose the day and time from which to begin collecting data into the report (the report shows no more than one day at a time).
End Time	Choose the day and time at which to stop collecting data into the report (the report shows no more than one day at a time).
Target Agent Group	Choose the Agent group on which to report.
Target Agent	Choose individual agents on which to report.
Last Queue	Restrict the data in the report based on the name of the last queue in which the interaction traveled before it was handled. This attribute excludes virtual queues.
Customer ID	Restrict the data in the report based on the customer ID as it appears in an external CRM application. This value enables Genesys Info Mart tables to be joined to external data-mart tables and is referenced by the user-defined GIM key that has an ID of 10053. Refer to the Genesys Info Mart 8.0 Deployment Guide for information about GIM attached data key assignments.
From	Restrict the data in the report based on the source address of the interaction. For voice, the source address is the interaction's automatic number identification (ANI). For email, the source address is the customer's email address. For chat, the source address is empty.
To	Restrict the data in the report based on the target address of the interaction. For voice, the target address is the interaction's dialed number identification service (DNIS). For email, the target address is a contact center email address. For chat, the target address is empty.
Business Result	Restrict the data in the report based on the business result.
Customer Segment	Restrict the data in the report based on the customer segment.
Service Type	Restrict the data in the report based on the service type.
Service Subtype	Restrict the data in the report based on the service subtype.

Prompt	Description
Media Type	Restrict the data in the report based on the media type.
Interaction Type	Restrict the data in the report based on the interaction type.
Predictor	Restrict the data in the report based on the identifier for the predictor that was used to request scoring for predictive routing.
Model	Restrict the data in the report based on the identifier for the model that was used to score the agent for predictive routing.
Tenant	Restrict the data in the report based on the tenant name.
Interaction ID	Restrict the data in the report based on the identifiers associated with interactions.

## Attributes in the Predictive Routing Detail Report

Attribute	Description
Tenant	Enables the organization of data based on the specific tenant or business unit for a customer deployment.
Media Type	Enables the organization of data based on the media type of the interaction—for example, VOICE, EMAIL, and CHAT.
Interaction ID	Enables the organization of data based on the interaction ID of the INTERACTION_FACT or the INTERACTION_RESOURCE_FACT table. For voice interactions, the Interaction ID is the call's connection ID, which is assigned by the telephony server. This ID remains unchanged for as long as the telephony server processes the interaction. For multimedia interactions originating from an Interaction Server, this value is the assigned Interaction ID.
Start Timestamp	Enables the organization of data based on the moment when the interaction entered the contact center.
End Timestamp	Enables the organization of data based on the moment when the interaction ended.
From	Enables the organization of data based on the source address of the interaction. For voice, the source address is the interaction's automatic number identification (ANI). For email, the source address is the customer's email address. For chat, the source address is empty.
To	Enables the organization of data based on the

Attribute	Description
	target address of the interaction. For voice, the target address is the interaction's dialed number identification service (DNIS). For email, the target address is a contact center email address. For chat, the target address is empty.
GUID	Enables the organization of data based on the globally unique identifier of the interaction as reported by the interaction media server. This identifier may not be unique. In the case of T-Server voice interactions, the GUID is the Call UUID. In the case of Multimedia, the GUID is the Interaction ID from Interaction Server.
Interaction/Handling Attempt ID	Enables the organization of data based on the primary key of the INTERACTION_RESOURCE_FACT table.
Interaction/Type	Enables the organization of data based on the interaction's type—for example, Inbound, Outbound, and Internal.
Customer ID	<p>The customer ID as it appears in an external CRM application. This value enables Genesys Info Mart tables to be joined to external data-mart tables and is referenced by the user-defined Genesys Info Mart key that has an ID of 10053. Refer to the Genesys Info Mart Deployment Guide for information about Genesys Info Mart attached data key assignments.</p> <p>The Customer ID attribute in the Flow folder references a field in a derived table whose values are sourced, in part, from the listed Info Mart table.</p>
Handling Attempt Start	Enables data to be organized by the moment when the resource's participation in the interaction started.
Handling Attempt End	Enables data to be organized by the moment when the resource's participation in the interaction ended.
Business Attributes/Service Type	Enables the organization of data based on the type of service that was assigned to the interaction.
Business Attributes/Service Subtype	Enables the organization of data based on the detailed type of service that the customer requested.
Business Attributes/Customer Segment	Enables the organization of data based on the configured customer segment.
Business Attributes/Business Result	Enables the organization of data based on the configured business result.
Routing Target Selected	Enables the organization of data based on the name of the DN group that is the target of the routing strategy.
Last Queue Type	Enables data within the reporting interval to be organized based on the type of queue, such as ACDQueue, InteractionQueue, or

Attribute	Description
	<p>InteractionWorkBin.</p> <p>Adding this Last Queue to a report can have a significant impact on performance.</p>
Last VQueue	Enables the organization of data based on the name of the last virtual queue in which the interaction traveled before it was handled.
Handling Resource	Enables the organization of data based on the name of the queue, virtual queue, workbin, Interaction queue, IVR port, or agent.
Resource State	Enables the organization of data based on the media-specific or detailed state of the resource—for example, Busy, Ready, NotReady, and AfterCallWork.
Technical Result	Enables the organization of data based on its disposition—its technical result and other aspects of the technical result—for example, Abandoned, Completed, Diverted, Pulled, and Transferred.
Technical Result/Reason	Enables the organization of data based on the reason for the technical result—for example, Abandoned-WhileRinging, AnsweredByAgent, and RouteOnNoAnswer.
Technical Result/Resource Role	Enables the organization of data based on the role that is associated by the resource—for example, Puller, Received, and RoutedTo.
Technical Result/Role Reason	Enables the organization of data based on the reason of the resource role—for example, Conference-Initiator, ConferenceJoined, and PulledBackTimeout.
Predictor Switch	Enables the organization of data based on whether predictive routing is ON or OFF.
Agent / Customer Surplus	Enables the organization of data by whether an interaction was processed by GPR under an 'Agent-Surplus' or 'Interaction Surplus' scenario, when running in A/B Testing interleaved mode.
PR Mode	Enables the organization of data based on the value of gpm-mode, which indicates the current mode of operation of GPR. Value is one of: prod, off, gpmdiscovery, ab-test-time-sliced, or unknown.
PR Result	Enables the organization of data by whether the predictive routing request was processed successfully. The value is either error or OK.
Model	Enables the organization of data by the name of the model that was used to score the agent for predictive routing.
Predictor ID	Enables the organization of data by the identifier for the predictor that was used to request scoring for predictive routing.

Attribute	Description
Predictor	Enables the organization of data by the name of the predictor that was used to request scoring for predictive routing.
GPR Customer Data Found	Enables the organization of data by whether features from customer records were successfully retrieved from CRM database and used in the calculation of agent scores.

## Metrics in the Predictive Routing Detail Report

Metric	Description																	
Interaction Duration	The duration of the interaction, in seconds.																	
PR Message	<p>If an error occurs while returning scoring results, this field contains the error message. The value is NULL if no error is returned, or an integer between 1 and 15 to identify the error as one of the following strings:</p> <table> <tr> <td>1 — Ok</td> <td>execution error</td> </tr> <tr> <td>2 — Authentication to scoring engine failed</td> <td>9 — Interaction log not found in global map</td> </tr> <tr> <td>3 — Scoring request failed</td> <td>10 — Unknown error</td> </tr> <tr> <td>4 — Agent list is empty</td> <td>11 — Channel is not supported</td> </tr> <tr> <td>5 — URS overload, interaction skipped</td> <td>12 — Reserved for future use</td> </tr> <tr> <td>6 — Predictor not found</td> <td>13 — Call Abandoned</td> </tr> <tr> <td>7 — Failed to build scoring request</td> <td>14 — Call Routing Failed</td> </tr> <tr> <td>8 — SetIdealAgent or SetReadyCondition</td> <td>15 — Predictive Routing is turned off or not used for this interaction</td> </tr> </table>	1 — Ok	execution error	2 — Authentication to scoring engine failed	9 — Interaction log not found in global map	3 — Scoring request failed	10 — Unknown error	4 — Agent list is empty	11 — Channel is not supported	5 — URS overload, interaction skipped	12 — Reserved for future use	6 — Predictor not found	13 — Call Abandoned	7 — Failed to build scoring request	14 — Call Routing Failed	8 — SetIdealAgent or SetReadyCondition	15 — Predictive Routing is turned off or not used for this interaction	
1 — Ok	execution error																	
2 — Authentication to scoring engine failed	9 — Interaction log not found in global map																	
3 — Scoring request failed	10 — Unknown error																	
4 — Agent list is empty	11 — Channel is not supported																	
5 — URS overload, interaction skipped	12 — Reserved for future use																	
6 — Predictor not found	13 — Call Abandoned																	
7 — Failed to build scoring request	14 — Call Routing Failed																	
8 — SetIdealAgent or SetReadyCondition	15 — Predictive Routing is turned off or not used for this interaction																	
GPR Agent Score	Predictive routing score for the agent that handled the interaction.																	
GPR Global Score	The average predictive routing score for all agents in the target group.																	
GPR Median Score	The median predictive routing score for the target group of agents.																	
GPR Max Score	The highest predictive routing score for any agent in the target group.																	
GPR Min Score	The lowest predictive routing score for any agent in the target group.																	

Metric	Description
GPR Agent Rank	The agent's predictive routing score ranked against all other agents in the target group, where 1 is the rank of the agent with the best score.
GPR Target Pool Size	The number of available agents with the requested skill set.
Interaction Duration (Fmt)	The duration of the interaction (HH:MM:SS).
Response Time (Fmt)	The time that elapsed (HH:MM:SS) before the customer received service or abandoned the interaction, including the time that the interaction spent in a queue (including routing points and non-self-service IVR ports) prior to abandonment or reaching a handling resource (agent or self-service IVR) as well as the alert duration at the resource prior to the interaction being accepted. Additionally, this metric includes the mediation duration of any immediate previous attempt to deliver the interaction that was redirected with a technical result of RoutedOnNoAnswer or Unspecified, as well as the alert duration that is associated with this attempt. Received consultations and collaborations are excluded from consideration.
Queue Time (Fmt)	The sum of the durations (HH:MM:SS) that interactions spent at ACD queue resources prior to arrival at the IRF resource. This duration excludes abandoned-while-queued interactions.
Routing Point Time (Fmt)	The sum of the durations (HH:MM:SS) that this IRF spent in routing point resources or routing strategy resources prior to arrival at the IRF resource.
Total Duration (Fmt)	The total duration (HH:MM:SS) of the IRF resource's participation in the interaction, irrespective of the interval(s) in which the IRF endures, including hold duration and the time that the interaction spent in mediation. This metric excludes alert duration, received consultations, and received collaborations.
Customer Engage Time (Fmt)	The amount of time (HH:MM:SS) that the agent processed a customer-related interaction at this resource during an interaction handling attempt. This metric includes internal interactions. For synchronous interactions, this is the time that the agent spent interacting with a customer. The duration includes talk duration of conferenced interactions. For asynchronous interactions, this is the time that the agent spent handling an inbound interaction from a customer, handling an internal interaction from another agent, or handling a reply interaction back to the customer. This duration excludes consultations and collaborations, whether they were initiated or received.
Customer Hold Time (Fmt)	The amount of time (HH:MM:SS) that the agent had the customer on hold. This metric excludes hold durations that are associated with initiated or received consultations but includes hold duration of

Metric	Description
	conferenced interactions.
Customer Handle Time (Fmt)	The sum of the values of Customer Engage Time, Customer Hold Time, and Customer Wrap Time metrics.
Customer Alert Time (Fmt)	For voice interactions, the amount of time (HH:MM:SS) that the interaction was ringing at the resource during a voice handling attempt while a customer was present.  For multimedia interactions, the amount of time (HH:MM:SS) that the customer-related interaction was alerting at the resource during an interaction handling attempt. For email interactions, this metric includes agent's handling of an inbound email from a customer or an internal email from another agent, or handling a reply email back to the customer. This metric excludes handling a collaboration, whether on the initiating or receiving side.
Customer Dial Time (Fmt)	The amount of time (HH:MM:SS) that the IRF resource spent initiating an outbound, customer-related interaction. The duration starts when the dialing event is sent, includes the mediation time that the initiator incurs while waiting for the target resource to connect, and ends when the call is either established or terminated on no answer. Initiated consultations are excluded from consideration.
Customer Wrap Time (Fmt)	The amount of time (HH:MM:SS) that the resource was in interaction-related After-Call Work (ACW or Wrap) state that pertained to this customer voice-interaction resource. The duration excludes ACW duration that is associated with received consultations.
Conference Initiated Time (Fmt)	The amount of time (HH:MM:SS) that a conference initiated by the IRF resource was connected (established). Duration applies only to the portion of the IRF that represents the IRF resource as a conference initiator.
Conference Received Time (Fmt)	The amount of time (HH:MM:SS) that a conference that was joined by the IRF resource was connected (established). Duration applies only to the portion of the IRF that represents the IRF resource as a conference joiner.