



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

Field Codes Reference Guide

Data types

Contents

- 1 Number
- 2 String
- 3 Date and time
- 4 Boolean



- Administrator

Learn about the data types you can use in field codes.

Related documentation:

-

Field codes can use the data types detailed on this page.

Number

You use numbers in field code formulas in much the same way you would in other applications, such as Microsoft Excel. All arithmetic calculations are performed internally using floating point arithmetic (with the decimal point). Rounding occurs only during formatting.

When you write numbers in formulas, you can use scientific notation (for example, 12.34e-2 is the same as 0.1234).

The Operators table lists the operators that you can use with numbers. Some rows show more than one symbol for the same operator. In these cases, the symbols are synonyms.

Operators

Operator	Description	Example	Result
-	Unary Minus	-4	-4
^	Exponentiation	2^3	8
*	Multiplication	2*3	6
/	Division	8/2	4
Mod	Modulus (Remainder)	14 Mod 5	4
+	Addition	2 + 3	5
-	Subtraction	2 - 3	-1
> GT	Greater Than	2 > 3	False
>= GE	Greater Than or Equal To	2 >= 2	True
	Less Than	2	True
	Less Than or Equal To	2	True
= == EQ	Equal To	2 = 3	False
!= NE	Not Equal To	2 3	True

Operator	Description	Example	Result
:	Format	2 : "#.###"	2.00

String

Use the String data type to represent textual data. When you write a string in a formula, you must enclose it in double quotation marks. For example:

"The sixth sheik's sixth sheep's sick."

You can use the escape sequences shown in the Escape Sequences table to include special characters in a string, such as tabs or carriage returns.

It is also possible to use HTML tags in field codes.

Escape Sequences

Escape	Translates to
\a	Alert (Bell)
\b	Backspace
\f	Form Feed
\n	Line Feed (Newline)
\r	Carriage Return
\t	Horizontal Tab
\v	Vertical Tab
\'	Single Quotation Mark
\"	Double Quotation Mark
\\	Backslash

The Operators and Strings table lists the operators that you can use with strings. All the comparison operators are case insensitive. Some rows show more than one symbol for the same operator. In these cases, the symbols are synonyms.

Operators and Strings

Symbol	Meaning	Example	Result
+	Concatenation	"How" + "die"	"Howdie"
>GT	Greater Than	"A" > "B"	False
>=GE	Greater Than or Equal To	"A" >= "B"	False
	Less Than	"A"	True
	Less Than or Equal To	"A"	True
= ==EQ	Equal To	"A" = "a"	True
!= NE	Not Equal To	"A" NE "B"	True

Date and time

Date/Time values in field code formulas represent specific moments (for example, February 3, 2002, at 10:03:55 AM). The most common operations performed on Date/Times are comparisons (for example,

If you subtract two Date/Time values, the result is the number of days between them. See the Date/Time Example 1 table for examples.

Date/Time Example 1

Formula	Result
Date(2002, 11, 23) - Date(2002, 11, 22)	1
Date(2002, 11, 22) - Date(2002, 11, 23)	-1
Date(2002, 11, 23) - Date(2002, 11, 23, 12)	-0.5

If you add (or subtract) a number to (from) a Date/Time, the result is the Date/Time moved forward (or backward) by that many days. See the Date/Time Example 2 table for examples.

Date/Time Example 2

Formula	Result
Date(2003, 11, 23) + 1	2003-11-24 00:00:00
Date(2003, 11, 23) - 0.5	2003-11-22 12:00:00

Boolean

Set Boolean values in field code formulas to either True or False. You can use the True and False keywords to write a Boolean value explicitly, although this is rarely required. Comparison operators (for example, and so on) always yield Boolean results.

The Operators and Booleans table lists the operators that you can use with Booleans. Some rows show more than one symbol for the same operator. In these cases, the symbols are synonyms.

Operators and Booleans

Symbol	Meaning	Example	Result
Not !	Unary Not	Not False Not True	True False
And &&	Logical And	False And False False And True True And False True And True	False False False True
Or {!!} {!!}	Logical Or	False Or False False Or True True Or False True Or True	False True True True
XOr	Logical Exclusive Or	False XOr False False XOr True True XOr False True XOr True	False True True False
= == EQ	Equal To	True = False	False

Symbol	Meaning	Example	Result
!= NE	Not Equal To	True False	True