



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

Operations

Logging overview and approaches

Contents

- 1 Overview and approaches
- 2 Solution-level logging approaches
 - 2.1 AKS logging approach
- 3 GKE logging
 - 3.1 Enable cloud logging
 - 3.2 Accessing logs
 - 3.3 Cloud Monitoring Console
 - 3.4 GKE Console
 - 3.5 Command-Line

Learn about the structured, unstructured, and Sidecar logging methods that Genesys Multicloud CX private edition services use.

Related documentation:

-
-

RSS:

- [For private edition](#)

Overview and approaches

Application log files contain the important diagnostic information for various issues that may arise. Support of Genesys services rely on access to these application logs. In Genesys Multicloud CX private edition, the Genesys Multicloud CX services write these log files using different methods and formats. Some services write to a standard out/standard error (stdout/stderr) console while others write directly into an RWX shared storage. This data must be accessible outside of the cluster environment for shipping diagnostic logs for further review.

By default, GKE clusters are natively integrated with Cloud Logging. When you create a GKE cluster, Cloud Logging is enabled by default.

Solution-level logging approaches

Private edition services use one of the following approaches:

- **Kubernetes-supported structured logging** — The services write structured logs. These logs are written in the standard stdout/stderr console and supported by Kubernetes. Fluentd collects these logs from multiple nodes and formats them by appending Kubernetes pod and project metadata. For more information, see Kubernetes-supported structured logging.
- **Sidecar processed logging** — The services write their logs in a log file. A sidecar container processes these log files and then writes them to the stdout/stderr console. A log aggregator such as Fluentd collects these logs from stdout/stderr and formats them by appending Kubernetes pod and project metadata. For more information, see Sidecar processed logging.
- **RWX logging (unstructured)** — The services write unstructured logs. These unstructured logs can neither be directly processed by a sidecar container nor be collected by Fluentd. These services write their logs in a mounted Persistent Volume Claim (PVC) bound to Persistent Volume (PV) which is backed by an RWX shared storage such as NFS or NAS for ease of access. For more information, see RWX (unstructured) logging.

Important

A Cluster Administrator must create appropriate PVCs and RWX shared storage path for the services that use the RWX logging method. For more information about creating the log-specific storage, refer to the related Genesys Multicloud CX private edition services.

RWX logging is deprecated. It will be phased out with the use of sidecars to facilitate legacy logging behavior.

AKS logging approach

In Azure, the Log Analytics workspace feature in the Azure Monitor service collects log data from multiple services and system. You can create a single or multiple workspaces and feed the application logs into them.

For more detailed instructions, refer [Genesys logging github](#).


GKE logging

Google Cloud's operations suite is backed by Google Stackdriver which controls logging, monitoring, and alerting within Google Cloud Platform. System and user workload logs are captured using Google's own Fluentd DaemonSet called Google-Fluentd that runs on each node in your cluster. The Daemon set parses container logs and pipes them to the stackdriver for processing.

Stackdriver provides built-in log metric capabilities that allows you to monitor specific log events for building dashboards and alert policies.

By default, GKE clusters are natively integrated with cloud logging. When you create a GKE cluster, cloud logging is enabled by default.

You can create a cluster with Logging enabled, or enable Logging in an existing cluster.



Enable cloud logging

The following table provides the supported values for the `--logging` flag for the create and update commands.

Source	Value	Logs collected
System	SYSTEM	<p>Collects logs from:</p> <ul style="list-style-type: none"> Pods running in namespaces <code>kube-system</code>, <code>istio-system</code>, <code>knative-serving</code>, <code>gke-system</code>, and <code>config-management-system</code>. Key services that are not containerized including <code>docker/containerd</code> runtime, <code>kubelet</code>, <code>kubelet-monitor</code>, <code>node-problem-detector</code>,

Source	Value	Logs collected
		<p>and kube-container-runtime-monitor.</p> <ul style="list-style-type: none"> The node's serial ports output, if the VM instance metadata <code>serial-port-logging-enable</code> is set to <code>true</code>.
Workload	WORKLOAD	All logs generated by non-system containers running on user nodes.

Console UI

To enable cloud logging through console UI, follow these steps:

1. Navigate to Console UI using: <https://console.cloud.google.com/kubernetes/list/overview?project=gcpe0001>
2. Select **Clusters** and then select the cluster name.
3. Under **Features**, select **Cloud Logging**, and then click **Edit**.
4. Select **Enable Cloud Logging** and then select **System and Workflow** from drop-down.
5. Save the changes.

The screenshot shows the Google Cloud Console UI for managing a Kubernetes cluster. On the left is a sidebar with navigation links: Clusters, Workloads, Services & Ingress, Applications, Configuration, Storage, Object Browser, Migrate to containers, and Config Management. The main area displays a table of security settings under the 'Security' tab. On the right, a modal dialog titled 'Edit Cloud Logging' is open. The dialog contains the following fields:

- Cloud Logging**: A description of the Cloud Logging add-on and a link to 'Learn more'.
- Enable Cloud Logging**: A checked checkbox.
- System and Workloads**: A dropdown menu currently set to 'System and Workloads'.
- Features**: A section with two entries: 'Cloud Run for Anthos' (Disabled) and 'Cloud Logging' (System).

At the bottom of the dialog are 'CANCEL' and 'SAVE CHANGES' buttons.

GCloud CLI

To enable cloud logging through GCloud CLI, follow these steps:

1. Log on to the existing GCloud cluster.

```
gcloud container clusters get-credentials gke1 --zone us-west1-a --project gcpe0001
```

2. Configure the logs to be sent to Cloud Logging by updating a comma-separated list of values to the `gcloud container clusters update` with `--logging` flag.


```
gcloud container clusters update gke1 \
--zone=us-west1-a \
--logging=SYSTEM,WORKLOAD
```


Accessing logs

Log Explorer

Log explorer is Google's central Logging UI. You can access logs for your Google cloud resources from this console, including GKE, Cloud SQL, VM instances and so on. You can then use logging filters to select the Kubernetes resources, such as cluster, node, namespace, pod, or container logs.

For more details about the console, click [here](#).





Cloud Monitoring Console

Cloud Monitoring Console allows you to track metrics of resources within your GCP/GKE environment. This console allows you to access your logs from a particular Cluster, Namespace, Node, and Pod.

GKE Console

GKE web console enables you to access to logs on individual pods actively running within a workload.

There is a filter option available to filter specific events, and a drop-down field to target specific severity of log events.

Logs provide a link to access **Logs Explorer** from a given pod to access the main logs explorer page for enhanced querying capabilities and other features.

Command-Line

The standard **kubectl** logs commands are supported in GKE. They provide actively running stdout logs from containers.

Example:

```
kubectl logs gvp-mcp-0 -n gvp -c fluentbit | more
```

```
mcooke@GEN-3HDH3: /mnt/c/Users/mcooke/PATS$ kubectl logs -n gvp gvp-mcp-0 -c fluentbit | more
[8] MCP.genesys.lbg.gvp.mcp.mcp.MCP.20211109_104655_624.log: [{"log":>,"2021-11-18T06:27:25.051 Int 50819 00640219-10000EA1 1405888777184 prompt_end done"}]
[1] MCP.genesys.lbg.gvp.mcp.mcp.MCP.20211109_104655_624.log: [{"log":>,"2021-11-18T06:27:25.051 Int 50836 00640219-10000EA1 1405888901000032 appl_end"}]
[2] MCP.genesys.lbg.gvp.mcp.mcp.MCP.20211109_104655_624.log: [ {"log":>,"2021-11-18T06:27:25.051 Int 50152 00640219-10000EA1 14058884950632 rtp_stats RTP 38192: Rx 0/0 lost 0 dropped 0 dec_err
o jitter 0, Tx 182/31384 enc_err 0"}]
[3] MCP.genesys.lbg.gvp.mcp.mcp.MCP.20211109_104655_624.log: [ {"log":>,"2021-11-18T06:27:25.053 Int 50801 00640219-10000EA1 14058825337664 incall_end aplend"}]
[4] MCP.genesys.lbg.gvp.mcp.mcp.MCP.20211109_104655_624.log: [ {"log":>,"2021-11-18T06:27:25.222 Int 50802 00640219-10000EA2 140588225337664 incall_initiated 0"}]
[5] MCP.genesys.lbg.gvp.mcp.mcp.MCP.20211109_104655_624.log: [ {"log":>,"2021-11-18T06:27:25.231 Int 50805 00640219-10000EA2 140588225337664 call_center 1-3813@10.198.68.76}3f05FE9E-9123-708
o-8378-944898006059 [NA/NA][NA/NA"]]
[6] MCP.genesys.lbg.gvp.mcp.mcp.MCP.20211109_104655_624.log: [ {"log":>,"2021-11-18T06:27:25.231 Int 50800 00640219-10000EA2 140588225337664 incall_begin sip:msml@127.0.0.1:5070:sip:vlegi@10.198
.68.76:1236 20211118216845593 [NA/NA][NA/NA"]}]
[6] MCP.genesys.lbg.gvp.mcp.mcp.MCP.20211109_104655_624.log: [ {"log":>,"2021-11-18T06:27:30.251 Int 50152 00640219-10000EA2 140588402948416 rtp_stats RTP 38192: Rx 0/0 lost 0 dropped 0 dec_err
o jitter 0, Tx 249/42828 enc_err 0"}]
[1] MCP.genesys.lbg.gvp.mcp.mcp.MCP.20211109_104655_624.log: [ {"log":>,"2021-11-18T06:27:30.251 Int 50801 00640219-10000EA1 140588225337664 incall_end usrend"}]
[0] MCP.genesys.lbg.gvp.mcp.mcp.MCP.20211109_104655_624.log: [ {"log":>,"2021-11-18T06:27:35.263 Int 50802 00640219-10000EA3 140588225337664 incall_initiated 0"}]
[1] MCP.genesys.lbg.gvp.mcp.mcp.MCP.20211109_104655_624.log: [ {"log":>,"2021-11-18T06:27:35.263 Int 50805 00640219-10000EA3 140588225337664 call_center 1-2132@10.198.65.79}8298697A-E371-062
-3-F407-0987671168E [Environment]VWrapDefault[NA/NA"]]
[2] MCP.genesys.lbg.gvp.mcp.mcp.MCP.20211109_104655_624.log: [ {"log":>,"2021-11-18T06:27:35.263 Int 50800 00640219-10000EA3 140588225337664 incall_begin sip:msml-dr@127.0.0.1:5060:sip:ipp@10.1
98.65.79:1236 20211118216845593 [NA/NA][NA/NA"]}]
[3] MCP.genesys.lbg.gvp.mcp.mcp.MCP.20211109_104655_624.log: [ {"log":>,"2021-11-18T06:27:35.263 Int 50153 00640219-10000EA1 14058880992416 appl_begin INIT_URL_file:///..../samples/ultra_wellngt0
..vxml [DEFAUTL]-file:///usr/local/genesys/mcp/config/defaultDefs.def.vxml]ANI-sip:ipp@10.198.65.79:1236 [DNIS=sip:msml-dr@127.0.0.1:5060] [PROTOCOLNAME=sip] [PROTOCOLVERSION=1.2] [CALLID=er-1-2132@10.198.65.79] [XML_U_TYPE=wellngt0
..vxml]"]
[4] MCP.genesys.lbg.gvp.mcp.mcp.MCP.20211109_104655_624.log: [ {"log":>,"2021-11-18T06:27:35.263 Int 50801 00640219-10000EA1 14058880992416 wf_logon_file:///..../samples/ultra_wellngt0..vxml"]]
```