



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

Operations

Monitoring Dashboards API

Learn about Cloud Monitoring API used to create dashboards, update existing dashboards or delete dashboards.

Related documentation:

•

RSS:

- [For private edition](#)

The Cloud Monitoring API provides a resource called `projects.dashboards` which offers a familiar set of methods: create, delete, get, list, and patch.

Create

POST `https://monitoring.googleapis.com/v1/{parent}/dashboards`

Delete

DELETE `https://monitoring.googleapis.com/v1/{name}`

GET

GET `https://monitoring.googleapis.com/v1/{name}`

List

GET `https://monitoring.googleapis.com/v1/{parent}/dashboards`

Patch

PATCH `https://monitoring.googleapis.com/v1/{dashboard.name}`

Here is an example:

`https://content-monitoring.googleapis.com/v1/projects//dashboards`

Errors in Logs Dashboard: Using this example, you can find errors in logs.

```
{
  "category": "CUSTOM",
  "displayName": "Errors in Logs Dashboard",
  "mosaicLayout": {
    "columns": 12,
    "tiles": [
```

```

{
  "height": 4,
  "widget": {
    "alertChart": {
      "name": "projects//alertPolicies/1502724684856373513"
    }
  },
  "width": 6,
  "xPos": 0,
  "yPos": 0
},
{
  "height": 4,
  "widget": {
    "title": "logging/user/Kubernetes-container-error-logs [SUM]",
    "xyChart": {
      "chartOptions": {
        "mode": "COLOR"
      },
      "dataSets": [
        {
          "minAlignmentPeriod": "60s",
          "plotType": "STACKED_BAR",
          "targetAxis": "Y1",
          "timeSeriesQuery": {
            "apiSource": "DEFAULT_CLOUD",
            "timeSeriesFilter": {
              "aggregation": {
                "alignmentPeriod": "60s",
                "crossSeriesReducer": "REDUCE_NONE",
                "perSeriesAligner": "ALIGN_RATE"
              },
              "filter": "metric.type=\\"logging.googleapis.com/user/Kubernetes-container-
error-logs\\" resource.type=\\"k8s_container\\"",
              "secondaryAggregation": {
                "alignmentPeriod": "60s",
                "crossSeriesReducer": "REDUCE_SUM",
                "groupByFields": [
                  "resource.label.\\"pod_name\\"
                ],
                "perSeriesAligner": "ALIGN_NONE"
              }
            }
          }
        }
      ],
      "timeshiftDuration": "0s",
      "yAxis": {
        "label": "y1Axis",
        "scale": "LINEAR"
      }
    }
  },
  "width": 6,
  "xPos": 6,
  "yPos": 0
},
{
  "height": 4,
  "widget": {
    "timeSeriesTable": {
      "dataSets": [
        {

```

```

    "minAlignmentPeriod": "60s",
    "tableDisplayOptions": {},
    "timeSeriesQuery": {
      "timeSeriesFilter": {
        "aggregation": {
          "alignmentPeriod": "60s",
          "crossSeriesReducer": "REDUCE_NONE",
          "perSeriesAligner": "ALIGN_RATE"
        },
        "filter": "metric.type=logging.googleapis.com/user/Kubernetes-container-
error-logs resource.type=k8s_container resource.label.namespace_name!=kube-
system",
        "secondaryAggregation": {
          "alignmentPeriod": "60s",
          "crossSeriesReducer": "REDUCE_MAX",
          "groupByFields": [
            "resource.label.pod_name"
          ],
          "perSeriesAligner": "ALIGN_MAX"
        }
      }
    }
  ],
  "title": "logging/user/Kubernetes-container-error-logs (filtered) [99TH PERCENTILE]"
},
"width": 6,
"xPos": 0,
"yPos": 4
}
]
}
}
}

```