

GENESYS

This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

Tenant Service Private Edition Guide

Tenant Service metrics and alerts

Contents

- 1 Metrics
- 2 Alerts

Find the metrics Tenant Service exposes and the alerts defined for Tenant Service.

Related documentation:

•

•

•

.

RSS:

For private edition

Service	CRD or annotations?	Port	Endpoint/Selector	Metrics update interval
Tenant Service	PodMonitor	15000	/metrics (http://:15000/metrics)	30 seconds (Applicable for any metric(s) that Tenant Service exposes. The update interval is not a property of the metric; it is a property of the optional PodMonitor that you can create.)

See details about:

- Tenant Service metrics
- Tenant Service alerts

Metrics

You can query Prometheus directly to see all the metrics that the Tenant Service exposes. The following metrics are likely to be particularly useful. Genesys does not commit to maintain other currently available Tenant Service metrics not documented on this page.

Metric and description	Metric details	Indicator of
tenant_service_health_level	Unit: N/A	Health

Metric and description	Metric details	Indicator of
Metric and description Health level of the tenant node. Values are -1 (fail), 0 (starting), 1 (degraded), 2 (pass). When the value is 2, the tenant Tenant Service node is fully functional. When the value is 1, the tenant might have issues with some of its internal functions and external dependencies, but is still capable of providing some services. When a value of 1 is reported, additional investigation is	Metric details Type: gauge Label: Sample value: 2	Indicator of
needed, via tenant logs, to troubleshoot and recover.		
A value of 0 or -1 indicates an inoperable node, either pending start or it has failed.		

Alerts

If you enable a Tenant PodMonitor to expose the Tenant health metric, then you can create a basic alert rule for the Tenant Service using a template like the following:

Enter your values where there are placeholders in the preceding template; the placeholders are:

•

Values are based on how you deployed tenant(s); in other words, what you used for override values.

No alerts are defined for Tenant Service.