



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

Voice Microservices Events and Models Reference

Releasing calls

12/19/2025

Contents

- 1 Release phase
- 2 Release from conference phase
- 3 Delete from conference phase

Learn about the standard processes by which calls are released.

Related documentation:

-
-
-

RSS:

- [For private edition](#)

For simplicity, the examples on this page use abbreviated attribute values. For example, ConnID **1**, which – in actual events – displays as ConnID>@metainformation>.

The following comments and abbreviations are used in the call models:

- OPT—Optional.
- DIAL—Might be a dialed number or is not present if Voice Microservices have no information about the other party.

Release phase

The following table describes the release phase.

Party A	Party B
Conversation	
Release (TReleaseCall)	
EventReleased ConnID 1 ThisDN A OtherDN B *OPT CallState OK	EventReleased ConnID 1 ThisDN B OtherDN A *OPT CallState OK

Release from conference phase

The following table describes the release from conference phase.

Party A	Party B	Party C

Conference		
	Release (TReleaseCall)	
EventPartyDeleted ConnID 1 ThisDN A OtherDN B OtherDNRole DeletedParty ThirdPartyDN B ThirdPartyDNRole DeletedBy CallState OK/Conferenced ^a	EventReleased ConnID 1 ThisDN B CallState OK	EventPartyDeleted ConnID 1 ThisDN C OtherDN B OtherDNRole DeletedParty ThirdPartyDN B ThirdPartyDNRole DeletedBy CallState OK/Conferenced ^a
Conversation		

a. If more than two parties remain in the conference call, **CallState** has a value of Conferenced; otherwise, **CallState** has a value of OK.

Delete from conference phase

The following table describes the release phase.

Party A	Party B	Party C
Conference		
Delete B (TDeleteFromConference)		
EventPartyDeleted ConnID 1 ThisDN A OtherDN B OtherDNRole DeletedParty ThirdPartyDN A ThirdPartyDNRole DeletedBy CallState OK/Conferenced ^a	EventReleased ConnID 1 ThisDN B CallState OK	EventPartyDeleted ConnID 1 ThisDN C OtherDN B OtherDNRole DeletedParty ThirdPartyDN A ThirdPartyDNRole DeletedBy CallState OK/Conferenced ^a
Conversation		

a. If more than two parties remain in the conference call, **CallState** has a value of Conferenced; otherwise, **CallState** has a value of OK.