



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

Voice Microservices Private Edition Guide

[Config Service metrics and alerts](#)

Contents

- 1 Metrics
- 2 Alerts

Find the metrics Config Service exposes and the alerts defined for Config Service.

Service	CRD or annotations?	Port	Endpoint/Selector	Metrics update interval
Config Service	Supports both CRD and annotations	9100	http://:9100/metrics	30 seconds

See details about:

- Config Service metrics
- Config Service alerts

Metrics

You can query Prometheus directly to see all the metrics that the Voice Config Service exposes. The following metrics are likely to be particularly useful. Genesys does not commit to maintain other currently available Config Service metrics not documented on this page.

Metric and description	Metric details	Indicator of
config_device_response Number of device responses for each request.	Unit: N/A Type: counter Label: location, tenant, request_type, status Sample value: 2	Traffic
config_tenant_response Number of Tenant responses for each request.	Unit: N/A Type: counter Label: location, request_type, status Sample value: 2	Traffic
config_node_get_response Number of Get responses for each request.	Unit: N/A Type: counter Label: Sample value:	Traffic
config_node_agent_response Number of agent responses for each request.	Unit: N/A Type: counter Label: Sample value:	Traffic
config_redis_state	Unit: N/A	Errors

Metric and description	Metric details	Indicator of
Current Redis connection state: -1 - error 0 - disconnected 1 - connected 2 - ready	Type: gauge Label: location, redis_cluster_name Sample value: 2	
service_version_info Displays the version of Voice Config Service that is currently running. In the case of this metric, the labels provide the important information. The metric value is always 1 and does not provide any information.	Unit: N/A Type: gauge Label: version Sample value: service_version_info{version="100.0.1000006"} 1	
config_health_level Health level of the config node: -1 - error 0 - fail 1 - degraded 2 - pass	Unit: N/A Type: gauge Label: Sample value: 2	Errors
config_healthcheck_generic_exception Generic error during health check.	Unit: N/A Type: gauge Label: Sample value: 0	

Alerts

The following alerts are defined for Config Service.

Alert	Severity	Description	Based on	Threshold
Redis disconnected for 5 minutes	Warning	<p>Actions:</p> <ul style="list-style-type: none"> If the alarm is triggered for multiple services, make sure there are no issues with Redis, then restart Redis. If the alarm is triggered only for the pod {{ \$labels.pod }}, check to see if there is an issue with the 	redis_state	Redis is not available for pod {{ \$labels.pod }} for 5 minutes.

Alert	Severity	Description	Based on	Threshold
		pod.		
Redis disconnected for 10 minutes	Critical	<p>Actions:</p> <ul style="list-style-type: none"> • If the alarm is triggered for multiple services, make sure there are no issues with Redis, then restart Redis. • If the alarm is triggered only for the pod {{ \$labels.pod }}, check to see if there is an issue with the pod. 	redis_state	Redis is not available for the pod {{ \$labels.pod }} for 10 minutes.
Pod Failed	Warning	<p>Actions:</p> <ul style="list-style-type: none"> • One of the containers in the pod has entered a failed state. Check the Kibana logs for the reason. 	kube_pod_status_phase	Pod failed {{ \$labels.pod }}.
Pod Unknown state	Warning	<p>Actions:</p> <ul style="list-style-type: none"> • If the alarm is triggered for multiple services, make sure there are no issues with the Kubernetes cluster. • If the alarm is triggered only for the pod {{ \$labels.pod }}, check to see whether the image is correct and if the container is starting up. 	kube_pod_status_phase	Pod {{ \$labels.pod }} is in Unknown state for 5 minutes.

Alert	Severity	Description	Based on	Threshold
Pod Pending state	Warning	<p>Actions:</p> <ul style="list-style-type: none"> If the alarm is triggered for multiple services, make sure the Kubernetes nodes where the pod is running are alive in the cluster. If the alarm is triggered only for the pod {{ \$labels.pod }}, check the health of the pod. 	kube_pod_status_phase	Pod {{ \$labels.pod }} is in Pending state for 5 minutes.
Pod Not ready for 10 minutes	Critical	<p>Actions:</p> <ul style="list-style-type: none"> If this alarm is triggered, check whether the CPU is available for the pods. Check whether the port of the pod is running and serving the request. 	kube_pod_status_ready	Pod {{ \$labels.pod }} is in NotReady state for 10 minutes.
Container restarted repeatedly	Critical	<p>Actions:</p> <ul style="list-style-type: none"> One of the containers in the pod has entered a failed state. Check the Kibana logs for the reason. 	kube_pod_container_start_time	Container {{ \$labels.container }} was restarted 5 or more times total within 15 minutes.
Pod memory greater than 65%	Warning	<p>High memory usage for pod {{ \$labels.pod }}.</p> <p>Actions:</p> <ul style="list-style-type: none"> Check whether 	container_memory_working_set_bytes kube_pod_container_resource_requests_memory_bytes	Container {{ \$labels.container }} memory usage exceeded 65% for 5 minutes.

Alert	Severity	Description	Based on	Threshold
		<p>the horizontal pod autoscaler has triggered and if the maximum number of pods has been reached.</p> <ul style="list-style-type: none"> • Check Grafana for abnormal load. • Collect the service logs; raise an investigation ticket. 		
Pod memory greater than 80%	Critical	<p>Critical memory usage for pod {{ \$labels.pod }}.</p> <p>Actions:</p> <ul style="list-style-type: none"> • Check whether the horizontal pod autoscaler has triggered and if the maximum number of pods has been reached. • Check Grafana for abnormal load. • Restart the service. • Collect the service logs; raise an investigation ticket. 	Container {{ \$labels.container }}.memory_usage_exceeded_80_percent_for_kube_pod_container_resource_requests_memory_bytes	
Pod CPU greater than 65%	Warning	<p>High CPU load for pod {{ \$labels.pod }}.</p> <p>Actions:</p> <ul style="list-style-type: none"> • Check whether the horizontal 	Container {{ \$labels.container }}.cpu_usage_exceeded_65_percent_for_container_spec_cpu_period	

Alert	Severity	Description	Based on	Threshold
		<p>pod autoscaler has triggered and if the maximum number of pods has been reached.</p> <ul style="list-style-type: none"> • Check Grafana for abnormal load. • Collect the service logs; raise an investigation ticket. 		
Pod CPU greater than 80%	Critical	<p>Critical CPU load for pod {{ \$labels.pod }}.</p> <p>Actions:</p> <ul style="list-style-type: none"> • Check whether the horizontal pod autoscaler has triggered and if the maximum number of pods has been reached. • Check Grafana for abnormal load. • Restart the service. • Collect the service logs; raise an investigation ticket. 	container_cpu_usage_seconds_total{container_labels.container_spec_cpu_period} - container_spec_cpu_period	Container {{ \$labels.container }} CPU usage exceeded 80% for 5 minutes.